

ADE-208-417(Z)

HVC357

Variable Capacitance Diode for VCO

HITACHI

Rev. 0
Nov. 1995


Features

- Low series resistance. ($r_s=0.35\Omega$ max)
- Ultra small Flat Package (UFP) is suitable for surface mount design.

Ordering Information

Type No.	Laser Mark	Package Code
HVC357	J	UFP

Outline



Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Value	Unit
Reverse voltage	V_R	10	V
Junction temperature	T_j	125	°C
Storage temperature	T_{stg}	-55 to +125	°C

Electrical Characteristics (Ta = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse current	I_{R1}	—	—	10	nA	$V_R = 10\text{ V}$
	I_{R2}	—	—	100		$V_R = 10\text{ V}, T_a = 60\text{ °C}$
Capacitance	C_1	19.5	—	23.5	pF	$V_R = 1\text{ V}, f = 1\text{ MHz}$
	C_2	14.3	—	17.6		$V_R = 2\text{ V}, f = 1\text{ MHz}$
Capacitance ratio	n	1.3	—	—	—	C_1 / C_2
Series resistance	r_s	—	—	0.35	Ω	$V_R = 1\text{ V}, f = 470\text{ MHz}$




Fig.1 Reverse current Vs. Reverse voltage




Fig.2 Capacitance Vs. Reverse voltage




Fig.3 Series resistance Vs. Reverse voltage






Fig.4 Linearity factor Vs. Reverse voltage

Package Dimensions

Unit: mm



- 1 Cathode
- 2 Anode

HITACHI Code	UFP
JEDEC Code	—
EIAJ Code	SC-79
Weight (g)	0.0016