


FM DEMODULATION IC FOR BROADCASTING SATELLITE RECEIVER

The TA8804F combines the necessary function on a single monolithic integrated circuit to modulate FM signal of the 2nd IF of DBS.

FEATURES


- 5V Power Supply
- 2nd IF AGC Amp
- dB-Linear Signal Level Amp
- PLL FM Detector
- Keyed AFT



Weight : 0.63g (Typ.)

TA8804F

BLOCK DIAGRAM







TOSHIBA

TECHNICAL DATA




TA8804F

TERMINAL FUNCTION

| PIN No. | PIN NAME | FUNCTION | INTERFACE CIRCUIT |
|---------|----------------------------------|---|--|
| 1 | Keyed Pulse Input | <p>It clamps at the pulse peak and generates the reference level. The input impedance is $3k\Omega$.</p> <ul style="list-style-type: none"> If any keyed pulse input, Keyed pulse : low level sample state Keyed pulse : high level hold state If no keyed pulse input, sample state at all time |  |
| 2 3 | Detect Output | It outputs the detection output through a low-pass filter of 30MHz cut off frequency using an emitter follower. |  |
| 4 5 | Video Amplifier Level Adjustment | <p>It controls the level adjustment by varying the emitter resistance of a differential amplifier. If the resistance between pins 4 and 5 is reduced the output will be greater, however, since the output dynamic range is narrow the output level should be used in the range of lower than $0.7V_{p-p}$.</p> |  |
| 6 7 | Loop Filter | <p>The output impedance is 200Ω. In the application circuit, $\omega \approx 174\text{MHz}$, $\xi \approx 0.81$.</p> |  |

INTEGRATED CIRCUIT
TOSHIBA **TECHNICAL DATA**

TA8804F

| PIN No. | PIN NAME | FUNCTION | INTERFACE CIRCUIT |
|---------|---------------------------------|--|--|
| 8 | GND1 | It is the GND of VCO circuit blocks that are VCO (pins 9, 10, 12), loop filter (pins 6, 7), video amplifier (pins 4, 5) AFT system (pins 1, 23, 24, 25, 26, 27, 28) and S/H (pins 29, 30). | |
| 9 10 | VCO Coil | It is the VCO using variations in internal impedance of diode for control voltage from mixer. Use a UJ characteristic for the capacitor of the external tank circuit to correct the internal temperature drift. |  |
| 12 | VCO Temperature Compensate Bias | The VCO bias is composed of a synthesis of bias in proportion to V_{BE} and V_T of transistor, and this terminal generates a bias proportioned to the V_{BE} . If the external resistance reduced, the VCO sensitivity will rise. |  |
| 13 | 2nd AGC Adjustment | It changes the input level for a AGC detector. It adjusts by adding the direct current offset to pins 14 and 15. The variation width of about 8dB can be added. internal bias is 2.5V. |  |

TOSHIBA




TECHNICAL DATA

TA8804F

| PIN No. | PIN NAME | FUNCTION | INTERFACE CIRCUIT |
|----------|--------------------------|---|-------------------|
| 14 15 | 2nd AGC Filter | It generates the AGC voltage by filtering the 402.78MHz (479.5MHz) IF signal by means of an internal resistance and an external condenser. If applying the V _{CC} to pin 15, the AGC will be minimum gain and the VCO oscillates at free-running frequency. | |
| 16 | 1st AGC Slice Adjustment | It sets the input level threshold for generating the control signal to lower gain from the IC to the 2nd converter of front stage when excessive input. Even if the 2nd AGC adjustment varies, the 1st AGC adjustment point hardly changes. The internal bias is 2.5V. | |
| 17 | 1st AGC Filter | It outputs by comparing with the AGC and 1st AGC slice level adjustment voltages. This comparator is constructed by the active load type high gain amplifier and determines its response by a capacitor connected to this terminal. | |
| 18 | 1st AGC Control | It outputs the control voltage using an emitter follower (active low level). The internal current sink has only 25μA. | |

INTEGRATED CIRCUIT
TOSHIBA **TECHNICAL DATA**

TA8804F

| PIN No. | PIN NAME | FUNCTION | INTERFACE CIRCUIT |
|----------|------------------------|---|--|
| 19 | Signal Level Out | <p>It outputs the AGC voltage by doing logarithm <-> linear conversion. In the TA8804F the level detection can be carried out even after the 1st AGC is effective and input is reduced using the 1st AGC output.</p> |  |
| 20 22 | 2nd IF In | <p>The IF amplifier constructed by the 3-step series connection of variable gm type gain control, of which the maximum gain is 47dB and minimum gain - 8dB. In order to prevent a sneak of radio frequency all the circuits are balance-connected. Therefore, the differential combination is also desirable for the IC input. The internal bias is 2.0V and input impedance 1kΩ.</p> |  |
| 23 | AFT Output (Analog) | <p>It outputs by integrating the detection output by means of pin 27 and 28 filters, doing center adjustment and multiplying about five times as much.</p> |  |

TOSHIBA


TECHNICAL DATA

| PIN No. | PIN NAME | FUNCTION | INTERFACE CIRCUIT |
|----------|-------------------------|--|-------------------|
| 24 25 | AFT Output (Digital) | It outputs by converting the analog AFT output to binary with a comparator. In the case of center detection, the each output will be high level. The width of dead zone is determined by the internal threshold and VCO sensitivity, that cannot be adjusted externally. | |
| 26 | AFT Center Adjustment | It moves the AFT center frequency in the width of 10MHz and absorbs the center gap caused by dispersion of each AFT circuit. | |
| 27 28 | AFT Filter | It constructs a filter whose cut off frequency is less than 1Hz (capacitor : 0.7Hz at 0.1μF) with an internal 1.1MΩ resistance and external condenser. | |
| 29 30 | Hold Capacitor | Sample and hold by charge / discharging the condenser using the switching signal regenerated by keyed pulse. | |

MAXIMUM RATINGS (Ta = 25°C)

| CHARACTERISTIC | SYMBOL | RATING | UNIT |
|-----------------------|---------------------|------------|------|
| Power Supply Voltage | V _{CC} MAX | 6.0 | V |
| Power Dissipation | P _D MAX | 1000 | mW |
| Operation Temperature | T _{opr} | -20~75 | °C |
| Storage Temperature | T _{stg} | -55~150 | °C |
| Lead Temperature | — | 260°C, 10s | |

Recommended assembly method : Recommended temperature profile of reflow soldering of far and medium infrared rays



RECOMMENDED POWER SUPPLY VOLTAGE

| PIN No. | PIN NAME | MIN. | TYP. | MAX. | UNIT |
|---------|-----------------|------|------|------|------|
| 11 | V _{CC} | 4.5 | 5.0 | 5.5 | V |

TOSHIBA

TECHNICAL DATA

TA8804F

ELECTRICAL CHARACTERISTICS

DC CHARACTERISTICS (Unless otherwise specified, $V_{CC} = 5.0V$, $T_a = 25^\circ C$)

| CHARACTERISTIC | SYMBOL | TEST CIR-CUIT | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|------------------------------------|------------|---------------|----------------|--------------------------|-------|------|--------|
| Supply Current | I_{CC} | 1 | — | 55 | 80 | 105 | mA |
| Terminal Voltage | | 1 | — | 2.0 | 2.5 | 3.0 | V |
| Pin 1 | V_1 | | — | 1.9 | 2.4 | 2.9 | |
| Pin 2 | V_2 | | — | 1.9 | 2.4 | 2.9 | |
| Pin 3 | V_3 | | — | 0.8 | 1.3 | 1.8 | |
| Pin 4 | V_4 | | — | 0.8 | 1.3 | 1.8 | |
| Pin 5 | V_5 | | — | 1.7 | 2.1 | 2.5 | |
| Pin 6 | V_6 | | — | 1.7 | 2.1 | 2.5 | |
| Pin 7 | V_7 | | — | 2.4 | 2.8 | 3.2 | |
| Pin 9 | V_9 | | — | 2.4 | 2.8 | 3.2 | |
| Pin 10 | V_{10} | | — | 0.4 | 0.7 | 1.0 | |
| Pin 12 | V_{12} | | — | 2.3 | 2.5 | 2.7 | |
| Pin 13 | V_{13} | | — | — | 3.6 | — | |
| Pin 14 | V_{14} | | — | — | 3.6 | — | |
| Pin 15 | V_{15} | | — | 2.1 | 2.5 | 2.9 | |
| Pin 16 | V_{16} | | — | Pin 17 : $1k\Omega$ -GND | 1.0 | 1.3 | |
| Pin 18 | V_{18h} | | — | Pin 17 : V_{CC} | 3.9 | 4.3 | 4.7 |
| | V_{18l} | | — | — | 1.5 | 2.0 | 2.5 |
| Pin 20 | V_{20} | | — | — | 1.5 | 2.0 | 2.5 |
| Pin 22 | V_{22} | | — | — | — | 2.3 | 2.8 |
| Pin 27 | V_{27} | | — | — | — | 2.3 | 2.8 |
| Pin 28 | V_{28} | | — | — | 1.8 | 2.3 | 2.8 |
| Pin 29 | V_{29} | | — | — | 1.8 | 2.3 | 2.8 |
| Pin 30 | V_{30} | | — | — | — | — | |
| Pin 2, 3 Acceptable Output Current | I_2, I_3 | 1 | — | — | -1.0 | — | 6.0 mA |
| 1'st AGC Output Current | I_{18} | 1 | — | — | -0.02 | — | 6.0 mA |

INTEGRATED CIRCUIT

TOSHIBA

TECHNICAL DATA

TA8804F

AC CHARACTERISTICS

| CHARACTERISTIC | SYMBOL | TEST CIRCUIT | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|---|-----------------------|---------------------|---|----------|-----------|-----------|---------------------|
| IF Input Frequency Range | f_{in} | — | — | 350 | 400 | 550 | MHz |
| IF Input Level Range | v_{in} | — | — | -60 | — | -10 | dBmW (50Ω) |
| 1st AGC Shoulder Level Range | AGC MAX | 2 | (Note 1) | — | -20 | -10 | dBmW (50Ω) |
| 1st AGC Control Sensitivity | ΔAGC | 2 | (Note 2) | 1.0 | 3.5 | 6.0 | V / dB |
| Signal Level Sensitivity | $\Delta V / \Delta v$ | 2 | (Note 3) | 10 | 35 | 60 | mV / dB |
| VCO Conversion Sensitivity | β | 2 | Converting to output rate Pin 4, 5 : open / (Note 4) | — | 110 | 130 | MHz / V |
| VCO Temperature Drift | Δf_{Ta} | 2 | $Ta = -10 \sim 65^\circ C$ / (Note 5) | — | ± 1.0 | ± 2.5 | MHz |
| PLL Lock Range | f_L | 2 | (Note 6) | ± 25 | ± 30 | — | MHz |
| PLL Capture Range | f_{ca} | 2 | (Note 6) | ± 25 | ± 30 | — | MHz |
| Demodulation Output Level | V_{out} | 2 | $\Delta f = 10 \text{MHz}_{\text{p-p}}$ / (Note 7) | 0.15 | 0.26 | 0.40 | V _{p-p} |
| Video Amplifier Variable Width | $V_{outS/5}$ | 2 | Pin 4, 5 : short, $5k\Omega$ / (Note 8) | 10 | 14 | — | dB |
| Demodulation Output Amplitude Frequency Characteristics 1 | V_{outA1} | 2 | $f = 0.2 \sim 4 \text{MHz}$ / (Note 9) | — | — | ± 0.5 | dB |
| Demodulation Output Amplitude Frequency Characteristics 2 | V_{outA2} | 2 | $f = 4 \sim 9 \text{MHz}$ / (Note 9) | — | — | ± 2 | dB |
| Group Delay Characteristics 1 | τ_{pd1} | 2 | $f = 0.2 \sim 4 \text{MHz}$ / (Note 9) | — | — | ± 10 | ns |
| Group Delay Characteristics 2 | τ_{pd2} | 2 | $f = 4 \sim 9 \text{MHz}$ / (Note 9) | — | — | ± 40 | ns |
| AFT Sensitivity | $\Delta f / \Delta V$ | 2 | (Note 12) | 2.4 | 3.2 | 4.0 | MHz / V |
| S/H Sample Speed | Δf_{spl} | 2 | Converting to input frequency rate / (Note 10) | 0.1 | 0.2 | — | MHz / μs |
| Keyed AFT Input Range | V_1 | 2 | — | 0.35 | 0.5 | 0.65 | V _{p-p} |
| Keyed AFT Input Frequency | T_1 | 2 | (Note 11) | 8.0 | 16.7 | 50 | ms |
| AFT Width of Dead Zone | V_{DEAD} | 2 | (Note 13) | 250 | 340 | 400 | kHz |
| Digital AFT Voltage Low Level | V_{20L} | 2 | (Note 13) | — | 0.3 | 0.5 | V |
| DG | DG | application circuit | APL 90% / (Note 14) | — | ± 2.0 | ± 5.0 | % |

TOSHIBA
INTEGRATED CIRCUIT
TECHNICAL DATA

TA8804F

| CHARACTERISTIC | SYMBOL | TEST CIRCUIT | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|--------------------|--------|---------------------|--------------------------------|------|------|------|------|
| DP | DP | application circuit | APL 90% / (Note 14) | — | ±2.0 | ±5.0 | ° |
| Inter-Modulation 2 | IM2 | application circuit | 2.15MHz beat level / (Note 15) | 40 | 45 | — | dB |
| Inter-Modulation 3 | IM3 | application circuit | 1.43MHz beat level / (Note 15) | 40 | 50 | — | dB |
| Video Output S/N | S/NSAT | application circuit | C/N = ∞ | 48 | 51 | — | dB |

MEASUREMENT CONDITION

(Note 1) 1st AGC Shoulder Level Range : AGCMAX

F=402.78MHz input level $v_{in}=0$ to -40dBmW (50Ω) to pin 20. Measure v_{in} that pin 18 voltage is lower than 4V by opening pin 16 and raising v_{in} .

(Note 2) 1st AGC Control Sensitivity : ΔAGC

Input f=402.78MHz $v_{in}=0 \sim -40\text{dBmW}$ (50Ω) to pin 20. Calculate v_{in} that pin 18 voltage is 4V / 1V (as v_{in1} , v_{in2}), using the equation below.

$$\Delta AGC = -3 / (v_{in1} - v_{in2}) \text{ V/dB}$$

(Note 3) Signal Level Sensitivity : $\Delta V/\Delta v$

Measure each output voltage of pin 19 at $v_{in} = -40, -60\text{dBmW}$ (50Ω)

$$\Delta V/\Delta v = (V - 60 - V - 40) / 20 \text{ mV/dB}$$

(Note 4) VCO Conversion Sensitivity : β

Input mainly f=402.78MHz and sweep $\pm 5\text{MHz}$, $v_{in} = -30\text{dBmW}$ (50Ω) to pin 20.

Calculate $\beta = 10 / (V_{det+5} - V_{det-5})$ and multiply the gain portion (2.66) of video amplifier when outputting a direct current voltage to pin 3 at 407.78MHz, 397.78MHz as V_{det+5} and V_{det-5} each.

(Note 5) VCO Temperature Drift : Δf_{Ta}

Short pin 6 and 7, and connect pin 14 to GND.

Measure the VCO frequency at ambient temperature $T_a = 25^\circ\text{C}, -10^\circ\text{C} +65^\circ\text{C}$ and calculate how much changes from 25°C . (read out the VCO leakage output by spectrum analyzer.)

(Note 6) PLL Lock Range : f_L , Capture Range : f_{ca}

Measure the range that synchronizes with VCO by putting pin 20 input frequency away from the free-running frequency.

(Note 7) Demodulation Output Level : V_{out}Input pin 20 f = 402.78MHz, f_m = 100kHz, Δf = 10MHz p-p, v_{in} = -30dBmW (50Ω)

Open pin 4 and 5 and measure the output level of pin 3.

(Note 8) Video Amplifier Variable Width : V_{outS}, V_{out5}Input pin 20 f = 402.78MHz, f_m = 100kHz, Δf = 10MHz p-p, v_{in} = -30dBmW (50Ω)

Measure the variation of video output by shorting between pin 4 and 5 and connecting a 5kΩ resistance.


(Note 9) Demodulation Output level Width, Group Delay Characteristics : V_{outA}, τ_{pd}Input pin 20 f = 402.78MHz, f_m = 100kHz, 60Hz to 4MHz to 9MHz, Δf = 5MHz p-p, v_{in} = -30dBmW (50Ω)

Compare to the value at 100kHz by opening pin 4 and 5, and measuring the output level and group delay of pin 3.


(Note 10) S/H Sample Speed : Δf_{spl}

Input the signal 1 below for a modulation signal. Input the signal 2 below to pin 1.

Observe the differential voltage waveform between pin 29 and 30, and measure the slew rate in the sampling period.

(Note 11) Keyed Pulse Allowable Period : T₁

Input the signal below to pin 1 and open pin 27 and 28. Observe the pin 23 output and change f so as to be 2.5V voltage.



Measure the frequency range in which a 2kHz sine wave does not output to pin 23, by changing the signal 3 period.

If the sample-hold circuit malfunctions, the 2kHz sine wave will be outputted from pin 23.

INTEGRATED CIRCUIT
TOSHIBA **TECHNICAL DATA**

TA8804F

(Note 12) AFT Sensitivity : $\Delta f / \Delta V_{23}$

Input pin 20 $f = 402.78\text{MHz} \pm 1\text{MHz}$, $v_{in} = -30\text{dBmW}$ (50Ω)


Adjust f so that pin 23 output will be 2.5V. By moving f up. and down, calculate each frequency as f_H , f_L when pin 23 voltage varies 0.5V using the following equation.

$$\Delta f / \Delta V_{23} = f_H - f_L (\text{MHz/V})$$

(Note 13) AFT Digital Output Width of Blind Sector : f_{DEAD}

Input pin 20 $f = 402.78\text{MHz} \pm 5\text{MHz}$, $v_{in} = -30\text{dBmW}$ (50Ω)

Measure the input frequency range in which both pin 24 and 25 become high level, by sweeping f .



(Note 14) DG, DP

Input pin 20 $f = 402.78\text{MHz} \pm 5\text{MHz}$, $v_{in} = -30\text{dBmW}$ (50Ω), $\Delta f = 17\text{MHz}_{\text{p-p}}$. Gray level video signal (APL : 10~90%)... Pre-emphasis-on

(Note 15) IM2, IM3

Input pin 20 $f = 402.78\text{MHz} \pm 5\text{MHz}$, $v_{in} = -30\text{dBmW}$ (50Ω), $\Delta f = 17\text{MHz}_{\text{p-p}}$. Color subcarrier (3.579MHz), Sound subcarrier (5.7272MHz) ...

Observe the frequency component outputting to the screen output pin (pin 3) through the video gate of a video noise meter by spectrum analyzer, and measure the level difference between 3.579MHz component and 2.15MHz, 1.43MHz components.

JAN-09-02 11:22

FROM-TOSHIBA ELECTRONIC


+9498593963

T-473 P.15/17 F-966


TOSHIBA
INTEGRATED CIRCUIT
TECHNICAL DATA

TA8804F**TEST CIRCUIT 1**

DC characteristics

**TEST CIRCUIT 2**


AC characteristics



TOSHIBA

TECHNICAL DATA

TA8804F



APPLICATION CIRCUIT

(2'nd IF : 402MHz)

TA8804F - 15

TA8804F - 15

1996-4-22

TOSHIBA CORPORATION

JAN-09-02 11:23

FROM-TOSHIBA ELECTRONIC

+9498593963


T-473 P.17/17 F-966

TOSHIBA INTEGRATED CIRCUIT
TECHNICAL DATA

TA8804F

OUTLINE DRAWING
SSOP30-P-375

Unit : mm



Weight : 0.63g (Typ.)