

[查询IRF7422D2供应商](#)

捷多邦，专业PCB打样工厂，24小时加急出货

## HEXFET® Power MOSFETs

INTERNATIONAL RECTIFIER



[www.irf.com](http://www.irf.com)

ANNIVERSARY 1947-1997

Part Number	V <sub>(BR)DSS</sub> Drain-to-Source Breakdown Voltage (V)	R <sub>D(on)</sub> On-State Resistance (Ω)	I <sub>D</sub> Continuous 25°C (A)	I <sub>D</sub> Continuous 70° (A)	R <sub>θ</sub> Max. Thermal Resistance <sup>1</sup> (°C/W)	P <sub>D</sub> Max. Power Dissipation <sup>1</sup> (W)	VFM Forward Voltage Drop @ TJ = 25°C	Fax on Demand Number	Case Outline Key
-------------	---	--	--	---	--	--	---	----------------------------	------------------------

### Surface Mount Packages

FETKY Micro8

### FETKY (Co-packaged HEXFET Power MOSFET and Schottky Diode)

#### N-Channel

IRF7521D1	20	0.135	2.4	1.9	100	1.25	0.50 @ 1.0A	91646
IRF7523D1	30	0.135	2.4	1.9	100	0.8	0.50 @ 1.0A	91647

#### P-Channel

IRF7524D1	-20	0.27	-1.7	-1.4	100	0.8	0.50 @ 1.0A	91648
IRF7526D1	-30	0.27	-1.7	-1.4	100	0.8	0.50 @ 1.0A	91649

<sup>1</sup> Measured at ambient for Micro8 and SO-8 package styles. All others measured at case.



Illustrations not to scale

Micro8

SO-8

D<sup>2</sup>-Pak

TO-220AB

# HEXFET® Power MOSFETs



[www.irf.com](http://www.irf.com)

Part Number	V <sub>(BR)DSS</sub> Drain-to-Source Breakdown Voltage (V)	R <sub>DS(on)</sub> On-State Resistance (Ω)	I <sub>D</sub> Continuous Drain Current 25°C (A)	I <sub>D</sub> Continuous Drain Current 70° (A)	R <sub>θ</sub> Max. Thermal Resistance <sup>1</sup> (°C/W)	P <sub>D</sub> Max. Power Dissipation <sup>1</sup> (W)	VFM Forward Voltage Drop @ TJ = 25°C	Fax on Demand Number	Case Outline Key
-------------	---	---	---	--	--	--	---	----------------------------	------------------------

## Surface Mount Packages

FETKY SO-8

### FETKY (Co-packaged HEXFET Power MOSFET and Schottky Diode)

#### N-Channel

<b>IRF7421D1</b>	30	0.035	4.1	3.3	50	1.0	0.50 @ 1.0A	91411	H5
<b>IRF7422D2</b>	-20	0.09	-2.9	-2.3	50	1.0	0.57 @ 3.0A	91412	

#### P-Channel

<b>IRF7321D2</b>	-30	0.058	-4.9	-3.9	62.5	2.0	0.57 @ 3.0A	91667	H5
------------------	-----	-------	------	------	------	-----	-------------	-------	----

<sup>1</sup> Measured at ambient for Micro8 and SO-8 package styles. All others measured at case.



Illustrations not to scale



# HEXFET® Power MOSFETs



[www.irf.com](http://www.irf.com)

Part Number	V <sub>(BR)DSS</sub> Drain-to-Source Breakdown Voltage (V)	R <sub>D(on)</sub> On-State Resistance (Ω)	I <sub>D</sub> Continuous Drain Current 25°C (A)	I <sub>D</sub> Continuous Drain Current 100° (A)	R <sub>θ</sub> Max. Thermal Resistance <sup>1</sup> (°C/W)	P <sub>D</sub> Max. Power Dissipation <sup>1</sup> (W)	Fax on Demand Number	Case Outline Key
-------------	---	--	---	---	--	--	-------------------------------	------------------------

## Surface Mount Packages

D2Pak

### FETKY (Co-packaged HEXFET Power MOSFET and Schottky Diode): Logic Level

N-Channel

IRL3103D1S	30	0.014	54	34	1.8	3.1	91558	H10
------------	----	-------	----	----	-----	-----	-------	-----

<sup>1</sup> Measured at ambient for Micro8 and SO-8 package styles. All others measured at case.



Illustrations not to scale

input

control

switch

output

distribution

# HEXFET® Power MOSFETs



[www.irf.com](http://www.irf.com)

Part Number	V <sub>(BR)DSS</sub> Drain-to-Source Breakdown Voltage (V)	R <sub>D(on)</sub> On-State Resistance (Ω)	I <sub>D</sub> Continuous Drain Current 25°C (A)	I <sub>D</sub> Continuous Drain Current 100° (A)	R <sub>θ</sub> Max. Thermal Resistance <sup>1</sup> (°C/W)	P <sub>D</sub> Max. Power Dissipation <sup>1</sup> (W)	Fax on Demand Number	Case Outline Key
-------------	---	--	---	---	--	--	-------------------------------	------------------------

## Through-Hole Packages

TO-220AB

**FETKY (Co-packaged HEXFET Power MOSFET and Schottky Diode):  
Logic Level**

N-Channel

IRL3103D1	30	0.014	54	34	1.8	2	91608	H12
-----------	----	-------	----	----	-----	---	-------	-----

<sup>1</sup> Measured at ambient for Micro8 and SO-8 package styles. All others measured at case.



Illustrations not to scale

input

control

switch

output

distribution