

<b>SANYO</b>	No.2483A	2SC4162
	NPN Triple Diffused Planar Type Silicon Transistor	
SWITCHING REGULATOR APPLICATIONS		

**Features**

- . High breakdown voltage, high reliability
- . Fast switching speed ( $t_f=0.1\mu s$  typ)
- . Wide ASO
- . Adoption of MBIT process
- . Micaless package facilitating mounting

**Absolute Maximum Ratings at  $T_a=25^\circ C$**

			unit
Collector-to-Base Voltage	$V_{CB0}$	500	V
Collector-to-Emitter Voltage	$V_{CEO}$	400	V
Emitter-to-Base Voltage	$V_{EBO}$	7	V
Collector Current	$I_C$	10	A
Peak Collector Current	$i_{cp}$	$PW \leq 300\mu s, \text{duty cycle} \leq 10\%$	A
Collector Dissipation	$P_C$	$T_c=25^\circ C$	35 W
Junction Temperature	$T_j$	150	$^\circ C$
Storage Temperature	$T_{stg}$	-55 to +150	$^\circ C$


**Electrical Characteristics at  $T_a=25^\circ C$**

			min	typ	max	unit
Collector Cutoff Current	$I_{CBO}$	$V_{CB}=400V, I_E=0$			10	$\mu A$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB}=5V, I_C=0$			10	$\mu A$
DC Current Gain	$h_{FE1}$	$V_{CE}=5V, I_C=1.6A$	15*		50*	
	$h_{FE2}$	$V_{CE}=5V, I_C=8A$	10			
	$h_{FE3}$	$V_{CE}=5V, I_C=10mA$	10			
Gain-Bandwidth Product	$f_T$	$V_{CE}=10V, I_C=1.6A$		20		MHz
Output Capacitance	$c_{ob}$	$V_{CB}=10V, f=1MHz$		120		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C=6A, I_B=1.6A$			0.8	V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C=6A, I_B=1.6A$			1.5	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C=1mA, I_E=0$	500			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C=5mA, R_{BE}=\infty$	400			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E=1mA, I_C=0$	7			V

Continued on next page.


**Switching Time Test Circuit**

$PW=20\mu s, \text{duty factor} \leq 1\%$



Unit (Resistance :  $\Omega$ , Capacitance : F)

**Package Dimensions 2041 (unit:mm)**



E: Emitter  
C: Collector  
B: Base

SANYO: TO220ML









2SC4162




Continued from preceding page.

		$I_C=4.5A, I_{B1}=0.45A,$ $I_{B2}=-1.8A, L=500\mu H, \text{clamped}$	min.	typ	max	unit
C-E Sustain Voltage	$V_{CEX(sus)}$		400			V
Turn-on Time	$t_{on}$	$I_C=7A, I_{B1}=1.4A, I_{B2}=2.8A,$ $R_L=28.6\text{ohms}, V_{CC}=200V$			0.5	$\mu s$
Storage Time	$t_{stg}$	" "			2.5	$\mu s$
Fall Time	$t_f$	" "			0.3	$\mu s$

\*: The  $h_{FE1}$  of the 2SC4162 is classified as follows. When specifying the  $h_{FE1}$  rank, specify two ranks or more in principle.

15	L	30	20	M	40	30	N	50
----	---	----	----	---	----	----	---	----





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.