

Ordering number : EN4863

CMOS LSI



LC7536R

High Breakdown Voltage Serial Control Electronic Volume Control

Overview

The LC7536R is an electronic volume control IC that implements volume and balance functions with a minimum number of external components.


Features

- The LC7536R is controlled by a 3-wire (DI, CL and CE) serial data control scheme that can be shared with other ICs. Up to two LC7536Rs can be used on the same bus by using the S (select) pin.
- Eighty positions in 1 dB steps plus mute ($-\infty$), maximum attenuation is over 80 dB
- Input impedance (5 dB inputs): 47 k Ω (typical)
- High breakdown voltage: ± 16 V

Package Dimensions

unit: mm

3047A-DIP30S



Specifications

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$, $V_{SS} = 0$ V

Parameter	Symbol	Conditions	Ratings	Unit
Maximum supply voltage	V_{DD} max	$V_{EE} \leq V_{SS} < V_{CC} < V_{DD}$	V_{SS} to $V_{SS} + 18$	V
	V_{EE} max	$V_{EE} \leq V_{SS} < V_{CC} < V_{DD}$	$V_{SS} - 18$ to V_{SS}	V
	V_{CC} max	$V_{EE} \leq V_{SS} < V_{CC} < V_{DD}$	V_{SS} to $V_{SS} + 7$	V
Input voltage	V_{I1}	CL, DI, CE	0 to $V_{DD} + 0.3$	V
	V_{I2}	IN1, IN2	$V_{EE} - 0.3$ to $V_{DD} + 0.3$	V
	V_{I3}	S	$V_{CC} - 0.3$ to $V_{DD} + 0.3$	V
Allowable power dissipation	P_d max	$T_a \leq 75^\circ\text{C}$	250	mW
Operating temperature	T_{opr}		-30 to +75	$^\circ\text{C}$
Storage temperature	T_{stg}		-40 to +125	$^\circ\text{C}$

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.



LC7536R


Allowable Operating Ranges at Ta = 25°C, VSS = 0 V

Parameter	Symbol	Conditions	min	typ	max	Unit
Supply voltage	V _{DD}		V _{CC} + 4.5		16	V
	V _{EE}		-16		0	V
	V _{CC}		4.5	5	5.5	V
Input high level voltage	V _{IH1}	CL, DI, CE	0.8 V _{CC}		V _{CC}	V
Input low level voltage	V _{IL1}	CL, DI, CE	V _{SS}		0.2 V _{CC}	V
Input high level voltage	V _{IH2}	S	$0.8 \times (V_{DD} - V_{CC}) + V_{CC}$		V _{DD}	V
Input low level voltage	V _{IL2}	S	V _{CC}		$0.2 \times (V_{DD} - V_{CC}) + V_{CC}$	V
Input pulse width	t _{øw}	CL	1			µs
Setup time	t _{set up}	CL, DI, CE	1			µs
Hold time	t _{hold}	CL, DI, CE	1			µs
Operating frequency	f _{opg}	CL			500	kHz
Input signal amplitude	V _{IN}	IN1, IN2	V _{EE}		V _{DD}	V
Input leakage current	I _{IN}	CL, DI, CE, S	-10		+10	µA

Electrical Characteristics at Ta = 25°C, VSS = 0 V

Parameter	Symbol	Conditions	min	typ	max	Unit
Current drain	I _{DD}				1	mA
	I _{CC}				1	mA
Output off leakage current	I _{OFF}	IN1, IN2, V _{M1} , V _{M2} , CT1, CT2, OUT1, OUT2, analog switch off	-10		+10	µA
Total harmonic distortion	THD1	V _{IN} = 1 Vrms, f = 1 kHz, V _{DD} - V _{EE} = 32 V, V _R = max		0.004		%
	THD2	V _{IN} = 0.1 Vrms, f = 1 kHz, V _{DD} - V _{EE} = 32 V, V _R = max		0.02		%
Inter-channel crosstalk	C _T	OUT1 and OUT2, with a 20 kHz 1 Vrms input to one channel		-75	-60	dB
Output at maximum attenuation	V _O	f = 20 kHz, V _{IN} = 1 Vrms		-98		dB

Pin Assignment




A02486

Top view


LC7536R

Equivalent Circuit Block Diagram



A02487

Internal Resistor Equivalent Circuit Diagram




unit (resistance: KΩ)

A02488


LC7536R

Pin Functions


Pin No.	Symbol	Function	Note
1	L 5dBIN	Inputs to the 5 dB step attenuator. Must be driven by low impedance outputs.	
30	R 5dBIN		
3	NC	No connection	
4	NC		
28	NC		
27	NC		
5	L 5dBOUT	Outputs from the 5 dB step attenuator. Outputs should be received by a load of about 1 M Ω .	
26	R 5dBOUT		
6	L 1dBIN	Inputs to the 1 dB step attenuator. Must be driven by low impedance outputs.	
25	R 1dBIN		
8	L 1dBOUT	Outputs from the 1 dB step attenuator. Outputs should be received by a load in the range 47 k Ω to 1 M Ω .	
23	R 1dBOUT		
9	L V_M	Volume control common connections. The impedance of the pattern connected to these pins should be lowered as far as possible. Since $L V_M$, $R V_M$ and V_{SS} are not connected internally, they should be connected externally according to their respective specifications. In particular, when a single-sided power supply is used, the capacitor connected between V_M and V_{SS} appears as the residual resistance when the volume is attenuated. Thus care is required when selecting the value for this capacitor.	 <p style="text-align: right;">A00461</p>
22	R V_M		
12	S	Selection pin for the address code in the data format. When this pin is connected to V_{DD} , the LC7536R will accept data when the address code is 9 and when connected to V_{CC} , the LC7536R will accept data when the address code is 8.	
17	CL	Inputs for controlling the LC7536R from serial data. Signals should have an amplitude of 0 to 5 V.	
18	DI		
19	CE		
10	V_{EE}	Power supply connections. Do not bring up the V_{CC} voltage before the V_{DD} voltage when powering up the LC7536R.	
13	V_{DD}		
14	V_{SS}		
21	V_{CC}		
2, 7, 11, 15, 16, 20, 24, 29	NC	No connection	

LC7536R


Data Format



A02489




A02490



A02491

LC7536R

Sample Application Circuit



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any and all SANYO products described or contained herein fall under strategic products (including services) controlled under the Foreign Exchange and Foreign Trade Control Law of Japan, such products must not be exported without obtaining export license from the Ministry of International Trade and Industry in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.