




HCF4008B

4 BIT FULL ADDER WITH PARALLEL CARRY OUTPUT

- HIGH SPEED OPERATION :
SUM IN TO SUM OUT 160ns (Typ.)
CARRY IN TO CARRY OUT 50ns (Typ.)
at $V_{DD} = 10V$, $C_L = 50pF$
- 4 SUM OUTPUTS PLUS PARALLEL
LOOK-AHEAD CARRY OUTPUT
- QUIESCENT CURRENT SPECIFIED UP TO
20V
- 5V, 10V AND 15V PARAMETRIC RATINGS
- INPUT LEAKAGE CURRENT
 $I_I = 100nA$ (MAX) AT $V_{DD} = 18V$ $T_A = 25^\circ C$
- 100% TESTED FOR QUIESCENT CURRENT
- MEETS ALL REQUIREMENTS OF JEDEC
JESD13B " STANDARD SPECIFICATIONS
FOR DESCRIPTION OF B SERIES CMOS
DEVICES"

DESCRIPTION

The HCF4008B is a monolithic integrated circuit fabricated in Metal Oxide Semiconductor technology available in DIP and SOP packages. The HCF4008B consists of four full adder stages with fast look ahead carry provision from stage to




ORDER CODES

| PACKAGE | TUBE | T & R |
|---------|------------|---------------|
| DIP | HCF4008BEY | |
| SOP | HCF4008BM1 | HCF4008M013TR |

stage. Circuitry is included to provide a fast "parallel carry out" to permit high speed operation in arithmetic sections using several HCF4008B's. HCF4008B inputs include the four sum bits, S1 to S4. In addition to the high speed "parallel carry out" which may be utilized at a succeeding HCF4008B section.


PIN CONNECTION



S-2381

HCF4008B

INPUT EQUIVALENT CIRCUIT



PIN DESCRIPTION


| PIN No | SYMBOL | NAME AND FUNCTION |
|----------------|-----------------|-------------------------|
| 7, 5, 3, 1 | A1 to A4 | A Operand Inputs |
| 6, 4, 2, 15 | B1 to B4 | B Operand Inputs |
| 10, 11, 12, 13 | S1 to S4 | Sum Outputs |
| 9 | CI | Carry In |
| 14 | CO | Carry Out |
| 8 | V _{SS} | Negative Supply Voltage |
| 16 | V _{DD} | Positive Supply Voltage |

TRUTH TABLE

| An | Bn | Cl | Co | Sum |
|----|----|----|----|-----|
| L | L | L | L | L |
| H | L | L | L | H |
| L | H | L | L | H |
| H | H | L | H | L |
| L | L | H | L | H |
| H | L | H | H | L |
| L | H | H | H | L |
| H | H | H | H | H |

X : Don't Care

LOGIC DIAGRAM



ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|-----------|---|------------------------|------|
| V_{DD} | Supply Voltage | -0.5 to +22 | V |
| V_I | DC Input Voltage | -0.5 to $V_{DD} + 0.5$ | V |
| I_I | DC Input Current | ± 10 | mA |
| P_D | Power Dissipation per Package | 200 | mW |
| | Power Dissipation per Output Transistor | 100 | mW |
| T_{op} | Operating Temperature | -55 to +125 | °C |
| T_{stg} | Storage Temperature | -65 to +150 | °C |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied.

All voltage values are referred to V_{SS} pin voltage.

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Value | Unit |
|----------|-----------------------|---------------|------|
| V_{DD} | Supply Voltage | 3 to 20 | V |
| V_I | Input Voltage | 0 to V_{DD} | V |
| T_{op} | Operating Temperature | -55 to 125 | °C |

HCF4008B

DC SPECIFICATIONS

| Symbol | Parameter | Test Condition | | | | Value | | | | | | Unit | |
|----------|---------------------------|----------------|--------------|--------------------------|-----------------|--------------------|---------------|-----------|------------------------------|---------|-------------------------------|---------|---------|
| | | V_I (V) | V_O (V) | $ I_{OL} $ (μ A) | V_{DD} (V) | $T_A = 25^\circ C$ | | | $-40 \text{ to } 85^\circ C$ | | $-55 \text{ to } 125^\circ C$ | | |
| | | | | | | Min. | Typ. | Max. | Min. | Max. | Min. | Max. | |
| I_L | Quiescent Current | 0/5 | | | 5 | | 0.04 | 5 | | 150 | | 150 | μA |
| | | 0/10 | | | 10 | | 0.04 | 10 | | 300 | | 300 | |
| | | 0/15 | | | 15 | | 0.04 | 20 | | 600 | | 600 | |
| | | 0/20 | | | 20 | | 0.08 | 100 | | 3000 | | 3000 | |
| V_{OH} | High Level Output Voltage | 0/5 | | <1 | 5 | 4.95 | | | 4.95 | | 4.95 | | V |
| | | 0/10 | | <1 | 10 | 9.95 | | | 9.95 | | 9.95 | | |
| | | 0/15 | | <1 | 15 | 14.95 | | | 14.95 | | 14.95 | | |
| V_{OL} | Low Level Output Voltage | 5/0 | | <1 | 5 | | 0.05 | | | 0.05 | | 0.05 | V |
| | | 10/0 | | <1 | 10 | | 0.05 | | | 0.05 | | 0.05 | |
| | | 15/0 | | <1 | 15 | | 0.05 | | | 0.05 | | 0.05 | |
| V_{IH} | High Level Input Voltage | | 0.5/4.5 | <1 | 5 | 3.5 | | | 3.5 | | 3.5 | | V |
| | | | 1/9 | <1 | 10 | 7 | | | 7 | | 7 | | |
| | | | 1.5/13.5 | <1 | 15 | 11 | | | 11 | | 11 | | |
| V_{IL} | Low Level Input Voltage | | 4.5/0.5 | <1 | 5 | | | 1.5 | | 1.5 | | 1.5 | V |
| | | | 9/1 | <1 | 10 | | | 3 | | 3 | | 3 | |
| | | | 13.5/1.5 | <1 | 15 | | | 4 | | 4 | | 4 | |
| I_{OH} | Output Drive Current | 0/5 | 2.5 | <1 | 5 | -1.36 | -3.2 | | -1.1 | | -1.1 | | mA |
| | | 0/5 | 4.6 | <1 | 5 | -0.44 | -1 | | -0.36 | | -0.36 | | |
| | | 0/10 | 9.5 | <1 | 10 | -1.1 | -2.6 | | -0.9 | | -0.9 | | |
| | | 0/15 | 13.5 | <1 | 15 | -3.0 | -6.8 | | -2.4 | | -2.4 | | |
| I_{OL} | Output Sink Current | 0/5 | 0.4 | <1 | 5 | 0.44 | 1 | | 0.36 | | 0.36 | | mA |
| | | 0/10 | 0.5 | <1 | 10 | 1.1 | 2.6 | | 0.9 | | 0.9 | | |
| | | 0/15 | 1.5 | <1 | 15 | 3.0 | 6.8 | | 2.4 | | 2.4 | | |
| I_I | Input Leakage Current | 0/18 | Any Input | | 18 | | $\pm 10^{-5}$ | ± 0.1 | | ± 1 | | ± 1 | μA |
| C_I | Input Capacitance | | Any Input | | | | 5 | 7.5 | | | | | pF |

The Noise Margin for both "1" and "0" level is: 1V min. with $V_{DD}=5V$, 2V min. with $V_{DD}=10V$, 2.5V min. with $V_{DD}=15V$


DYNAMIC ELECTRICAL CHARACTERISTICS ($T_{amb} = 25^\circ C$, $C_L = 50pF$, $R_L = 200K\Omega$, $t_r = t_f = 20 ns$)

| Symbol | Parameter | Test Condition | | Value (*) | | | Unit |
|---------------------|--|----------------|--|-----------|------|------|------|
| | | V_{DD} (V) | | Min. | Typ. | Max. | |
| t_{PLH} t_{PHL} | Propagation Delay Time (SUM IN to SUM OUT) | 5 | | | 400 | 800 | ns |
| | | 10 | | | 160 | 320 | |
| | | 15 | | | 115 | 230 | |
| t_{PLH} t_{PHL} | Propagation Delay Time (CARRY IN to SUM OUT) | 5 | | | 370 | 740 | ns |
| | | 10 | | | 155 | 310 | |
| | | 15 | | | 115 | 230 | |
| t_{PLH} t_{PHL} | Propagation Delay Time (SUM IN to CARRY OUT) | 5 | | | 200 | 400 | ns |
| | | 10 | | | 90 | 180 | |
| | | 15 | | | 65 | 130 | |
| t_{PLH} t_{PHL} | Propagation Delay Time (CARRY IN to CARRY OUT) | 5 | | | 100 | 200 | ns |
| | | 10 | | | 50 | 100 | |
| | | 15 | | | 40 | 80 | |
| t_{THL} t_{TLH} | Transition Time (carry out or decoded out lines) | 5 | | | 100 | 200 | ns |
| | | 10 | | | 50 | 100 | |
| | | 15 | | | 40 | 80 | |

(*) Typical temperature coefficient for all V_{DD} value is 0.3 %/ $^\circ C$.

TYPICAL APPLICATION

SPEED CHARACTERISTICS OF A 16 BIT-ADDER




NOTES : All "A" and "B" input bits occur at $t = 0$

All sums settled at $t = 345ns$

$C_L = 50pF$, $T_{amb} = 25^\circ C$, $V_{DD} - V_{SS} = 10V$

HCF4008B

TEST CIRCUIT



$C_L = 50\text{pF}$ or equivalent (includes jig and probe capacitance)


$R_L = 200\text{K}\Omega$

$R_T = Z_{OUT}$ of pulse generator (typically 50Ω)

CS03770

Plastic DIP-16 (0.25) MECHANICAL DATA

| DIM. | mm. | | | inch | | |
|------|------|-------|------|-------|-------|-------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| a1 | 0.51 | | | 0.020 | | |
| B | 0.77 | | 1.65 | 0.030 | | 0.065 |
| b | | 0.5 | | | 0.020 | |
| b1 | | 0.25 | | | 0.010 | |
| D | | | 20 | | | 0.787 |
| E | | 8.5 | | | 0.335 | |
| e | | 2.54 | | | 0.100 | |
| e3 | | 17.78 | | | 0.700 | |
| F | | | 7.1 | | | 0.280 |
| I | | | 5.1 | | | 0.201 |
| L | | 3.3 | | | 0.130 | |
| Z | | | 1.27 | | | 0.050 |




P001C

HCF4008B

SO-16 MECHANICAL DATA

| DIM. | mm. | | | inch | | |
|------|------|------------|------|-------|-------|-------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| A | | | 1.75 | | | 0.068 |
| a1 | 0.1 | | 0.2 | 0.003 | | 0.007 |
| a2 | | | 1.65 | | | 0.064 |
| b | 0.35 | | 0.46 | 0.013 | | 0.018 |
| b1 | 0.19 | | 0.25 | 0.007 | | 0.010 |
| C | | 0.5 | | | 0.019 | |
| c1 | | 45° (typ.) | | | | |
| D | 9.8 | | 10 | 0.385 | | 0.393 |
| E | 5.8 | | 6.2 | 0.228 | | 0.244 |
| e | | 1.27 | | | 0.050 | |
| e3 | | 8.89 | | | 0.350 | |
| F | 3.8 | | 4.0 | 0.149 | | 0.157 |
| G | 4.6 | | 5.3 | 0.181 | | 0.208 |
| L | 0.5 | | 1.27 | 0.019 | | 0.050 |
| M | | | 0.62 | | | 0.024 |
| S | | 8° (max.) | | | | |



PO13H

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2001 STMicroelectronics - Printed in Italy - All Rights Reserved
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom
© <http://www.st.com>

