



# STPR1520D/F

## ULTRA-FAST RECOVERY RECTIFIER DIODES

### MAIN PRODUCTS CHARACTERISTICS

$I_{F(AV)}$	15 A
$V_{RRM}$	200 V
$T_j(\text{max})$	150°C
$V_F(\text{max})$	0.99 V
$t_{rr}(\text{max})$	30 ns

### FEATURES

- SUITED FOR SMPS
- LOW LOSSES
- LOW FORWARD AND REVERSE RECOVERY TIME
- HIGH SURGE CURRENT CAPABILITY
- HIGH AVALANCHE ENERGY CAPABILITY

### DESCRIPTION

Low cost single chip rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged in TO-220AC and ISOWATT220AC, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



Symbol	Parameter			Value	Unit
$V_{RRM}$	Repetitive peak reverse voltage			200	V
$I_{F(RMS)}$	RMS forward current			30	A
$I_{F(AV)}$	$\delta = 0.5$	TO-220AC	$T_c = 115^\circ\text{C}$	15	A
		ISOWATT220AC	$T_c = 70^\circ\text{C}$		
$I_{FSM}$	Surge non repetitive forward current		$T_p = 10 \text{ ms}$ Sinusoidal	150	A
$T_{stg}$	Storage temperature range			- 65 to + 150	°C
$T_j$	Maximum operating junction temperature			+ 150	

## STPR1520D/F

### THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to case	TO-220AC	2	°C/W
		ISOWATT220AC	4.5	

### STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameters	Test conditions		Min.	Typ.	Max.	Unit
$I_R$ *	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			50	$\mu\text{A}$
		$T_j = 100^\circ\text{C}$				1	$\text{mA}$
$V_F$ **	Forward voltage drop	$T_j = 125^\circ\text{C}$	$I_F = 15 \text{ A}$			0.99	V
		$T_j = 125^\circ\text{C}$	$I_F = 30 \text{ A}$			1.20	
		$T_j = 25^\circ\text{C}$	$I_F = 30 \text{ A}$			1.25	

Pulse test : \*  $tp = 5 \text{ ms}, \delta < 2 \%$

\*\*  $tp = 380 \mu\text{s}, \delta < 2 \%$


To evaluate the conduction losses use the following equation :

$$P = 0.78 \times I_{F(AV)} + 0.014 \times I_{F}^2(\text{RMS})$$


### RECOVERY CHARACTERISTICS

Symbol	Test conditions			Min.	Typ.	Max.	Unit
$t_{rr}$	$T_j = 25^\circ\text{C}$	$I_F = 0.5 \text{ A}$	$I_{rr} = 0.25 \text{ A}$	$I_R = 1 \text{ A}$		30	ns
$t_{fr}$	$T_j = 25^\circ\text{C}$	$I_F = 1 \text{ A}$	$tr = 10 \text{ ns}$			20	
$V_{FP}$	$T_j = 25^\circ\text{C}$	$I_F = 1 \text{ A}$	$tr = 10 \text{ ns}$			3	V


**Fig. 1:** Average forward power dissipation versus average forward current.




**Fig. 2:** Peak current versus form factor.




**Fig. 3:** Average current versus ambient temperature.




**Fig. 5:** Non repetitive surge peak forward current versus overload duration (maximum values) (TO-220AC)




**Fig. 7:** Relative variation of thermal transient impedance junction to case versus pulse duration (TO-220AC).




**Fig. 4:** Average current versus ambient temperature.



**Fig. 6:** Non repetitive surge peak forward current versus overload duration (maximum values) (ISOWATT220AC).




**Fig. 8:** Relative variation of thermal transient impedance junction to case versus pulse duration (ISOWATT220AC).




## STPR1520D/F


**Fig. 9:** Forward voltage drop versus forward current.




**Fig. 10:** Junction capacitance versus reverse voltage applied (typical values).




**Fig. 11:** Recovery charge versus  $dI_F/dt$ .



**Fig. 12:** Peak reverse current versus  $dI_F/dt$ .



**Fig. 13:** Dynamic parameters versus junction temperature.



## PACKAGE MECHANICAL DATA

TO-220AC

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.40	4.60	0.173	0.181
C	1.23	1.32	0.048	0.051
D	2.40	2.72	0.094	0.107
E	0.49	0.70	0.019	0.027
F	0.61	0.88	0.024	0.034
F1	1.14	1.70	0.044	0.066
G	4.95	5.15	0.194	0.202
H2	10.00	10.40	0.393	0.409
L2	16.40 typ.		0.645 typ.	
L4	13.00	14.00	0.511	0.551
L5	2.65	2.95	0.104	0.116
L6	15.25	15.75	0.600	0.620
L7	6.20	6.60	0.244	0.259
L9	3.50	3.93	0.137	0.154
M	2.6 typ.		0.102 typ.	
Diam. I	3.75	3.85	0.147	0.151

## STPR1520D/F

### PACKAGE MECHANICAL DATA ISOWATT220AC

REF.	DIMENSIONS					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	2.50		2.70	0.098		0.106
D	2.40		2.75	0.094		0.108
E	0.40		0.70	0.016		0.028
F	0.75		1.00	0.030		0.039
F1	1.15		1.70	0.045		0.067
G	4.95		5.20	0.195		0.205
H	10.00		10.40	0.394		0.409
L2		16.00			0.630	
L3	28.60		30.60	1.125		1.205
L6	15.90		16.40	0.626		0.646
L7	9.00		9.30	0.354		0.366
Diam	3.00		3.20	0.118		0.126

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.  
STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2001 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany

Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore  
Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>