


**SD1434**

RF & MICROWAVE TRANSISTORS UHF MOBILE APPLICATIONS

- 470 MHz
- 12.5 VOLTS
- COMMON EMITTER
- $P_{OUT} = 45\text{ W MIN. WITH } 5.0\text{ dB GAIN}$




.500 6LFL (M111)
epoxy sealed

ORDER CODE
SD1434

BRANDING
SD1434

PIN CONNECTION



1. Collector 3. Emitter
2. Base 4. Emitter

DESCRIPTION

The SD1434 is a 12.5 V Class C epitaxial silicon NPN planar transistor designed primarily for UHF communications. This device utilizes diffused emitter resistors to achieve infinite VSWR under operating conditions.

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}\text{C}$)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	36	V
V_{CEO}	Collector-Emitter Voltage	16	V
V_{CES}	Collector-Emitter Voltage	36	V
V_{EBO}	Emitter-Base Voltage	4.0	V
I_C	Device Current	10.0	A
P_{DISS}	Power Dissipation	175	W
T_J	Junction Temperature	+200	$^{\circ}\text{C}$
T_{STG}	Storage Temperature	- 65 to +150	$^{\circ}\text{C}$

THERMAL DATA

$R_{TH(j-c)}$	Junction-Case Thermal Resistance	1.0	$^{\circ}\text{C/W}$
---------------	----------------------------------	-----	----------------------

SD1434

ELECTRICAL SPECIFICATIONS ($T_{case} = 25^{\circ}C$)

STATIC


Symbol	Test Conditions		Value			Unit
			Min.	Typ.	Max.	
BV_{CBO}	$I_C = 5mA$	$I_E = 0mA$	36	—	—	V
BV_{CES}	$I_C = 20mA$	$V_{BE} = 0V$	36	—	—	V
BV_{CEO}	$I_C = 50mA$	$I_B = 0mA$	16	—	—	V
BV_{EBO}	$I_E = 5mA$	$I_C = 0mA$	4.0	—	—	V
I_{CES}	$V_{CE} = 22V$	$I_E = 0mA$	—	—	5	mA
I_{CBO}	$V_{CB} = 15V$	$I_E = 0mA$	—	—	5	mA
h_{FE}	$V_{CE} = 5V$	$I_C = 1A$	20	—	200	—

DYNAMIC


Symbol	Test Conditions			Value			Unit
				Min.	Typ.	Max.	
P_{OUT}	$f = 470\text{ MHz}$	$P_{IN} = 14\text{ W}$	$V_{CE} = 12.5\text{ V}$	45	—	—	W
G_P	$f = 470\text{ MHz}$	$P_{IN} = 14\text{ W}$	$V_{CE} = 12.5\text{ V}$	5	—	—	dB
C_{OB}	$f = 1\text{ MHz}$	$V_{CB} = 12.5\text{ V}$		—	130	—	pF

TYPICAL PERFORMANCE


POWER OUTPUT vs POWER INPUT





POWER OUTPUT vs FREQUENCY




TYPICAL PERFORMANCE (cont'd)

OUTPUT CAPACITANCE vs COLLECTOR
BASE VOLTAGE

IMPEDANCE DATA



TEST CIRCUIT



C1 : 10pF Unelco, 200 mil Sq.
 C2 : 36pF Unelco, 400 mil Sq.
 C3 : 34pF Unelco, 400 mil Sq.
 C4 : 36pF Unelco, 400 mil Sq.
 C5 : 38pF Unelco, 400 mil Sq.
 C6 : 16pF Unelco, 200 mil Sq.
 C7 : 10pF Unelco, 200 mil Sq.
 C8 : 25pF Unelco, 200 mil Sq.
 C9 : 1 - 12pF, ATC Variable
 C10 : 6pF Unelco, 200 mil Sq.


C11 : .01μF 50V, Erie Disc
 C12 : 1000pF Unelco, 400 mil Sq.
 C13 : 47μF 63V, Sprague Electrolytic
 C14 : 10pF Unelco, 200 mil Sq.

L1 : 27μH Molded
 L2 : 6 Turns, #18 AWG, .175" I.D.

Material : Pc Board, Double Sided Copper 1/32" Thick
 Teflon-Glass, 3M-K-6098

PACKAGE MECHANICAL DATA

Ref.: Dwg. No.12-0111



SGS-THOMSON MICROELECTRONICS			CONT'D		
	MINIMUM Inches/mm	MAXIMUM Inches/mm		MINIMUM Inches/mm	MAXIMUM Inches/mm
A	.150/3,43	.160/4,06	K	.095/2,41	.105/2,67
B	.045/1,14		L	.150/3,81	.170/4,32
C	.210/5,33	.220/5,59	M		.280/7,11
D	.835/21,21	.865/21,97			
E	.200/5,08	.210/5,33			
F	.490/12,45	.510/12,95			
G	.003/0,08	.007/0,18			
H	.125/3,18				
I	.720/18,29	.730/18,54			
J	.970/24,64	.980/24,89			

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES
 Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
 Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A