





**SD1460**

**RF & MICROWAVE TRANSISTORS  
FM BROADCAST APPLICATIONS**

- 108 MHz
- 28 VOLTS
- EFFICIENCY 75%
- COMMON EMITTER
- GOLD METALLIZATION
- P<sub>OUT</sub> = 150 W MIN. WITH 9.2 dB GAIN



**DESCRIPTION**

The SD1143 is a 28 V gold metallized epitaxial silicon NPN planar transistor designed for VHF FM broadcast transmitters. This device utilizes diffused emitter resistors to achieve infinite VSWR at rated operating conditions.

**ABSOLUTE MAXIMUM RATINGS (T<sub>case</sub> = 25°C)**

Symbol	Parameter	Value	Unit
V <sub>CBO</sub>	Collector-Base Voltage	60	V
V <sub>CEO</sub>	Collector-Emitter Voltage	25	V
V <sub>CES</sub>	Collector-Emitter Voltage	60	V
V <sub>EBO</sub>	Emitter-Base Voltage	4.0	V
I <sub>c</sub>	Device Current	16	A
P <sub>DISS</sub>	Power Dissipation	230	W
T <sub>J</sub>	Junction Temperature	+200	°C
T <sub>STG</sub>	Storage Temperature	- 65 to +150	°C

**THERMAL DATA**

R <sub>TH(j-c)</sub>	Junction-Case Thermal Resistance	0.75	°C/W
----------------------	----------------------------------	------	------



# SD1460

## ELECTRICAL SPECIFICATIONS (T<sub>case</sub> = 25°C)

### STATIC


Symbol	Test Conditions		Value			Unit
			Min.	Typ.	Max.	
BV <sub>CBO</sub>	I <sub>C</sub> = 100mA	I <sub>E</sub> = 0mA	60	—	—	V
BV <sub>CER</sub>	I <sub>C</sub> = 100mA	R <sub>BE</sub> = 10Ω	55	—	—	V
BV <sub>CEO</sub>	I <sub>C</sub> = 100mA	I <sub>B</sub> = 0mA	25	—	—	V
BV <sub>EBO</sub>	I <sub>E</sub> = 20mA	I <sub>C</sub> = 0mA	4.0	—	—	V
h <sub>FE</sub>	V <sub>CE</sub> = 5V	I <sub>C</sub> = 1A	20	—	150	—

### DYNAMIC


Symbol	Test Conditions			Value			Unit
				Min.	Typ.	Max.	
P <sub>OUT</sub>	f = 108 MHz	P <sub>IN</sub> = 18 W	V <sub>CE</sub> = 28 V	150	—	—	W
G <sub>P</sub>	f = 108 MHz	P <sub>IN</sub> = 18 W	V <sub>CE</sub> = 28 V	9.2	—	—	dB
η <sub>c</sub>	f = 108 MHz	P <sub>IN</sub> = 18 W	V <sub>CE</sub> = 28 V	70	—	—	%
C <sub>OB</sub>	f = 1 MHz	V <sub>CB</sub> = 28 V		—	—	150	pF

## TYPICAL PERFORMANCE


POWER OUTPUT vs POWER INPUT



SAFE OPERATING AREA




## IMPEDANCE DATA





## PACKAGE MECHANICAL DATA

Ref.: Dwg. No.12-0174



SGS-THOMSON MICROELECTRONICS			CONT'D		
	MINIMUM Inches/mm	MAXIMUM Inches/mm		MINIMUM Inches/mm	MAXIMUM Inches/mm
A	.220/5,59	.230/5,84	K		.280/7,11
B	.125/3,18		L		1.050/26,67
C	.245/6,22	.255/6,48			
D	.720/18,28	.730/18,54			
E	.125/3,18				
F	.970/24,64	.980/24,89			
G	.495/12,57	.505/12,83			
H	.003/0,08	.007/0,18			
I	.090/2,29	.110/2,79			
J	.160/4,06	.175/4,45			

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES  
 Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
 Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A