




**STPR1210D/F
STPR1220D/F**

ULTRA FAST RECOVERY RECTIFIER DIODES

- SUITED FOR SMPS
- LOW LOSSES
- LOW FORWARD AND REVERSE RECOVERY TIME
- HIGH SURGE CURRENT CAPABILITY
- HIGH AVALANCHE ENERGY CAPABILITY



DESCRIPTION

Low cost single chip rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged in TO220AC and ISOwatt220AC, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit
I _F (RMS)	RMS Forward Current			30	A
I _F (AV)	Average Forward Current $\delta = 0.5$	TO220AC	T _c = 115°C	12	A
		ISOwatt220AC	T _c = 80°C		
I _{FSM}	Surge Non Repetitive Forward Current		T _p = 10 ms Sinusoidal	120	A
T _{stg} T _j	Storage and Junction Temperature Range			- 65 to + 150 - 65 to + 150	°C

Symbol	Parameter	STPR		Unit
		1210D 1210F	1220D 1220F	
V _{RRM}	Repetitive Peak Reverse Voltage	100	200	V

THERMAL RESISTANCE

Symbol	Parameter		Value	Unit
R _{th} (j-c)	Junction-case	TO220AC	2.5	°C/W
		ISOwatt220AC	5.0	

STPR1210D/F / STPR1220D/F

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

Symbol	Tests Conditions		Min.	Typ.	Max.	Unit
I_R *	$T_j = 25^\circ C$	$V_R = V_{RRM}$			50	μA
	$T_j = 100^\circ C$				0.8	mA
V_F **	$T_j = 125^\circ C$	$I_F = 12 A$			0.99	V
	$T_j = 125^\circ C$	$I_F = 24 A$			1.20	
	$T_j = 25^\circ C$	$I_F = 24 A$			1.25	

Pulse test : * $t_p = 5 \text{ ms}$, duty cycle < 2 %

** $t_p = 380 \mu\text{s}$, duty cycle < 2%

RECOVERY CHARACTERISTICS

Symbol	Tests Conditions			Min.	Typ.	Max.	Unit	
tr_r	$T_j = 25^\circ C$	$I_F = 0.5 A$	$I_R = 1 A$	$I_{rr} = 0.25 A$			30	ns
tfr	$T_j = 25^\circ C$	$I_F = 1 A$	$tr = 10 \text{ ns}$	$V_{FR} = 1.1 \times V_F$		20		ns
V_{FP}	$T_j = 25^\circ C$	$I_F = 1 A$	$tr = 10 \text{ ns}$			3		V

To evaluate the conduction losses use the following equation :

$$P = 0.78 \times I_F(AV) + 0.0175 I_F^2(\text{RMS})$$

Fig.1 : Average forward power dissipation versus average forward current.





Fig.2 : Peak current versus form factor.



STPR1210D/F / STPR1220D/F

Fig.3 : Average current versus ambient temperature.
(duty cycle : 0.5) (TO220AC)




Fig.5 : Non repetitive surge peak forward current versus overload duration.
(Maximum values) (TO220AC)




Fig.7 : Relative variation of thermal transient impedance junction to case versus pulse duration.
(TO220AC)




Fig.4 : Average current versus ambient temperature.
(duty cycle : 0.5) (ISOWATT220AC)




Fig.6 : Non repetitive surge peak forward current versus overload duration.
(Maximum values) (ISOWATT220AC)





Fig.8 : Relative variation of thermal transient impedance junction to case versus pulse duration.
(ISOWATT220AC)



STPR1210D/F / STPR1220D/F

Fig.9 : Forward voltage drop versus forward current.
(Maximum values)




Fig.11 : Recovery charge versus dIF/dt.




Fig.13 : Dynamic parameters versus junction temperature.




Fig.10 : Junction capacitance versus reverse voltage applied. (Typical values)






Fig.12 : Peak reverse current versus dIF/dt.



STPR1210D/F / STPR1220D/F

PACKAGE MECHANICAL DATA

TO220AC (JEDEC outline)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	10	10.4	0.393	0.409
B	15.2	15.9	0.598	0.626
C	13	14	0.511	0.551
D	6.2	6.6	0.244	0.260
E	16.4 typ.		0.645 typ.	
F	3.5	4.2	0.137	0.165
G	2.65	2.95	0.104	0.116
H	4.4	4.6	0.173	0.181
I	3.75	3.85	0.147	0.151
J	1.23	1.32	0.048	0.051
K	1.27 typ.		0.050 typ.	
L	0.49	0.70	0.019	0.027
M	2.4	2.72	0.094	0.107
N	4.95	5.15	0.194	0.203
O	1.14	1.70	0.044	0.067
P	0.61	0.88	0.024	0.034

Cooling method : C

Marking : Type number


Weight : 1.9 g

Recommended torque value : 0.55m.N

Maximum torque value : 0.7m.N

PACKAGE MECHANICAL DATA

ISOWATT220AC (JEDEC outline)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	10	10.4	0.393	0.409
B	15.9	16.4	0.626	0.645
C	28.6	30.6	1.126	1.204
D	16 typ		0.630 typ	
E	9	9.3	0.354	0.366
H	4.4	4.6	0.173	0.181
I	3	3.2	0.118	0.126
J	2.5	2.7	0.098	0.106
L	0.4	0.7	0.015	0.027
M	2.4	2.75	0.094	0.108
N	4.95	5.2	0.195	0.204
O	1.15	1.7	0.045	0.067
P	0.75	1	0.030	0.039

Cooling method : C

Marking : Type number

Weight : 2 g

Recommended torque value : 0.55m.N

Maximum torque value : 0.70m.N

Electrical Isolation : 2000V DC

Capacitance : 12pF

STPR1210D/F / STPR1220D/F

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

TURBOSWITCH, TRANSIL, TRISIL, SNUBBERLESS are Trademarks of SGS-THOMSON Microelectronics.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A