


SIEMENS

Preliminary data

SPP46N03
SPB46N03

SIPMOS® Power Transistor

- N-Channel
- Enhancement mode
- Avalanche rated
- dv/dt rated
- 175°C operating temperature



Pin 1	Pin 2	Pin 3
G	D	S

Type	V_{DS}	I_D	$R_{DS(on)}$	@ V_{GS}	Package	Ordering Code
SPP46N03	30 V	46 A	0.015 Ω	$V_{GS} = 10 \text{ V}$	P-TO220-3-1	Q67040-S4145-A2
SPB46N03					P-TO263-3-2	Q67040-S4742-A3

Maximum Ratings, at $T_j = 25 \text{ °C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current $T_C = 25 \text{ °C}$, ¹⁾ $T_C = 100 \text{ °C}$	I_D	46 46	A
Pulsed drain current $T_C = 25 \text{ °C}$	$I_{D \text{ puls}}$	184	
Avalanche energy, single pulse $I_D = 46 \text{ A}$, $V_{DD} = 25 \text{ V}$, $R_{GS} = 25 \text{ } \Omega$	E_{AS}	250	mJ
Avalanche current, periodic limited by T_{jmax}	I_{AR}	46	A
Avalanche energy, periodic limited by $T_{j(max)}$	E_{AR}	12	mJ
Reverse diode dv/dt $I_S = 46 \text{ A}$, $V_{DS} = 24 \text{ V}$, $dI/dt = 200 \text{ A}/\mu\text{s}$, $T_{jmax} = 175 \text{ °C}$	dv/dt	6	kV/ μs
Gate source voltage	V_{GS}	± 20	V
Power dissipation $T_C = 25 \text{ °C}$	P_{tot}	120	W
Operating temperature	T_j	-55 ... +175	°C
Storage temperature	T_{stg}	-55 ... +175	
IEC climatic category; DIN IEC 68-1		55/175/56	

¹current limited by bond wire

Electrical Characteristics

Parameter at $T_j = 25\text{ °C}$, unless otherwise specified	Symbol	Values			Unit
		min.	typ.	max.	

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	-		1.25	K/W
Thermal resistance, junction - ambient	R_{thJA}	-	62	-	
SMD version, device on PCB: @ min. footprint @ 6 cm ² cooling area ¹	R_{thJA}	- -	tbd tbd	- -	

Static Characteristics

Drain- source breakdown voltage $V_{GS} = 0\text{ V}$, $I_D = 0.25\text{ mA}$	$V_{(BR)DSS}$	30	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D = 80\text{ }\mu\text{A}$, $T_j = 25\text{ °C}$	$V_{GS(th)}$	2.1	3	4	
Zero gate voltage drain current $V_{DS} = 30\text{ V}$, $V_{GS} = 0\text{ V}$, $T_j = 25\text{ °C}$ $V_{DS} = 30\text{ V}$, $V_{GS} = 0\text{ V}$, $T_j = 150\text{ °C}$	I_{DSS}	- -	0.1 -	1 100	μA
Gate-source leakage current $V_{GS} = 20\text{ V}$, $V_{DS} = 0\text{ V}$	I_{GSS}	-	10	100	
Drain-Source on-state resistance $V_{GS} = 10\text{ V}$, $I_D = 46\text{ A}$	$R_{DS(on)}$	-	0.009	0.015	Ω

¹ Device on 50mm*50mm*1.5mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical without blown air.

Electrical Characteristics

Parameter at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified	Symbol	Values			Unit
		min.	typ.	max.	
Dynamic Characteristics					
Transconductance $V_{DS} \geq 2 \cdot I_D \cdot R_{DS(on)max}$, $I_D = 46\text{ A}$	g_{fs}	20	39	-	S
Input capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{iss}	-	1400	1750	pF
Output capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{oss}	-	645	810	
Reverse transfer capacitance $V_{GS} = 0\text{ V}$, $V_{DS} = 25\text{ V}$, $f = 1\text{ MHz}$	C_{rss}	-	260	325	
Turn-on delay time $V_{DD} = 15\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 46\text{ A}$, $R_G = 6.8\text{ }\Omega$	$t_{d(on)}$	-	13	20	ns
Rise time $V_{DD} = 15\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 46\text{ A}$, $R_G = 6.8\text{ }\Omega$	t_r	-	24	36	
Turn-off delay time $V_{DD} = 15\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 46\text{ A}$, $R_G = 6.8\text{ }\Omega$	$t_{d(off)}$	-	27	42	
Fall time $V_{DD} = 15\text{ V}$, $V_{GS} = 10\text{ V}$, $I_D = 46\text{ A}$, $R_G = 6.8\text{ }\Omega$	t_f	-	24	36	

Electrical Characteristics

Parameter at $T_j = 25\text{ °C}$, unless otherwise specified	Symbol	Values			Unit
		min.	typ.	max.	

Dynamic Characteristics


Gate charge at threshold $V_{DD} = 24\text{ V}$, $I_D \geq 0,1\text{ A}$, $V_{GS} = 0\text{ to }1\text{ V}$	$Q_{G(th)}$	-	2.4	3.6	nC
Gate charge at $V_{GS}=7\text{ V}$ $V_{DD} = 24\text{ V}$, $I_D = 46\text{ A}$, $V_{GS} = 0\text{ to }7\text{ V}$	$Q_{g(7)}$	-	30.2	45	nC
Gate charge total $V_{DD} = 24\text{ V}$, $I_D = 46\text{ A}$, $V_{GS} = 0\text{ to }10\text{ V}$	Q_g	-	39	60	
Gate plateau voltage $V_{DD} = 24\text{ V}$, $I_D = 46\text{ A}$	$V_{(plateau)}$	-	5.5	-	V

Reverse Diode

Inverse diode continuous forward current $T_C = 108\text{ °C}$	I_S	-	-	46	A
Inverse diode direct current,pulsed $T_C = 25\text{ °C}$	I_{SM}	-	-	184	
Inverse diode forward voltage $V_{GS} = 0\text{ V}$, $I_F = 92\text{ A}$	V_{SD}	-	1.06	1.7	V
Reverse recovery time $V_R = 15\text{ V}$, $I_F = I_S$, $di_F/dt = 100\text{ A}/\mu\text{s}$	t_{rr}	-	40	60	ns
Reverse recovery charge $V_R = 15\text{ V}$, $I_F = I_S$, $di_F/dt = 100\text{ A}/\mu\text{s}$	Q_{rr}	-	0.04	0.06	μC

Power Dissipation


$$P_{\text{tot}} = f(T_C)$$



Drain current

$$I_D = f(T_C)$$


parameter: $V_{GS} \geq 10 \text{ V}$



Transient thermal impedance

$$Z_{\text{thJC}} = f(t_p)$$


parameter: $D = t_p/T$



Typ. output characteristics

$$I_D = f(V_{DS})$$


parameter: $t_D = 80 \mu s$



Drain-source on-resistance

$$R_{DS(on)} = f(T_j)$$


parameter: $I_D = 46 A$, $V_{GS} = 10 V$



Typ. transfer characteristics $I_D = f(V_{GS})$

parameter: $t_p = 80 \mu s$


$V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$



Gate threshold voltage

$V_{GS(th)} = f(T_j)$


parameter: $V_{GS} = V_{DS}$, $I_D = 80 \mu A$



Typ. capacitances

$C = f(V_{DS})$


Parameter: $V_{GS} = 0 V$, $f = 1 MHz$



Forward characteristics of reverse diode

$I_F = f(V_{SD})$


parameter: T_j , $t_p = 80 \mu s$



Avalanche Energy $E_{AS} = f(T_j)$


parameter: $I_D = 46 \text{ A}$, $V_{DD} = 25 \text{ V}$

$R_{GS} = 25 \Omega$



Drain-source breakdown voltage


$V_{(BR)DSS} = f(T_j)$



Typ. gate charge

$V_{GS} = f(Q_{Gate})$

parameter: $I_{D \text{ puls}} = 46 \text{ A}$



Edition 7.97

**Published by Siemens AG,
Bereich Halbleiter Vertrieb,
Werbung, Balanstraße 73,
81541 München**

© Siemens AG 1997

All Rights Reserved.

Attention please!

As far as patents or other rights of third parties are concerned, liability is only assumed for components, not for applications, processes and circuits implemented within components or assemblies.

The information describes a type of component and shall not be considered as warranted characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, delivery and prices please contact the Semiconductor Group Offices in Germany or the Siemens Companies and Representatives worldwide (see address list).

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Siemens Office, Semiconductor Group.

Siemens AG is an approved CECC manufacturer.

Packing

Please use the recycling operators known to you. We can also help you - get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose!

Critical components¹ of the Semiconductor Group of Siemens AG, may only be used in life-support devices or systems² with the express written approval of the Semiconductor Group of Siemens AG.

1) A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.

2) Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or