



SAW Components

Data Sheet B7708, Pb-Free





SAW Components

B7708

Low Loss Filter

1575,42 MHz

Data Sheet




Features

- Low loss RF filter for GPS receivers
- Usable passband 2,0 MHz
- Low amplitude ripple
- Package for **Surface Mounted Technology (SMT)**
- Pb-free

Terminals

- Ni, gold-plated


Chip Sized SAW Package DCS4H



Dimensions in mm, approx. weight 0,01 g

Pin configuration

- 1 Input, unbalanced
- 3 Output, unbalanced
- 2, 4 To be grounded, Case Ground



Type	Ordering code	Marking and Package according to	Packing according to
B7708	B39162-B7708-K710	C61157-A7-A136	F61074-V8189-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T	- 40 / + 85	°C	source and load impedance 50 Ω continuous wave signal
Storage temperature range	T_{stg}	- 40 / + 85	°C	
DC voltage	V_{DC}	5	V	
ESD voltage	V^*_{ESD}	50*	V	
Input power max. 1574,3 ... 1576,7 MHz	P_{IN}	3	dBm	
50,0...1535,5 and 1625,5 ... 6000 MHz	P_{IN}	15	dBm	

* - acc. to JESD22-A115A (Machine Model), 10 negative & 10 positive pulses



SAW Components

B7708

Low Loss Filter

1575,42 MHz

Data Sheet



Characteristics

Operating temperature range: $T = -40\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ.	max.	
Center frequency	f_C	—	1575,42	—	MHz
Maximum insertion attenuation	α_{max}				
	1574,22 ... 1576,62 MHz	—	2,4	3,5	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	1574,22 ... 1576,62 MHz	—	0,1	1,0	dB
Group delay	τ				
	1574,22 ... 1576,62 MHz	—	35	50	ns
Attenuation	α				
	50,0 ... 1535,0 MHz	35	42	—	dB
	1625,0 ... 1630,0 MHz	30	44	—	dB
	1630,0 ... 3500,0 MHz	35	40	—	dB
	3500,0 ... 4000,0 MHz	20	35	—	dB
	4000,0 ... 6000,0 MHz	10	20	—	dB
Return loss					
	1574,22 ... 1576,62 MHz	11,0	19,0	—	dB
VSWR					
	1574,22 ... 1576,62 MHz	—	1,25	1,8	



SAW Components

B7708


Low Loss Filter

1575,42 MHz


Data Sheet



Transfer function



Transfer function (wide band)





SAW Components

B7708

Low Loss Filter

1575,42 MHz

Data Sheet



Published by EPCOS AG
Surface Acoustic Wave Components Division, SAW MC PD
P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2004. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



中发网 WWW.ZFA.CN

全球最大的PDF中文下载站



中发网
www.zfa.cn

PDF 资料下载尽在中发网