

**Sensors**

**B59901**

**Limit Temperature Sensors, Probe Assemblies**

**D 901**

**Applications**

- Limit temperature sensor


**Features**

- Sensor with epoxy resin coating
- Tinned leads
- Metal tag for easy mounting
- Characteristics for nominal threshold temperatures of 90 to 160 °C conform with DIN 44081
- Metal tag permits good thermal coupling and thus short response time

**Delivery mode**

- Cardboard strips in cardboard box

**Dimensional drawing**



Dimensions (mm)

**General technical data**

Max. operating voltage	( $T_A = 0 \dots 40 \text{ }^\circ\text{C}$ )	$V_{\max}$	30	VDC
Max. measuring voltage	( $T_A = 25 \text{ K} \dots T_{\text{NTT}} + 23 \text{ K}$ )	$V_{\text{meas,max}}$	7,5	VDC
Rated resistance	( $V_{\text{PTC}} \leq 2,5 \text{ V}$ )	$R_N$	$\leq 100$	$\Omega$
Thermal threshold time		$t_a$	$< 20$	s
Operating temperature range	( $V \leq V_{\text{meas,max}}$ )	$T_{\text{op}}$	$-40/T_{\text{NTT}} + 23$	$^\circ\text{C}$
	( $V = V_{\max}$ )	$T_{\text{op}}$	0/+ 40	$^\circ\text{C}$





Sensors

B59901

Limit Temperature Sensors, Probe Assemblies

D 901

**Electrical specifications and ordering codes**




$T_{NTT}$ $\pm \Delta T$ °C	$R^1$ ( $T_{NTT} - \Delta T$ ) $\Omega$	$R^1$ ( $T_{NTT} + \Delta T$ ) $\Omega$	$R^2$ ( $T_{NTT} + 15\text{ K}$ ) $\Omega$	$R^1$ ( $T_{NTT} + 23\text{ K}$ ) $\Omega$	Stamp code	Ordering code
$60 \pm 5$	$\leq 570$	$\geq 570$	—	$\geq 10\text{ k}$	331	B59901D0060A040
$70 \pm 5$	$\leq 570$	$\geq 570$	—	$\geq 10\text{ k}$	341	B59901D0070A040
$80 \pm 5$	$\leq 570$	$\geq 570$	—	$\geq 10\text{ k}$	351	B59901D0080A040
$90 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	361	B59901D0090A040
$100 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	371	B59901D0100A040
$110 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	381	B59901D0110A040
$120 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	391	B59901D0120A040
$130 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	401	B59901D0130A040
$140 \pm 5$	$\leq 550$	$\geq 1330$	$\geq 4\text{ k}$	—	411	B59901D0140A040

1)  $V_{PTC} \leq 2,5\text{ V}$



### Characteristics (typical)

PTC resistance  $R_{PTC}$  versus PTC temperature  $T_{PTC}$   
(measured at low signal voltage)



oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer E halten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständ zuholen.

**Published by EPCOS AG**

**Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY**

**☎ ++49 89 636 09, FAX (089) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the informa EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association).

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or tives.

Due to technical requirements components may contain dangerous substances. For information o also contact one of our Sales Offices.



中发网 [WWW.ZFA.CN](http://WWW.ZFA.CN)

全球最大的PDF中文下载站



**中发网**  
[www.zfa.cn](http://www.zfa.cn)

**PDF 资料下载尽在中发网**