

Overcurrent Protection

B599*5

Leaded Disks, Coated, 12 V


C 935 ... C 995

Applications

- Overcurrent and short-circuit protection

Features

- Lead-free terminals
- Manufacturer's logo and type designation stamped on in yellow
- Low resistance
- For rated currents of up to 2,1 A
- High thermal stability
- UL approval to UL 1434 (file number E69802)
- VDE approval (license number 104843 E)



TPT0647-V

Options

- Leadless disks and leaded disks without coating available on request
- Thermistors with diameter $b \leq 11,0$ mm are also available on tape (to IEC 60286-2)

Delivery mode

- Cardboard strips (standard)
- Cardboard tape reeled or in AMMO pack on request

Dimensions (mm)

Type	$b_{\max}$	$\varnothing d$	$h_{\max}$
C 935	22,0	0,6	25,5
C 945	17,5	0,6	21,0
C 955	13,5	0,6	17,0
C 965	11,0	0,6	14,5
C 975	9,0	0,6	12,5
C 985	6,5	0,6	10,0
C 995	4,0	0,5	7,5

General technical data

Max. operating voltage ($T_A = 60^\circ\text{C}$)	$V_{\max}$	20	VDC or VAC
Rated voltage	V_N	12	VDC or VAC
Switching cycles (typ.)	N	100	
Reference temperature (typ.)	T_{Ref}	160	$^\circ\text{C}$
Resistance tolerance	ΔR_N	$\pm 25\%$	
Operating temperature range ($V = 0$)	T_{op}	$-40/+125$	$^\circ\text{C}$
($V = V_{\max}$)	T_{op}	$0/+60$	$^\circ\text{C}$

Electrical specifications and ordering codes

Type	I_N mA	I_S mA	$I_{S\max}$ ($V = V_{\max}$) A	I_f (typ.) ($V = V_{\max}$) mA	I_r (typ.) ($V = V_N$) mA	R_N Ω	$R_{\min}$ Ω	Ordering code
C 935	2100	4150	10,0	240	380	0,3	0,2	B59935C0160A070
C 945	1500	3050	8,0	170	270	0,45	0,3	B59945C0160A070
C 955	950	1900	5,5	120	190	0,8	0,5	B59955C0160A070
C 965	700	1450	4,3	105	165	1,2	0,7	B59965C0160A070
C 975	550	1100	3,0	85	135	1,8	1,1	B59975C0160A070
C 985	300	600	1,0	65	100	4,6	2,7	B59985C0160A070
C 995	150	300	0,7	40	65	13	7,8	B59995C0160A070





Overcurrent Protection	B599*5
Leaded Disks, Coated, 12 V	C 935 ... C 995

Reliability data

Test	Standard	Test conditions	$ \Delta R_{25}/R_{25} $
Switching test at room temperature	IEC 60738-1	I_{Smax} V_{max} Number of cycles: 100	< 25 %
Dry heat at upper category temperature	IEC 60738-1	Storage at upper category temperature for t : 1000 h	< 25 %
Life test at V_{max}/T_{op}	IEC 60738-1	Storage at V_{max}/T_{op} for t : 1000 h	< 25 %
Storage in damp heat	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 56 days	< 10 %
Rapid change of temperature in air	IEC 60068-2-14, Test N_a	$T = T_{LCT}, T = T_{UCT}$ Number of cycles: 5 t : 30 min	< 10 %
Vibration	IEC 60068-2-6, Test F_C	$f = 10-55$ Hz $h = 0,75$ mm (respectively 10 g) t : 3 · 2 h	< 5 %
Bump	IEC 60068-2-27	Pulse shape: half-sine a : = 50 g Pulse duration: 1 ms; 6 · 3 pulses	< 5 %
Climatic sequence	IEC 60068-2-30	Dry heat: $T = T_{UCT}$ t : 16 h Damp heat first cycle Cold: $T = T_{LCT}$ t : 2 h Damp heat 5 cycles	< 10 %



Overcurrent Protection


B599*5

Leaded Disks, Coated, 12 V


C 935 ... C 995

Characteristics (typical)


PTC resistance R_{PTC} versus
PTC temperature T_{PTC}
(measured at low signal voltage)




PTC current I_{PTC} versus PTC voltage V_{PTC}
(measured at 25 °C in still air)



Switching time t_S versus switching current I_S
(measured at 25 °C in still air)



Rated current I_N versus ambient temperature T_A
(measured in still air)





Overcurrent Protection


B599*5

Leaded Disks, Coated, 12 V


C 935 ... C 995

Characteristics (typical)


PTC resistance R_{PTC} versus
PTC temperature T_{PTC}
(measured at low signal voltage)




PTC current I_{PTC} versus PTC voltage V_{PTC}
(measured at 25 °C in still air)



Switching time t_S versus switching current I_S
(measured at 25 °C in still air)



Rated current I_N versus ambient temperature T_A
(measured in still air)



fragen an unseren Kunden-Service, der Sie gerne weiterleitet. Alternativ können Sie sich auch an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer E halten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständ zuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained herein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the ZVEI (German Electrical and Electronic Manufacturers' Association).

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or your local representatives.

Due to technical requirements components may contain dangerous substances. For information on this please also contact one of our Sales Offices.



中发网 WWW.ZFA.CN

全球最大的PDF中文下载站



中发网
www.zfa.cn

PDF 资料下载尽在中发网