查询2SK3613-01供应商 捷多邦，专业PCB打样工厂，24小时加急出货

2SK3644-01

FUJI ELECTRIC

200304

FUJI POWER MOSFET
Super FAP-G Series

N-CHANNEL SILICON POWER MOSFET

■ Features

High speed switching
Low on-resistance
No secondary breadown
Low driving power
Avalanche-proof

■ Applications

Switching regulators
UPS (Uninterruptible Power Supply)
DC-DC converters

■ Outline Drawings (mm)

TO-220AB



■ Equivalent circuit schematic



■ Maximum ratings and characteristic Absolute maximum ratings

● (Tc=25°C unless otherwise specified)

Item	Symbol		Ratings	Unit
Drain-source voltage	V_{DS}		100	V
	V_{DSX} *5		70	V
Continuous drain current	I_D		±41	A
Pulsed drain current	$I_{D(puls)}$		±164	A
Gate-source voltage	V_{GS}		±30	V
Non-repetitive Avalanche current	I_{AS} *2		41	A
Maximum Avalanche Energy	E_{AS} *1		204.7	mJ
Maximum Drain-Source dV/dt	dV_{DS}/dt *4		20	kV/µs
Peak Diode Recovery dV/dt	dV/dt *3		5	kV/µs
Max. power dissipation	P_D	Ta=25°C	2.02	W
		Tc=25°C	150	
Operating and storage temperature range	T_{ch}		+150	°C
	T_{stg}		-55 to +150	°C

*1 L=146µH, Vcc=48V,Tch=25°C, See to Avalanche Energy Graph *2 Tch ≦150°C
*3 I_F≦ $-I_D$, -di/dt=50A/µs, Vcc≦BV_{DSS}, Tch≦150°C *4 V_{DS} ≦100V *5 V_{GS}=-30V

● Electrical characteristics (T_c =25°C unless otherwise specified)

Item	Symbol	Test Conditions		Min.	Typ.	Max.	Units
Drain-source breakdown voltaget	$V_{(BR)DSS}$	I_D= 250µA V_{GS}=0V		100			V
Gate threshold voltage	$V_{GS(th)}$	I_D= 250µA V_{DS}=V_{GS}		3.0		5.0	V
Zero gate voltage drain current	I_{DSS}	V_{DS}=100V V_{GS}=0V	T_{ch}=25°C			25	µA
		V_{DS}=80V V_{GS}=0V	T_{ch}=125°C			250	
Gate-source leakage current	I_{GSS}	V_{GS}=±30V V_{DS}=0V			10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	I_D=15A V_{GS}=10V			34	44	mΩ
Forward transcondutance	g_{fs}	I_D=15A V_{DS}=25V		9	18		S
Input capacitance	C_{iss}	V_{DS}=75V			1110	1665	pF
Output capacitance	C_{oss}	V_{GS}=0V			280	420	
Reverse transfer capacitance	C_{rss}	f=1MHz			22	33	
Turn-on time t_{on}	$t_{d(on)}$	V_{CC}=48V I_D=15A			16	24	ns
	t_r	V_{GS}=10V			23	35	
Turn-off time t_{off}	$t_{d(off)}$	R_{GS}=10 Ω			31	47	
	t_f				16	24	
Total Gate Charge	Q_G	V_{CC}=50V			32	48	nC
Gate-Source Charge	Q_{GS}	I_D=30A			13	20	
Gate-Drain Charge	Q_{GD}	V_{GS}=10V			9	14	
Avalanche capability	I_{AV}	L=146µH T_{ch}=25°C		41			A
Diode forward on-voltage	V_{SD}	I_F=30A V_{GS}=0V T_{ch}=25°C			1.10	1.65	V
Reverse recovery time	t_{rr}	I_F=30A V_{GS}=0V			0.1		µs
Reverse recovery charge	Q_{rr}	-di/dt=100A/µs T_{ch}=25°C			0.38		µC

● Thermalcharacteristics

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	$R_{th(ch-c)}$	channel to case			0.833	°C/W

找PDF 搜PDF pdf.dzsc.com

Characteristics

Allowable Power Dissipation
PD=f(Tc)



Maximum Avalanche Energy vs. starting Tch
E_{AS}=f(starting Tch):Vcc=48V



Typical Output Characteristics
ID=f(VDS):80µs Pulse test,Tch=25°C



Typical Transfer Characteristic
ID=f(VGS):80µs Pulse test, VDS=25V,Tch=25°C



Typical Transconductance
gfs=f(ID):80µs Pulse test, VDS=25V,Tch=25°C



Typical Drain-Source on-state Resistance
RDS(on)=f(ID):80µs Pulse test, Tch=25°C



Drain-Source On-state Resistance
RDS(on)=f(Tch):ID=15A,VGS=10V



Gate Threshold Voltage vs. Tch
VGS(th)=f(Tch):VDS=VGS,ID=1mA



Typical Gate Charge Characteristics
VGS=f(Qg):ID=30A, Tch=25°C



Typical Capacitance
C=f(VDS):VGS=0V,f=1MHz



Typical Forward Characteristics of Reverse Diode
IF=f(VSD):80µs Pulse test,Tch=25°C



Typical Switching Characteristics vs. ID
t=f(ID):Vcc=48V, VGS=10V, RG=10Ω



Maximum Avalanche Current vs Pulse width
I_{AV}=f(t_{AV}):starting Tch=25°C,Vcc=48V



Maximum Transient Thermal Impedance
Zth(ch-c)=f(t):D=0