

YG861S15R (5A)

(150V / 5A)

[0401]

High Voltage Schottky barrier diode

■ Major characteristics


Characteristics	YG861S15R	Units	Condition
V _{RRM}	150	V	
V _F	0.90	V	T _c =25°C MAX.
I _o	5	A	

■ Features

- Low V_F
- High Voltage
- Center tap connection
- High frequency operation
- DC-DC converters
- AC adapter


■ Applications

■ Outline drawings, mm



Package : TO-220F
Epoxy resin UL : V-0

■ Connection diagram



■ Maximum ratings and characteristics

- Absolute maximum ratings (at T_c=25°C Unless otherwise specified)

Item	Symbol	Conditions	Rating	Unit
Repetitive peak surge reverse voltage	V _{RSM}	t _w =500ns, duty=1/40	150	V
Repetitive peak reverse voltage	V _{RRM}		150	V
Isolating voltage	V _{iso}	Terminals-to-Case, AC.1min	1500	V
Average output current	I _o	Square wave, duty=1/2 T _c =94°C	5	A
Non-repetitive surge current	I _{FSM}	Sine wave 10ms 1shot	75	A
Operating junction temperature	T _j		+150	°C
Storage temperature	T _{stg}		-40 to +150	°C

- Electrical characteristics (at T_c=25°C Unless otherwise specified)

Item	Symbol	Conditions	Max.	Unit
Forward voltage drop	V _F	I _{FM} =5A	0.90	V
Reverse current	I _R	V _R =V _{RRM}	150	μA
Thermal resistance	R _{th(j-c)}	Junction to case	5.0	°C/W

Mechanical characteristics







Mounting torque

Recommended torque

0.3 to 0.5

N·m

■ Characteristics



(150V / 5A)

YG861S15R (5A)

