

## 89463 Twinax - Blue Hose® Cable

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

### Description:

20 AWG stranded (7x28) tinned copper conductors, FEP insulation, overall Beldfoil® (100% coverage) plus a tinned copper braid shield (76% coverage), FEP jacket.

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	20
Stranding	7x28
Conductor Diameter	.038 in.
Conductor Material	TC - Tinned Copper

#### INSULATION:

Insulation Material	FEP - Fluorinated Ethylene Propylene
---------------------	--------------------------------------

#### PAIR:

Pair Diameter	.151 in.
Pair Color Code Chart :	

Number	Color
1	Clear & Blue

#### OUTER SHIELD:

Outer Shield Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid
Outer Shield Material :	

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	76

Outer Shield % Coverage	100 %
-------------------------	-------

#### OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	7x28
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**89463 Twinax - Blue Hose® Cable**

**OUTER JACKET:**

Outer Jacket Material	FEP - Fluorinated Ethylene Propylene
-----------------------	--------------------------------------

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.203 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-70°C To +200°C
UL Temperature Rating	200°C
Bulk Cable Weight	36 lbs/1000 ft.
Max. Recommended Pulling Tension	48 lbs.
Min. Bend Radius (Install)	2.5 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CMP, CL2P
CEC/C(UL) Specification	CMP FT6
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
Customer Part Number Reference Specification	Allen Bradley P/N 1770-CD

**FLAME TEST:**

UL Flame Test	NFPA 262
---------------	----------

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	Y
Non-Plenum Number	9463

**ELECTRICAL CHARACTERISTICS:**

Nom. Characteristic Impedance	78 Ohms
Nom. Inductance	0.12 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	19.7 pF/ft
Nominal Velocity of Propagation	69 %
Nominal Delay	1.47 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	9.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance	4.1 Ohms/1000 ft
Nom. Attenuation :	

## 89463 Twinax - Blue Hose® Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.6
	10			2.1
	50			5.0
	100			7.5
	200			11.0
	400			16.0

Max. Operating Voltage - UL

300 V RMS

Other Electrical Characteristic 1

DC Resistance Unbalanced: .77 Ohms/1000 ft Max

### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
89463 0061000	2 #20 FEP FS BRD FEP	1000	34	BLUE, LIGHT	C
89463 0062500	2 #20 FEP FS BRD FEP	2500	90	BLUE, LIGHT	C

C = CRATE REEL PUT-UP.

Revision Number: 1

Revision Date: 09-09-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.