

9267 Coax - RG-59/U Type

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

20 AWG solid .032" bare copper conductor, gas-injected foam high density polyethylene insulation, paper tape separator, bare copper braid shields (95% coverage), Hypalon® jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	20
Stranding	Solid
Conductor Diameter	.032 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.145 in.

INNER SHIELD:

Inner Shield Type	Braid
Inner Shield Material	BC - Bare Copper
Inner Shield % Coverage	95 %

INNER JACKET:

Inner Jacket Material	PE - Polyethylene
Inner Jacket Diameter	.216 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield % Coverage	80 %

OUTER JACKET:

Outer Jacket Material Trade Name	Hypalon®
Outer Jacket Material	Chlorosulfinated Polyethylene

OUTER JACKET SEPARATOR :

9267 Coax - RG-59/U Type

Outer Jacket Separator Material	Paper tape
---------------------------------	------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.360 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Non-UL Temperature Rating	80°C
Bulk Cable Weight	78.5 lbs/1000 ft.
Max. Recommended Pulling Tension	124 lbs.
Min. Bend Radius (Install)	3.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	VW-1
---------------	------

SWEEP TEST:

Sweep Testing	100% Sweep tested 5 MHz to 3 GHz.
---------------	-----------------------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suitability - Aerial	Yes - When supported by a messenger wire
Suitability - Burial	Yes

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.097 μ H/ft
Nom. Capacitance Conductor to Shield	16.3 pF/ft
Nominal Velocity of Propagation	82 %
Nominal Delay	1.24 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	10.1 Ohms/1000 ft
Nom. Inner Shield DC Resistance:	2.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	2.6 Ohms/1000 ft
Minimum Structural Return Loss :	

9267 Coax - RG-59/U Type

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		5	850	21
		851	3000	15

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.3
	3.6			0.6
	10			0.9
	71.5			2.1
	135			2.9
	270			4.2
	360			4.8
	540			6.0
	720			6.7
	750			6.9
	1000			8.3
	1500			10.5
	2250			13.4
	3000			15.9

Max. Operating Voltage - Non-UL 300 V RMS

NOTES:

Notes Hypalon is a registered trademark of Dupont and has excellent durability and ruggedness in field use.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9267 0101000	#20 FPE BRD PE BRD CSM	1000	77	BLACK	C
9267 010500	#20 FPE BRD PE BRD CSM	500	39.5	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 05-04-2006

9267 Coax - RG-59/U Type

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.