

9268 Coax - 93 Ohm

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

93 ohm, RG-62A/U type, 22 AWG solid .025" bare copper-covered steel conductor, semi-solid polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	62A/U
AWG	22
Stranding	Solid
Conductor Diameter	.025 in.
Conductor Material	BCCS - Bare Copper Covered Steel

INSULATION:

Insulation Material	Semi-Solid PE - Semi-Solid Polyethylene
Insulation Diameter	.146 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield % Coverage	95 %

OUTER SHIELD SEPARATOR :

Outer Shield Separator Material	Polyester Tape
---------------------------------	----------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.260 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
UL Temperature Rating	60°C (UL AWM Style 1478)
Bulk Cable Weight	37 lbs/1000 ft.
Max. Recommended Pulling Tension	84 lbs.

9268 Coax - 93 Ohm

Min. Bend Radius (Install)	2.5 in.
----------------------------	---------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, CL2
CEC/C(UL) Specification	CM
AWM Specification	UL Style 1478 (30 V 60°C)
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
Customer Part Number Reference Specification	IBM P/N 5252750

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	93 Ohms
Nom. Inductance	0.116 μ H/ft
Nom. Capacitance Conductor to Shield	13.5 pF/ft
Nominal Velocity of Propagation	84 %
Nominal Delay	1.21 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	41.2 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	2.9 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.3
	10			0.9
	50			1.9
	100			2.7
	200			3.8
	400			5.3
	700			7.3
	900			8.2
	1000			8.7

Max. Operating Voltage - UL	300 V RMS (CM), 30 V RMS (UL AWM Style 1478), 150 V RMS (CL2)
-----------------------------	---

Max. Operating Voltage - Non-UL	750 V RMS
---------------------------------	-----------

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
------	-------------	--------------	--------------------	--------------	-------

9268 Coax - 93 Ohm

9268 010U1000	RG-62A/U TYPE COAX	U1000	42	BLACK	
9268 0101000	RG-62A/U TYPE COAX	1000	44	BLACK	C
9268 0102000	RG-62A/U TYPE COAX	2000	88	BLACK	C
9268 010500	RG-62A/U TYPE COAX	500	20	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-08-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.