

## 9408 Paired - 300V Power-Limited Tray Cable

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : ICEA Table E2.pdf</p>
--	--

### Description:

20 AWG pairs stranded (19x32) tinned copper conductors, twisted pairs, PVC insulation, unshielded, PVC jacket.

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	20
Stranding	19x32
Conductor Material	TC - Tinned Copper

#### INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Diameter	.068 in.

#### Pair Color Code Chart :

Number	Color
1	Black & Red

### OVERALL CABLING:

Overall Cabling Direction	Left-hand Lay
---------------------------	---------------

### OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

### OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.037 in.
Outer Jacket Ripcord	Yes

### OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.214 in.
--------------------------	----------

### MECHANICAL CHARACTERISTICS:

## 9408 Paired - 300V Power-Limited Tray Cable

Operating Temperature Range	-30°C To +105°C
Bulk Cable Weight	23 lbs/1000 ft.
Max. Recommended Pulling Tension	31 lbs.
Min. Bend Radius (Install)	2 in.

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

NEC/(UL) Specification	PLTC, ITC, CMG
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

#### FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT4
IEEE Flame Test	1202
ICEA Flame Test	T-29-520

#### SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suitability - Burial	Yes
Sunlight Resistance	Yes

#### PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

#### ELECTRICAL CHARACTERISTICS:

Nom. Inductance	.19 µH/ft
Nom. Capacitance Conductor to Shield @ 1 KHz	55 pF/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	30 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	9.5 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (PLTC, CMG), 150 V RMS (ITC)
Max. Recommended Current	7.6 Amps per conductor @ 25°C

#### PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9408 060U1000	2 #20 PVC PVC	U1000	23	CHROME	
9408 060U500	2 #20 PVC PVC	U500	12	CHROME	

---

## **9408 Paired - 300V Power-Limited Tray Cable**

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.