

9923 Hook-up/Lead - UL AWM Style 1007 and 1569





For more information please call 1-800-Belden1

See Put-ups and Colors

Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 300V. Rated 600V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1	
Total Number of Conductors	1	
AWG	24	
Stranding	7x32	
Conductor Material	TC - Tinned Copper	

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.015 in.

OVERALL:

Overall Nominal Diameter .056 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)			
UL Rating	300 V RMS, 80°C and 300 V, 105°C			
CSA Type	TR-64, TRSR-64			
CSA Rating	300 V RMS, 90°C and 300 V, 105°C			
EU CE Mark (Y/N)	Yes			
EU RoHS Compliant (Y/N)	Yes			
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005			
Other Specification	JQA-F-			

FLAME TEST:

UL Flame Test V	√W-1

PLENUM/NON-PLENUM:

Plenum (Y/N) N



9923 Hook-up/Lead - UL AWM Style 1007 and 1569

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9923 001100	24 STR PVC BRN	100	0.3	BROWN	
9923 0011000	24 STR PVC BRN	1000	4	BROWN	P
9923 0015000	#24 STR PVC BRN	5000	15	BROWN	С
9923 002100	24 STR PVC RED	100	0.3	RED	
9923 0021000	24 STR PVC RED	1000	4	RED	P
9923 0025000	#24 STR PVC RED	5000	15	RED	P
9923 0031000	24 STR PVC ORG	1000	4	ORANGE	P
9923 0035000	#24 STR PVC ORG	5000	15	ORANGE	СР
9923 004100	24 STR PVC YEL	100	0.3	YELLOW	
9923 0041000	24 STR PVC YEL	1000	4	YELLOW	P
9923 0045000	#24 STR PVC YEL	5000	15	YELLOW	С
9923 005100	24 STR PVC DGRN	100	0.3	GREEN, DARK	
9923 0051000	24 STR PVC GRN	1000	4	GREEN, DARK	P
9923 0055000	#24 STR PVC DGRN	5000	15	GREEN, DARK	P
9923 0071000	24 STR PVC VIO	1000	4	VIOLET	P
9923 0075000	#24 STR PVC VIO	5000	15	VIOLET	С
9923 0081000	24 STR PVC GRY	1000	4	GRAY	P
9923 0085000	#24 STR PVC GRY	5000	15	GRAY	P
9923 009100	24 STR PVC WHT	100	0.3	WHITE	
9923 0091000	24 STR PVC WHT	1000	4	WHITE	P
9923 0095000	#24 STR PVC WHT	5000	15	WHITE	P
9923 010100	24 STR PVC BLK	100	0.3	BLACK	
9923 0101000	24 STR PVC BLK	1000	4	BLACK	P
9923 0105000	#24 STR PVC BLK	5000	15	BLACK	С
9923 0131000	24 STR PVC D BLU	1000	4	BLUE, DARK	P
9923 0135000	#24 STR PVC DBLU	5000	15	BLUE, DARK	С

Detailed Specifications & Technical Data



9923 Hook-up/Lead - UL AWM Style 1007 and 1569

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 10-06-2005

© Copyright 2006 Belden, Inc All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Damping Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product Disclosure is not to be considered a warranty or legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.