

RS2AF THRU RS2MF-HAF

Surface Mount Fast Recovery Rectifier

Reverse Voltage - 50 to 1000 V


Forward Current - 2 A

Features

- Glass Passivated Chip Junction
- For surface mounted applications
- Low profile package
- Fast reverse recovery time
- Halogen and Antimony Free(HAF), RoHS compliant

Mechanical Data

- **Case:** SMAF
- **Terminals:** Solderable per MIL-STD-750, Method 2026



All Dimensions in mm

Absolute Maximum Ratings and Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Symbols	RS2AF	RS2BF	RS2DF	RS2GF	RS2JF	RS2KF	RS2MF	Units
	Marking	RS2A	RS2B	RS2D	RS2G	RS2J	RS2K	RS2M	-
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_a = 65^\circ\text{C}$	$I_{F(AV)}$	2							A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	50							A
Maximum Forward Voltage at 2 A	V_F	1.3							V
Maximum Reverse Current at Rated DC Blocking Voltage $T_a = 25^\circ\text{C}$ $T_a = 125^\circ\text{C}$	I_R	5 100							μA
Maximum Reverse Recovery Time at $I_F = 0.5\text{ A}$, $I_R = 1\text{ A}$, $t_{rr} = 0.25\text{ A}$	t_{rr}	150				250	500		ns
Typical Junction Capacitance at $V_R = 4\text{ V}$, $f = 1\text{ MHz}$	C_j	40							pF
Typical Thermal Resistance ¹⁾	$R_{\theta JA}$	75							$^\circ\text{C/W}$
Operating Junction and Storage Temperature Range	T_j, T_{stg}	- 55 to + 150							$^\circ\text{C}$

¹⁾ P.C.B. mounted with 0.5 X 0.5" (12.7 X 12.7 mm) copper pad areas.


TOP DYNAMIC




Dated: 14/12/2015 JD Rev: 01

RS2AF THRU RS2MF-HAF


Forward Current Derating Curve




Typical Reverse Characteristics




Typical Instantaneous Forward Characteristics



Typical Junction Capacitance



Maximum Non-Repetitive Peak Forward Surge Current



TOP DYNAMIC