



MMFTP2301

P-Channel Enhancement Mode MOSFET



1. Gate 2. Source 3. Drain
SOT-23 Plastic Package



Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$-V_{DSS}$	20	V
Gate-Source Voltage	V_{GS}	± 8	V
Drain Current - Continuous	$-I_D$	2.3	A
Drain Current - Pulse ¹⁾	$-I_{DM}$	8	A
Power Dissipation ($t \leq 10$ s)	P_{tot}	0.9	W
Operating Junction Temperature	T_j	- 55 to + 150	°C
Storage Temperature	T_{stg}	- 55 to + 150	°C

¹⁾ Repetitive Rating: Pulse width limited by maximum junction temperature.

MMFTP2301

Characteristics at $T_a = 25^\circ\text{C}$ unless otherwise specified






Parameter	Symbol	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage at $-I_D = 250 \mu\text{A}$	$-V_{(BR)DSS}$	20	-	-	V
Drain-Source Leakage Current at $-V_{DS} = 9.6 \text{ V}$	$-I_{DSS}$	-	-	1	μA
Gate Leakage Current at $V_{GS} = \pm 8 \text{ V}$	I_{GSS}	-	-	± 100	nA
Gate-Source Threshold Voltage at $V_{DS} = V_{GS}$, $-I_D = 250 \mu\text{A}$	$-V_{GS(th)}$	0.45	-	0.95	V
Drain-Source On-State Resistance at $-V_{GS} = 2.5 \text{ V}$, $-I_D = 2 \text{ A}$	$R_{DS(on)1}$	-	-	150	m Ω
Drain-Source On-State Resistance at $-V_{GS} = 4.5 \text{ V}$, $-I_D = 2.8 \text{ A}$	$R_{DS(on)2}$	-	-	100	m Ω
Forward Transconductance at $-V_{DS} = 5 \text{ V}$, $-I_D = 4 \text{ A}$	g_{FS}	-	6.5	-	S
Input Capacitance at $-V_{DS} = 6 \text{ V}$, $f = 1 \text{ MHz}$	C_{iss}	-	882.51	-	pF
Output Capacitance at $-V_{DS} = 6 \text{ V}$, $f = 1 \text{ MHz}$	C_{oss}	-	145.54	-	pF
Reverse Transfer Capacitance at $-V_{DS} = 6 \text{ V}$, $f = 1 \text{ MHz}$	C_{rss}	-	97.26	-	pF
Turn-On Delay Time at $-V_{DD} = 6 \text{ V}$, $-V_{GEN} = 4.5 \text{ V}$, $-I_D = 1 \text{ A}$, $R_G = 6 \Omega$, $R_L = 6 \Omega$	$t_{d(on)}$	-	17.28	-	ns
Turn-Off Delay Time at $-V_{DD} = 6 \text{ V}$, $-V_{GEN} = 4.5 \text{ V}$, $-I_D = 1 \text{ A}$, $R_G = 6 \Omega$, $R_L = 6 \Omega$	$t_{d(off)}$	-	36.05	-	ns
Turn-On Rise Time at $-V_{DD} = 6 \text{ V}$, $-V_{GEN} = 4.5 \text{ V}$, $-I_D = 1 \text{ A}$, $R_G = 6 \Omega$, $R_L = 6 \Omega$	t_r	-	3.73	-	ns
Turn-Off Fall Time at $-V_{DD} = 6 \text{ V}$, $-V_{GEN} = 4.5 \text{ V}$, $-I_D = 1 \text{ A}$, $R_G = 6 \Omega$, $R_L = 6 \Omega$	t_f	-	6.19	-	ns

TOP DYNAMIC



Dated: 28/04/2014 Rev: 05 CL

MMFTP2301



TOP DYNAMIC



Dated: 28/04/2014 Rev: 05 CL