


Features

- Schottky Brrier Chip
- Low Power Loss,High Efficiency
- Ideally Suited for Automatic Assembly
- Surge Overload Rating to 60A Peak
- Plastic Case Material has UL Flammability Classification Rating 94V-0

Mechanical Data

- Case: Moeded plastic SMA
- Terminals: Plated leads solderable per MIL-STD-750,Method 2026 guaranteed
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- Making: Type Number



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified

Single phase,half wave,60Hz,resistive or inductive load

For capacitive load derate current by 20%

Type Number	SYMBOL	SS 22U	SS 23U	SS 24U	SS 245U	SS 25U	SS 26U	SS 28U	SS 210U	SS 215U	SS 220U	SS 225U	Unit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	45	50	60	80	100	150	200	250	V
Maximum RMS Voltage	V _{RMS}	14	21	28	31	35	42	56	70	105	140	175	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	45	50	60	80	100	150	200	250	V
Average Rectified Output Current @T _A =90℃	I _o	2.0											A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	60											A
Forward Voltage @IF=2.0A	V _{FM}	0.50				0.67		0.82		0.90		0.95	V
Peak Reverse Current @T _A =25℃	I _R	0.1						0.05					mA
At Rated DC Blocking Voltage @T _A =100℃		10						5					
Typical Junction Capacitance (Note 2)	C _J	28											pF
Typical Thermal Resistance per leg	R _{θ JL}	88											℃ /W
Operating Temperature Range	T _J	-55 to+150											℃
Storage Temperature Range	T _{STG}	-55 to +150											℃

Note: 1.Pulse Test with PW=300usec,1%Duty Cycle.

2.Mounted on P.C.Board with 5.0 mm² (0.13mm thick) copper pad areas.

SS22U THRU SS225U

Fig. 1 Forward Current Derating Curve




Fig. 2 Typ. Forward Characteristics




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Reverse Characteristics (per element)

