


Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency
- High temperature soldering guaranteed:
260°C / 10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

SOD-123FL



Dimensions in inches and (millimeters)

Mechanical Data

- Case: SOD-123FL, molded plastic
- Terminals: plated leads solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting position: Any

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	DSS32	DSS33	DSS34	DSS35	DSS36	DSS38	DSS310	DSS315	DSS320	DSS325	UNITS
	Code	D32	D33	D34	D35	D36	D38	D310	D315	D320	D325	
Peak Repetitive Reverse Voltage	V_{RRM}											V
Working Peak Reverse Voltage	V_{RWM}	20	30	40	50	60	80	100	150	200	250	
DC Blocking Voltage	V_{DC}											
RMS Reverse Voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	175	V
Average Rectified Output Current @ $T_A = 90^\circ C$	I_o	3.0										A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	80										A
Forward Voltage per element @ $I_F = 3.0A$	V_{FM}	0.55			0.7		0.85		0.92		0.95	V
Peak Reverse Current @ $T_A = 25^\circ C$ At Rated DC Blocking Voltage @ $T_A = 100^\circ C$	I_R	0.1					0.05					uA
		10					5					
Operating junction temperature range	T_J	-55to+150										°C/W
Operating and Storage Temperature Range	T_{STG}	-55to+150										°C

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS

