





**SCHOTTKY DIODE**
**FEATURES**

- Low Forward Voltage
- Fast Switching

**SOT-23**

**BAS40 MARKING: 43•**

**BAS40-06 MARKING: 46**

**BAS40-05 MARKING: 45**

**BAS40-04 MARKING: 44**
**Maximum Ratings @ $T_A=25^\circ\text{C}$** 

Parameter	Symbol	Limits	Unit
Peak repetitive peak reverse voltage	$V_{RRM}$		
Working peak reverse voltage	$V_{RWM}$	40	V
DC Blocking Voltage	$V_R$		
Forward continuous Current	$I_{FM}$	200	mA
Power Dissipation	$P_D$	200	mW
Thermal Resistance. Junction to Ambient Air	$R_{\theta JA}$	625	°C/W
Junction temperature	$T_J$	125	°C
Storage temperature range	$T_{STG}$	-65-125	°C

**ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)**

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)}$	$I_R = 10\mu\text{A}$	40		V
Reverse voltage leakage current	$I_R$	$V_R=30\text{V}$		200	nA
Forward voltage	$V_F$	$I_F=1\text{mA}$ $I_F=40\text{mA}$		380 1000	mV
Diode capacitance	$C_D$	$V_R=0, f=1\text{MHz}$		5	pF
Reverse Recovery time	$t_{rr}$	$I_{rr}=1\text{mA}, I_R=I_F=10\text{mA}$ $R_L=100\Omega$		5	nS

## Typical Characteristics

