



SEMICONDUCTOR™

CD4099BC 8-Bit Addressable Latch

General Description

The CD4099BC is an 8-bit addressable latch with three address inputs (A0–A2), an active low enable input (\bar{E}), active high clear input (CL), a data input (D), and eight outputs (Q0–Q7).

Data is entered into a particular bit in the latch when that bit is addressed by the address inputs and the enable (\bar{E}) is LOW. Data entry is inhibited when enable (\bar{E}) is HIGH.

When clear (CL) and enable (\bar{E}) are HIGH, all outputs are LOW. When clear (CL) is HIGH and enable (\bar{E}) is LOW, the channel demultiplexing occurs. The bit that is addressed has an active output which follows the data input while all unaddressed bits are held LOW. When operating in the addressable latch mode ($\bar{E} = CL = LOW$), changing more than one bit of the address could impose a transient wrong

October 1987
Revised January 1999

CD4099BC 8-Bit Addressable Latch

address. Therefore, this should only be done while in the memory mode ($\bar{E} = HIGH$, CL = LOW).


Features

- Wide supply voltage range: 3.0V to 15V
- High noise immunity: 0.45 V_{DD} (typ.)
- Low power TTL: fan out of 2 driving 74LS compatibility: or 1 driving 74LS
- Serial to parallel capability
- Storage register capability
- Random (addressable) data entry
- Active high demultiplexing capability
- Common active high clear

Ordering Code:

Order Number	Package Number	Package Description
CD4099BCN	N16E	16-Lead Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide


Connection Diagram



Truth Table

Mode Selection				
\bar{E}	CL	Addressed Latch	Unaddressed Latch	Mode
L	L	Follows Data	Holds Previous Data	Addressable Latch
H	L	Holds Previous Data	Holds Previous Data	Memory
L	H	Follows Data	Reset to "0"	Demultiplexer
H	H	Reset to "0"	Reset to "0"	Clear

Logic Diagram



Absolute Maximum Ratings (Note 1)

(Note 2)

DC Supply Voltage (V_{DD})	-0.5 to +18 V_{DC}
Input Voltage (V_{IN})	-0.5 to V_{DD} +0.5 V_{DC}
Storage Temperature Range (T_S)	-65°C to +150°C
Power Dissipation (P_D)	
Dual-In-Line	700 mW
Small Outline	500 mW
Lead Temperature (T_L)	
(Soldering, 10 seconds)	260°C

Recommended Operating Conditions (Note 2)DC Supply Voltage (V_{DD}) 3.0 to 15 V_{DC} Input Voltage (V_{IN}) 0 to V_{DD} V_{DC} Operating Temperature Range (T_A) -40°C to +85°C

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed; they are not meant to imply that the devices should be operated at these limits. The tables of "Recommended Operating Conditions" and "Electrical Characteristics" provide conditions for actual device operation.

Note 2: $V_{SS} = 0V$ unless otherwise specified.

DC Electrical Characteristics (Note 2)

Symbol	Parameter	Conditions	-40°C		+25°C			+85°C		Units
			Min	Max	Min	Typ	Max	Min	Max	
I_{DD}	Quiescent Device Current	$V_{DD} = 5V, V_{IN} = V_{DD}$ or V_{SS}	20		0.02	20		150		μA
		$V_{DD} = 10V, V_{IN} = V_{DD}$ or V_{SS}	40		0.02	40		300		μA
		$V_{DD} = 15V, V_{IN} = V_{DD}$ or V_{SS}	80		0.02	80		600		μA
V_{OL}	LOW Level Output Voltage	$ I_O \leq 1\mu A$			0	0.05		0.05		V
		$V_{DD} = 5V$	0.05		0	0.05		0.05		V
		$V_{DD} = 10V$	0.05		0	0.05		0.05		V
		$V_{DD} = 15V$	0.05		0	0.05		0.05		V
V_{OH}	HIGH Level Output Voltage	$ I_O \leq 1\mu A$			4.95	5		4.95		V
		$V_{DD} = 5V$	4.95		9.95	10		9.95		V
		$V_{DD} = 10V$	9.95		14.95	15		14.95		V
		$V_{DD} = 15V$	14.95							V
V_{IL}	LOW Level Input Voltage	$V_{DD} = 5V, V_O = 0.5V$ or $4.5V$		1.5	2.25	1.5		1.5		V
		$V_{DD} = 10V, V_O = 1.0V$ or $9.0V$	3.0		4.5	3.0		3.0		V
		$V_{DD} = 15V, V_O = 1.5V$ or $13.5V$	4.0		6.75	4.0		4.0		V
V_{IH}	HIGH Level Input Voltage	$V_{DD} = 5V, V_O = 0.5V$ or $4.5V$	3.5		3.5	2.75		3.5		V
		$V_{DD} = 10V, V_O = 1.0V$ or $9.0V$	7.0		7.0	5.5		7.0		V
		$V_{DD} = 15V, V_O = 1.5V$ or $13.5V$	11.0		11.0	8.25		11.0		V
I_{OL}	LOW Level Output Current (Note 3)	$V_{DD} = 5V, V_O = 0.4V$	0.52		0.44	0.88		0.36		mA
		$V_{DD} = 10V, V_O = 0.5V$	1.3		1.1	2.25		0.9		mA
		$V_{DD} = 15V, V_O = 1.5V$	3.6		3.0	8.8		2.4		mA
I_{OH}	HIGH Level Output Current (Note 3)	$V_{DD} = 5V, V_O = 4.6V$	-0.52		-0.44	-0.88		-0.36		mA
		$V_{DD} = 10V, V_O = 9.5V$	-1.3		-1.1	-2.25		-0.9		mA
		$V_{DD} = 15V, V_O = 13.5V$	-3.6		-3.0	-8.8		-2.4		mA
I_{IN}	Input Current	$V_{DD} = 15V, V_{IN} = 0V$		-0.30		-10 ⁻⁵	-0.30		-1.0	μA
		$V_{DD} = 15V, V_{IN} = 15V$	0.30		10 ⁻⁵	0.30		1.0		μA


Note 3: I_{OH} and I_{OL} are tested one output at a time.


AC Electrical Characteristics (Note 4) $T_A = 25^\circ C$, $C_L = 50 \text{ pF}$, $R_L = 200\text{k}$, Input $t_r = t_f = 20 \text{ ns}$, unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
t_{PHL}, t_{PLH}	Propagation Delay Data to Output	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		200 75 50	400 150 100	ns ns ns
t_{PLH}, t_{PHL}	Propagation Delay Enable to Output	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		200 80 60	400 160 120	ns ns ns
t_{PHL}	Propagation Delay Clear to Output	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		175 80 65	350 160 130	ns ns ns
t_{TLH}, t_{THL}	Propagation Delay Address to Output	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		225 100 75	450 200 150	ns ns ns
t_{THL}, t_{TLH}	Transition Time (Any Output)	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		100 50 40	200 100 80	ns ns ns
T_{WH}, T_{WL}	Minimum Data Pulse Width	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		100 50 40	200 100 80	ns ns ns
t_{WH}, t_{WL}	Minimum Address Pulse Width	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		200 100 65	400 200 125	ns ns ns
t_{WH}	Minimum Clear Pulse Width	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		75 40 25	150 75 50	ns ns ns
t_{SU}	Minimum Set-Up Time Data to E	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		40 20 15	80 40 30	ns ns ns
t_H	Minimum Hold Time Data to E	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		60 30 25	120 60 50	ns ns ns
t_{SU}	Minimum Set-Up Time Address to E	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		-15 0 0	50 30 20	ns ns ns
t_H	Minimum Hold Time Address to E	$V_{DD} = 5V$ $V_{DD} = 10V$ $V_{DD} = 15V$		-50 -20 -15	15 10 5	ns ns ns
C_{PD}	Power Dissipation Capacitance	Per Package (Note 5)		100		pF
C_{IN}	Input Capacitance	Any Input		5.0	7.5	pF

Note 4: AC Parameters are guaranteed by DC correlated testing.

Note 5: Dynamic power dissipation (P_D) is given by: $P_D = (C_{PD} + C_L) V_{CC}^2 f + P_Q$; where C_L = load capacitance; f = frequency of operation; for further details, see application note AN-90, "54C/74C Family Characteristics".

Switching Time Waveforms

Physical Dimensions inches (millimeters) unless otherwise noted

16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
Package Number N16E

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com