

AMC Doc. #: AMC317_A
November 2001



ADD MICROTECH CORP.

AMC317

1.5A / 3-TERMINAL ADJUSTABLE REGULATOR

DESCRIPTION

The AMC317 series is a 3-terminal adjustable regulator featuring output current of typical 1.5A over a wide output range from 1.2V to 37V. Only two external resistors are required to set the output voltage. This feature provides better line and load regulation than fixed regulators.

Also, the AMC317 series offers full overload protection, current limit, and thermal protection features. In most applications, no capacitor is required for the AMC317. However, if the device is located far from the input filter capacitor, then an input bypass will be required. Also, in order to improve the transient response, an output capacitor is recommended.


FEATURES

- Output current capability of 1.5A
- Wide output voltage range – adjustable from 1.2V to 37V
- Ripple rejection typically 80 dB
- Typically 0.1% load regulation
- Built-in over current, over temperature and overload protection.
- Internal thermal overload protection
- Available in 3-Lead TO-220, and surface mount 3-Lead TO-263.
- Identical pin assignment to earlier LM317 series.


APPLICATIONS

- Voltage Regulators
- Power Supplies
- Current Regulators
- Switching Regulators
- Current Limiter
- Constant Current Battery Charger
- Current Limited Charger

PACKAGE PIN OUT




3-Pin Plastic TO-220
(Top View)



3-Pin Plastic TO-263
Surface Mount
(Top View)

ORDER INFORMATION

T _A (°C)	T	Plastic TO-220 3-pin	ST	Plastic TO-263 3-pin
0 to 70	AMC317T			AMC317ST
Note: All surface-mount packages are available in Tape & Reel. Append the letter "T" to part number (i.e. AMC317STT).				

TYPICAL APPLICATION

Note 1: C_{IN} is required if the regulator is far from the filter capacitor.

Note 2: C_{OUT} is recommended to improve the transient response.

$$\text{Note 3: } V_{OUT} = 1.25V \left(1 + \frac{R_2}{R_1} \right) + I_{ADJ}(R_2)$$

ABSOLUTE MAXIMUM RATINGS (Note 1)

Input-Output Differential Voltage V_D	40V
Operating Junction temperature	
Plastic (T, ST Package)	150°C
Storage Temperature Range	-65°C to 150°C
Lead temperature (Soldering, 10 seconds)	300°C

Note 1: Exceeding these ratings could cause damage to the device. All voltages are with respect to Ground. Currents are positive into, negative out of the specified terminal.

THERMAL DATA**T, ST PACKAGE:**

Thermal Resistance-Junction to Tab, θ_{JT}	3.0°C/W
Thermal Resistance-Junction to Ambient, θ_{JA}	45°C/W

Junction Temperature Calculation: $T_J = T_A + (P_D \times \theta_{JA})$.

The θ_{JA} numbers are guidelines for the thermal performance of the device/pc-board system.

All of the above assume no ambient airflow.

Maximum Power Calculation:

$$P_{D(MAX)} = \frac{T_{J(MAX)} - T_{A(MAX)}}{\theta_{JA}}$$

T_J (°C): Maximum recommended junction temperature

T_A (°C): Ambient temperature of the application

θ_{JA} (°C/W): Junction-to-junction temperature thermal resistance of the package, and other heat dissipating materials.

The maximum power dissipation for a single-output regulator is :

$$P_{D(MAX)} = [(V_{IN(MAX)} - V_{OUT(NOM)})] \times I_{OUT(NOM)} + V_{IN(MAX)} \times I_Q$$

Where: $V_{OUT(NOM)}$ = the nominal output voltage

$I_{OUT(NOM)}$ = the nominal output current, and

I_Q = the quiescent current the regulator consumes at $I_{OUT(MAX)}$

$V_{IN(MAX)}$ = the maximum input voltage







Then $\theta_{JA} = (150°C - T_A)/P_D$


RECOMMENDED OPERATING CONDITIONS					
Parameter	Symbol	Recommended Operating Conditions			Units
		Min.	Typ.	Max.	
Input-Output differential Voltage	V _D	3		40	V
Load Current (with adequate heatsinking)	I _O	10		1500	mA
Input Capacitor (V _{IN} to GND)			0.1		μF
Output Capacitor with ESR of 10Ω max., (V _{OUT} to GND)			1.0		μF

ELECTRICAL CHARACTERISTICS						
Parameter	Symbol	Test Conditions	AMC317			Units
			Min.	Typ.	Max.	
Reference Voltage	V _{REF}	3V ≤ V _{IN} – V _{OUT} ≤ 40V, 10mA ≤ I _{OUT} ≤ 1.5A, P ≤ 15W	1.20	1.25	1.30	V
Line Regulation (see note 2)	ΔV _{OL}	3V ≤ V _{IN} – V _{OUT} ≤ 40V, T _J = 25°C		0.01	0.04	%/V
		3V ≤ V _{IN} – V _{OUT} ≤ 40V		0.02	0.07	
Load regulation	ΔV _{OL}	10mA ≤ I _{OUT} ≤ 1.5A, T _J = 25°C		0.1	0.5	%
		10mA ≤ I _{OUT} ≤ 1.5A		0.3	1.5	
Minimum Load Current	I _{OUT(MIN)}	V _{IN} – V _{OUT} ≤ 40V		3.5	10	mA
Adjustment Pin Current	I _{ADJ}			50	100	μA
Adjustment Pin Current Change	ΔI _{ADJ}	3V ≤ V _{IN} – V _{OUT} ≤ 40V 10mA ≤ I _{OUT} ≤ 1.5A		0.2	5.0	μA
Current Limit	I _{CL}	(V _{IN} – V _{OUT}) ≤ 15V		1.5	2.2	A
		(V _{IN} – V _{OUT}) ≤ 24V		0.8	1.1	
		(V _{IN} – V _{OUT}) = 40V		0.15	0.4	
Ripple Rejection Ratio (Note 3)	R _R	V _{OUT} = 10V, f = 120Hz			65	dB
		V _{OUT} = 10V, f = 120Hz, 10μF capacitor between ADJ and GND		66	80	
Output Noise Voltage (Note 3)	V _{O RMS}	10Hz ≤ f ≤ 10KHz, T _J = 25°C		0.003		%
Long Term Stability (Note 3)		T _J = 125°C, and V _{IN} – V _{OUT} = 40V		0.3	1	%/1000hr
Temperature Stability (Note 3)	ΔV _{O(Temp)}	T _{MIN} ≤ T _J ≤ T _{MAX}			1	%


Note 2: Line regulation is defined as the percentage change in output voltage every 1V change at the input

Note 3: These parameters, although guaranteed, are not tested in production prior to shipment

TYPICAL APPLICATIONS**5V Logic Regulator with Shutdown**(Minimum output $\approx 1.2V$)**Adjustable Regulator with Improved Ripple****Rejection****1A Current Regulator****1.2V - 20V Regulator with Minimum Current (≈ 4 mA)****12V Battery Charger****Current Limited 6V Charger**(Peak Current = 0.6A with 1Ω resistor)

1.5A / 3-Terminal Adjustable Regulator**3-Pin Plastic TO-220**


	INCHES			MILLIMETERS		
	MIN	TYP	MAX	MIN	TYP	MAX
A	0.140	-	0.190	3.56	-	4.83
b1	0.045	-	0.070	1.14	-	1.78
b	0.020	-	0.045	0.51	-	1.14
c	0.012	-	0.045	0.30	-	1.14
D	0.560	-	0.650	14.22	-	16.51
E	0.380	-	0.420	9.65	-	10.67
e	0.090	-	0.110	2.29	-	2.79
e1	0.190	-	0.210	4.83	-	5.33
F	0.020		0.055	0.51	-	1.40
H1	0.230	-	0.270	5.84	-	6.86
J1	0.080	-	0.115	2.03	-	2.92
L	0.500	-	0.580	12.7	-	14.73
P	0.139	-	0.161	3.53	-	4.09
Q	0.100	-	0.135	2.54	-	3.43
L1	-	-	0.250	-	-	6.35

3-Pin Surface Mount TO-263


	INCHES			MILLIMETERS		
	MIN	TYP	MAX	MIN	TYP	MAX
A	0.160	-	0.190	4.06	-	4.83
b	0.020	-	0.039	0.51	-	0.99
b2	0.045	-	0.055	1.14	-	1.40
c	0.015 TYP.			0.38 TYP.		
c2	0.045	-	0.055	1.14	-	1.40
D	0.340	-	0.380	8.64	-	9.65
E	0.380	-	0.405	9.65	-	10.29
e	0.100 BSC			2.54 BSC		
L	0.575	-	0.625	14.61	-	15.88
L1	0.090	-	0.110	2.29	-	2.79
L2	-	-	0.115	-	-	2.92
L3	0.050	-	0.070	1.27	-	1.78

IMPORTANT NOTICE

ADD Microtech (ADDM) reserves the right to make changes to its products or to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

A few applications using integrated circuit products may involve potential risks of death, personal injury, or severe property or environmental damage. ADDM integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life-support applications, devices or systems or other critical applications. Use of ADDM products in such applications is understood to be fully at the risk of the customer. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

ADDM assumes no liability to customer product design or application support. ADDM warrants the performance of its products to the specifications applicable at the time of sale.

U.S.

**ADD Microtech Inc.
492 Altamont Drive
Milpitas, CA 95035**

**TEL: (408) 9410420
FAX: (408) 9410864**

Asia Pacific region

**ADD Microtech Corp
3F, 132, Sec. 4, Chung Hsiao E. Rd.,
Taipei, Taiwan**

**TEL: 2-27760166
FAX: 2-27764208**