



**ALPHA & OMEGA**  
SEMICONDUCTOR, LTD.

Rev 3: June 2004



## AO4408, AO4408L (Green Product) N-Channel Enhancement Mode Field Effect Transistor

### General Description

The AO4408 uses advanced trench technology to provide excellent  $R_{DS(ON)}$ , low gate charge and fast switching. This device makes an excellent high side switch for notebook CPU core DC-DC conversion. AO4408L(Green Product) is offered in a lead-free package.

### Features

$V_{DS} (V) = 30V$   
 $I_D = 12A$   
 $R_{DS(ON)} < 13m\Omega (V_{GS} = 10V)$   
 $R_{DS(ON)} < 16m\Omega (V_{GS} = 4.5V)$



### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Continuous Drain Current <sup>A</sup>	$I_D$	12	A
$T_A=70^\circ C$		10	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	80	
Avalanche Current <sup>B,E</sup>	$I_{AV}$	30	A
Repetitive Avalanche Energy <sup>B,E</sup> $L=0.1mH$	$E_{AV}$	100	mJ
Power Dissipation	$P_D$	3	W
$T_A=70^\circ C$		2.1	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	23	40	°C/W
Steady-State		48	65	°C/W
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	12	16	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=24\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		0.003	1	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 12\text{V}$			100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1	1.5	2.5	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	40			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=12\text{A}$ $T_J=125^\circ\text{C}$		10.5	14	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}, I_D=10\text{A}$		16	21	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=10\text{A}$	30	48		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=10\text{A}, V_{GS}=0\text{V}$		0.76	1	V
$I_S$	Maximum Body-Diode Continuous Current				4.5	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		1020	1200	pF
$C_{\text{oss}}$	Output Capacitance			320		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			80		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.25	0.5	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=15\text{V}, I_D=12\text{A}$		10.3	12.5	nC
$Q_{\text{gs}}$	Gate Source Charge			2.1		nC
$Q_{\text{gd}}$	Gate Drain Charge			3.9		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=1.2\Omega, R_{\text{GEN}}=3\Omega$		3.9	5.5	ns
$t_r$	Turn-On Rise Time			3	6	ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			19.2	30	ns
$t_f$	Turn-Off Fall Time			2.6	5	ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=12\text{A}, dI/dt=100\text{A}/\mu\text{s}$		26	32	ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=12\text{A}, dI/dt=100\text{A}/\mu\text{s}$		18	32	nC

A: The value of  $R_{\text{JJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design. The current rating is based on the  $t \leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to lead  $R_{\text{JUL}}$  and lead to ambient.

D: The static characteristics in Figures 1 to 6 are obtained using 80 $\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

---

### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Avalanche capability




Figure 13: Power De-rating (Note A)