

 POSEICO POSEICO SPA POwer SEmiconductors Italian COrporation	POSEICO SPA Via N. Lorenzi 8, 16152 Genova - ITALY Tel. ++ 39 010 6556234 - Fax ++ 39 010 6557519 Sales Office: Tel. ++ 39 010 6556775 - Fax ++ 39 010 6442510
--	---

RECTIFIER DIODE

AR3008

Repetitive voltage up to **3000 V**
 Mean forward current **2700 A**
 Surge current **30.2 kA**

FINAL SPECIFICATION

Iug 02 - ISSUE : 06

Symbol	Characteristic	Conditions	T _J [°C]	Value	Unit
BLOCKING					
V _{RRM}	Repetitive peak reverse voltage		175	3000	V
V _{RSM}	Non-repetitive peak reverse voltage		175	3100	V
I _{RRM}	Repetitive peak reverse current	V=VRRM	175	75	mA
CONDUCTING					
I _{F (AV)}	Mean forward current	180° sin ,50 Hz, Th=55°C, double side cooled		2700	A
I _{F (AV)}	Mean forward current	180° sin ,50 Hz, Tc=85°C, double side cooled		2650	A
I _{FSM}	Surge forward current	Sine wave, 10 ms without reverse voltage	175	30.2	kA
I ² t	I ² t			4560 x 1E3	A²s
V _{FM}	Forward voltage	Forward current = 2900 A	25	1.30	V
V _{F(TO)}	Threshold voltage		175	0.87	V
r _F	Forward slope resistance		175	0.127	mohm
SWITCHING					
t _{rr}	Reverse recovery time		175		µs
Q _{rr}	Reverse recovery charge				µC
I _{rr}	Peak reverse recovery current				A
MOUNTING					
R _{th(j-h)}	Thermal impedance, DC	Junction to heatsink, double side cooled		26	°C/kW
R _{th(c-h)}	Thermal impedance	Case to heatsink, double side cooled		6	°C/kW
T _j	Operating junction temperature			-30 / 175	°C
F	Mounting force			18.0 / 20.0	kN
	Mass			500	g

找PDF ORDERING INFORMATION : AR3008 S 30

standard specification ☐ ☒ VRRM/100



AR3008 RECTIFIER DIODE




FINAL SPECIFICATION lug 02 - ISSUE : 06


DISSIPATION CHARACTERISTICS

SQUARE WAVE

Th [°C]



PF(AV) [W]



AR3008 RECTIFIER DIODE




FINAL SPECIFICATION lug 02 - ISSUE : 06


DISSIPATION CHARACTERISTICS

SINE WAVE

T_h [°C]



$P_F(AV)$ [W]




AR3008 RECTIFIER DIODE




FINAL SPECIFICATION lug 02 - ISSUE : 06



FORWARD CHARACTERISTIC
 $T_j = 175^\circ\text{C}$



SURGE CHARACTERISTIC
 $T_j = 175^\circ\text{C}$



TRANSIENT THERMAL IMPEDANCE
DOUBLE SIDE COOLED



Dimensions
in mm



All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness $< .03 \text{ mm}$ and roughness $< 2 \mu\text{m}$.

In the interest of product improvement POSEICO SPA reserves the right to change any data given in this data sheet at any time without previous notice.

If not stated otherwise the maximum value of ratings (symbols over shaded background) and characteristics is reported.

Distributed by

