SI GE

Features

- Versatile GHz Frequency Range Down Converter
- Low Power Building Block
- Triple Balanced Mixer with High LO Rejection

Benefits

- Low Current Consumption
- Single Supply
- Wide Supply Voltage Range of 2.7 V to 4.6 V
- Easy to Use and Handle
- Fully Integrated 5.8 GHz RF Port Matching
- Integrated Coupling Capacitors at RF- and LO-ports
- Open Collector IF Output Port
- Wide Useful Frequency Ranges
- RF: 2 GHz to 7 GHz
- LO: 1 GHz to 4 GHz
- IF: 0 GHz to 3 GHz

Electrostatic sensitive device. Observe precautions for handling.




Description

The down converter IC ATR2809 is fabricated in Atmel's powerful SiGe bipolar process.

The single ended RF input signal is differentially converted and down (or up) converted by a triple balanced Gilbert-cell mixer.

Figure 1. Block Diagram





5.8-GHz Down Converter IC

ATR2809

Summary

Preliminary



Rev. 4692CS-DECT-06/04

Note: This is a summary document. A complete document is available under NDA. For more information, please contact your local Atmel sales office.



Ordering Information

Extended Type Number	Package	Remarks
ATR2809	QFN16	4 x 4 mm, exposed pad, taped and reeled

Package Information

Package: QFN 16 - 4x4 Exposed pad 2.1x2.1

(acc. JEDEC OUTLINE No. MO-220)

Dimensions in mm

Drawing-No.: 6.543-5090.01-4

Issue 2, 24.01.03

2



Atmel Corporation

2325 Orchard Parkway San Jose, CA 95131, USA Tel: 1(408) 441-0311 Fax: 1(408) 487-2600

Regional Headquarters

Europe

Atmel Sarl Route des Arsenaux 41 Case Postale 80 CH-1705 Fribourg Switzerland

Tel: (41) 26-426-5555 Fax: (41) 26-426-5500

Asia

Room 1219 Chinachem Golden Plaza 77 Mody Road Tsimshatsui East Kowloon Hong Kong Tel: (852) 2721-9778

Tel: (852) 2721-9778 Fax: (852) 2722-1369

Japan

9F, Tonetsu Shinkawa Bldg. 1-24-8 Shinkawa Chuo-ku, Tokyo 104-0033 Japan

Tel: (81) 3-3523-3551 Fax: (81) 3-3523-7581

Atmel Operations

Memory

2325 Orchard Parkway San Jose, CA 95131, USA Tel: 1(408) 441-0311 Fax: 1(408) 436-4314

Microcontrollers

2325 Orchard Parkway San Jose, CA 95131, USA Tel: 1(408) 441-0311 Fax: 1(408) 436-4314

La Chantrerie BP 70602

44306 Nantes Cedex 3, France

Tel: (33) 2-40-18-18-18 Fax: (33) 2-40-18-19-60

ASIC/ASSP/Smart Cards

Zone Industrielle 13106 Rousset Cedex, France Tel: (33) 4-42-53-60-00 Fax: (33) 4-42-53-60-01

1150 East Cheyenne Mtn. Blvd. Colorado Springs, CO 80906, USA

Tel: 1(719) 576-3300 Fax: 1(719) 540-1759

Scottish Enterprise Technology Park Maxwell Building

East Kilbride G75 0QR, Scotland

Tel: (44) 1355-803-000 Fax: (44) 1355-242-743

RF/Automotive

Theresienstrasse 2 Postfach 3535 74025 Heilbronn, Germany Tel: (49) 71-31-67-0 Fax: (49) 71-31-67-2340

1150 East Cheyenne Mtn. Blvd. Colorado Springs, CO 80906, USA

Tel: 1(719) 576-3300 Fax: 1(719) 540-1759

Biometrics/Imaging/Hi-Rel MPU/ High Speed Converters/RF Datacom

Avenue de Rochepleine

BP 123

38521 Saint-Egreve Cedex, France

Tel: (33) 4-76-58-30-00 Fax: (33) 4-76-58-34-80

Literature Requests www.atmel.com/literature

Disclaimer: Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

© Atmel Corporation 2004. All rights reserved.

Atmel® and combinations thereof are the registered trademarks of Atmel Corporation or its subsidiaries.

Other terms and product names may be the trademarks of others.

