查询BCR12PM供应商 捷多邦，专业PCB打样工厂，24小时加急出货

MITSUBISHI SEMICONDUCTOR 〈TRIAC〉

BCR12PM

MEDIUM POWER USE

INSULATED TYPE, PLANAR PASSIVATION TYPE

BCR12PM



- $I_{T\,(RMS)}$ 12A
- V_{DRM} 400V/600V
- $I_{FGT\,I}$, $I_{RGT\,I}$, $I_{RGT\,III}$ 30mA (20mA) *5
- V_{iso} 1500V
- UL Recognized: File No. E80276

OUTLINE DRAWING

Dimensions in mm



APPLICATION

Switching mode power supply, light dimmer, electric flasher unit, hair driver, control of household equipment such as TV sets · stereo · refrigerator · washing machine · infrared kotatsu · carpet, solenoid drivers, small motor control, copying machine, electric tool

MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		8	12	
V_{DRM}	Repetitive peak off-state voltage *1	400	600	V
V_{DSM}	Non-repetitive peak off-state voltage *1	500	720	V

Symbol	Parameter	Conditions	Ratings	Unit
$I_{T\,(RMS)}$	RMS on-state current	Commercial frequency, sine full wave 360° conduction, T_c=74°C	12	A
I_{TSM}	Surge on-state current	60Hz sinewave 1 full cycle, peak value, non-repetitive	120	A
I^2t	I^2t for fusing	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current	60	A^2s
P_{GM}	Peak gate power dissipation		5	W
$P_{G\,(AV)}$	Average gate power dissipation		0.5	W
V_{GM}	Peak gate voltage		10	V
I_{GM}	Peak gate current		2	A
T_j	Junction temperature		–40 ~ +125	°C
T_{stg}	Storage temperature		–40 ~ +125	°C
—	Weight	Typical value	2.0	g
V_{iso}	Isolation voltage	T_a=25°C, AC 1 minute, T_1 · T_2 · G terminal to case	1500	V

*1: Gate open.

找PDF 维库一下 pdf.dzsc.com

BCR12PM

MEDIUM POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE

ELECTRICAL CHARACTERISTICS

Symbol	Parameter		Test conditions	Limits Min.	Limits Typ.	Limits Max.	Unit
I_{DRM}	Repetitive peak off-state current		T_j=125°C, V_{DRM} applied	—	—	2.0	mA
V_{TM}	On-state voltage		T_C=25°C, I_{TM}=20A, Instantaneous measurement	—	—	1.6	V
$V_{FGT\ I}$	Gate trigger voltage *2	I	T_j=25°C, V_D=6V, R_L=6Ω, R_G=330Ω	—	—	1.5	V
$V_{RGT\ I}$		II		—	—	1.5	V
$V_{RGT\ III}$		III		—	—	1.5	V
$I_{FGT\ I}$	Gate trigger current *2	I	T_j=25°C, V_D=6V, R_L=6Ω, R_G=330Ω	—	—	30*5	mA
$I_{RGT\ I}$		II		—	—	30*5	mA
$I_{RGT\ III}$		III		—	—	30*5	mA
V_{GD}	Gate non-trigger voltage		T_j=125°C, V_D=1/2V_{DRM}	0.2	—	—	V
$R_{th\ (j-c)}$	Thermal resistance		Junction to case *4	—	—	3.5	°C/W
$(dv/dt)_c$	Critical-rate of rise of off-state commutating voltage			*3	—	—	V/µs

*2. Measurement using the gate trigger characteristics measurement circuit.
*3. The critical-rate of rise of the off-state commutating voltage is shown in the table below.
*4. The contact thermal resistance $R_{th\ (c-f)}$ in case of greasing is 0.5°C/W.
*5. High sensitivity (I_{GT}≤20mA) is also available. (I_{GT} item ①)

Voltage class	V_{DRM} (V)	$(dv/dt)_c$ Symbol	Min.	Unit	Test conditions	Commutating voltage and current waveforms (inductive load)
8	400	R	—	V/µs	1. Junction temperature T_j=125°C 2. Rate of decay of on-state commutating current $(di/dt)_c$=–6.0A/ms 3. Peak off-state voltage V_D=400V	
		L	10			
12	600	R	—			
		L	10			

PERFORMANCE CURVES

MAXIMUM ON-STATE CHARACTERISTICS



RATED SURGE ON-STATE CURRENT



MITSUBISHI ELECTRIC

BCR12PM

MEDIUM POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE

GATE CHARACTERISTICS



GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE



GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE



MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION TO CASE)



MAXIMUM TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (JUNCTION TO AMBIENT)



MAXIMUM ON-STATE POWER DISSIPATION



MITSUBISHI ELECTRIC

ALLOWABLE CASE TEMPERATURE VS. RMS ON-STATE CURRENT



ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT



ALLOWABLE AMBIENT TEMPERATURE VS. RMS ON-STATE CURRENT



REPETITIVE PEAK OFF-STATE CURRENT VS. JUNCTION TEMPERATURE



HOLDING CURRENT VS. JUNCTION TEMPERATURE



LACHING CURRENT VS. JUNCTION TEMPERATURE



BCR12PM

MEDIUM POWER USE
INSULATED TYPE, PLANAR PASSIVATION TYPE

BREAKOVER VOLTAGE VS. JUNCTION TEMPERATURE



BREAKOVER VOLTAGE VS. RATE OF RISE OF OFF-STATE VOLTAGE



COMMUTATION CHARACTERISTICS



GATE TRIGGER CURRENT VS. GATE CURRENT PULSE WIDTH



GATE TRIGGER CHARACTERISTICS TEST CIRCUITS



MITSUBISHI ELECTRIC