

[查询BFS25供应商](#)

[捷多邦，专业PCB打样工厂，24小时加急出货](#)

DISCRETE SEMICONDUCTORS

DATA SHEET

BFS25A NPN 5 GHz wideband transistor

Product specification

December 1997

File under Discrete Semiconductors, SC14

NPN 5 GHz wideband transistor**BFS25A****FEATURES**

- Low current consumption
- Low noise figure
- Gold metallization ensures excellent reliability
- SOT323 envelope.

PINNING

PIN	DESCRIPTION
Code: N6	
1	base
2	emitter
3	collector

DESCRIPTION

NPN transistor in a plastic SOT323 envelope.

It is designed for use in RF amplifiers and oscillators in pagers and pocket phones with signal frequencies up to 2 GHz.




Fig.1 SOT323.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{CBO}	collector-base voltage	open emitter	–	–	8	V
V_{CEO}	collector-emitter voltage	open base	–	–	5	V
I_C	DC collector current		–	–	6.5	mA
P_{tot}	total power dissipation	up to $T_s = 170^\circ\text{C}$; note 1	–	–	32	mW
h_{FE}	DC current gain	$I_C = 0.5 \text{ mA}; V_{CE} = 1 \text{ V}; T_j = 25^\circ\text{C}$	50	80	200	
f_T	transition frequency	$I_C = 1 \text{ mA}; V_{CE} = 1 \text{ V}; f = 1 \text{ GHz}; T_{amb} = 25^\circ\text{C}$	3.5	5	–	GHz
G_{UM}	maximum unilateral power gain	$I_C = 0.5 \text{ mA}; V_{CE} = 1 \text{ V}; f = 1 \text{ GHz}; T_{amb} = 25^\circ\text{C}$	–	13	–	dB
F	noise figure	$I_C = 0.5 \text{ mA}; V_{CE} = 1 \text{ V}; f = 1 \text{ GHz}; T_{amb} = 25^\circ\text{C}$	–	1.8	–	dB

LIMITING VALUES

In accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CBO}	collector-base voltage	open emitter	–	8	V
V_{CEO}	collector-emitter voltage	open base	–	5	V
V_{EBO}	emitter-base voltage	open collector	–	2	V
I_C	DC collector current		–	6.5	mA
P_{tot}	total power dissipation	up to $T_s = 170^\circ\text{C}$; note 1	–	32	mW
T_{stg}	storage temperature		-65	150	°C
T_j	junction temperature		–	175	°C

Note

1. T_s is the temperature at the soldering point of the collector tab.

NPN 5 GHz wideband transistor

BFS25A

THERMAL RESISTANCE

SYMBOL	PARAMETER	CONDITIONS	THERMAL RESISTANCE
$R_{th\ j-s}$	thermal resistance from junction to soldering point	up to $T_s = 170^\circ\text{C}$; note 1	190 K/W

Note

1. T_s is the temperature at the soldering point of the collector tab.

CHARACTERISTICS

$T_j = 25^\circ\text{C}$, unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{CBO}	collector cut-off current	$I_E = 0$; $V_{CB} = 5\text{ V}$	–	–	50	nA
h_{FE}	DC current gain	$I_C = 0.5\text{ mA}$; $V_{CE} = 1\text{ V}$	50	80	200	
C_{re}	feedback capacitance	$I_C = 0$; $V_{CB} = 1\text{ V}$; $f = 1\text{ MHz}$	–	0.3	0.45	pF
f_T	transition frequency	$I_C = 1\text{ mA}$; $V_{CE} = 1\text{ V}$; $f = 1\text{ GHz}$; $T_{amb} = 25^\circ\text{C}$	3.5	5	–	GHz
G_{UM}	maximum unilateral power gain (note 1)	$I_C = 0.5\text{ mA}$; $V_{CE} = 1\text{ V}$; $f = 1\text{ GHz}$; $T_{amb} = 25^\circ\text{C}$	–	13	–	dB
F	noise figure	$\Gamma_s = \Gamma_{opt}$; $I_C = 0.5\text{ mA}$; $V_{CE} = 1\text{ V}$; $f = 1\text{ GHz}$; $T_{amb} = 25^\circ\text{C}$	–	1.8	–	dB
		$\Gamma_s = \Gamma_{opt}$; $I_C = 1\text{ mA}$; $V_{CE} = 1\text{ V}$; $f = 1\text{ GHz}$; $T_{amb} = 25^\circ\text{C}$	–	2	–	dB

Note

1. G_{UM} is the maximum unilateral power gain, assuming S_{12} is zero and

$$G_{UM} = 10 \log \left(\frac{|S_{21}|^2}{(1 - |S_{11}|^2)(1 - |S_{22}|^2)} \right) \text{ dB.}$$

NPN 5 GHz wideband transistor

BFS25A




Fig.2 Power derating curve.


 $V_{CE} = 1$ V; $T_j = 25$ °C.

Fig.3 DC current gain as a function of collector current.


 $I_C = 0$; $f = 1$ MHz.

Fig.4 Feedback capacitance as a function of collector-base voltage.



 $f = 1$ GHz; $T_{amb} = 25$ °C.

Fig.5 Transition frequency as a function of collector current.

NPN 5 GHz wideband transistor


BFS25A

In Figs 6 to 9, G_{UM} = maximum unilateral power gain; MSG = maximum stable gain; G_{max} = maximum available gain.




$V_{CE} = 1$ V; $f = 500$ MHz; $T_{amb} = 25$ °C.

Fig.6 Gain as a function of collector current.




$f = 1$ GHz; $T_{amb} = 25$ °C.

Fig.7 Maximum unilateral power gain as a function of collector current.



$I_C = 0.5$ mA; $V_{CE} = 1$ V; $T_{amb} = 25$ °C.

Fig.8 Gain as a function of frequency.



$I_C = 1$ mA; $V_{CE} = 1$ V; $T_{amb} = 25$ °C.

Fig.9 Gain as a function of frequency.

NPN 5 GHz wideband transistor

BFS25A


 $V_{CE} = 1 \text{ V}; T_{amb} = 25^\circ\text{C}$.

Fig.10 Minimum noise figure as a function of collector current.


 $V_{CE} = 1 \text{ V}; T_{amb} = 25^\circ\text{C}$.

Fig.11 Minimum noise figure as a function of frequency.





Fig.12 Noise circle.


NPN 5 GHz wideband transistor

BFS25A



$I_C = 1 \text{ mA}; V_{CE} = 1 \text{ V};$
 $f = 1 \text{ GHz}; Z_0 = 50 \Omega.$

Fig.13 Noise circle.




$I_C = 1 \text{ mA}; V_{CE} = 1 \text{ V};$
 $f = 2 \text{ GHz}; Z_0 = 50 \Omega.$

Fig.14 Noise circle.


NPN 5 GHz wideband transistor

BFS25A



$I_C = 1 \text{ mA}$; $V_{CE} = 1 \text{ V}$;
 $Z_0 = 50 \Omega$.

Fig.15 Common emitter input reflection coefficient (S_{11}).





$I_C = 1 \text{ mA}$; $V_{CE} = 1 \text{ V}$.

Fig.16 Common emitter forward transmission coefficient (S_{21}).

NPN 5 GHz wideband transistor

BFS25A

 $I_C = 1 \text{ mA}; V_{CE} = 1 \text{ V}.$ Fig.17 Common emitter reverse transmission coefficient (S_{12}). $I_C = 1 \text{ mA}; V_{CE} = 1 \text{ V};$
 $Z_0 = 50 \Omega.$ Fig.18 Common emitter output reflection coefficient (S_{22}).


NPN 5 GHz wideband transistor

BFS25A

PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT323



DIMENSIONS (mm are the original dimensions)

UNIT	A	A ₁ max	b _p	c	D	E	e	e ₁	H _E	L _p	Q	v	w
mm	1.1 0.8	0.1	0.4 0.3	0.25 0.10	2.2 1.8	1.35 1.15	1.3	0.65	2.2 2.0	0.45 0.15	0.23 0.13	0.2	0.2

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ	SC-70		
SOT323						97-02-28

NPN 5 GHz wideband transistor**BFS25A****DEFINITIONS**

Data Sheet Status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.