

Triacs sensitive gate

BT136X series E

GENERAL DESCRIPTION

Glass passivated, sensitive gate triacs in a full pack plastic envelope, intended for use in general purpose bidirectional switching and phase control applications, where high sensitivity is required in all four quadrants.


QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	MAX.	MAX.	UNIT
V_{DRM}	BT136X- Repetitive peak off-state voltages	500E 500	600E 600	800E 800	V
$I_{T(RMS)}$ I_{TSM}	RMS on-state current Non-repetitive peak on-state current	4 25	4 25	4 25	A A


PINNING - SOT186A

PIN	DESCRIPTION
1	main terminal 1
2	main terminal 2
3	gate
case	isolated

PIN CONFIGURATION



SYMBOL



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.			UNIT
				-500 500 ¹	-600 600 ¹	-800 800	
V_{DRM}	Repetitive peak off-state voltages		-				V
$I_{T(RMS)}$ I_{TSM}	RMS on-state current Non-repetitive peak on-state current	full sine wave; $T_{hs} \leq 92^\circ\text{C}$ full sine wave; $T_j = 25^\circ\text{C}$ prior to surge $t = 20\text{ ms}$ $t = 16.7\text{ ms}$ $t = 10\text{ ms}$ $I_{TM} = 6\text{ A}; I_G = 0.2\text{ A};$ $dI_G/dt = 0.2\text{ A}/\mu\text{s}$	-	4			A
I^2t dI_t/dt	I^2t for fusing Repetitive rate of rise of on-state current after triggering		-	25	27	3.1	A^2s
I_{GM} V_{GM} P_{GM} $P_{G(AV)}$ T_{stg} T_j	Peak gate current Peak gate voltage Peak gate power Average gate power Storage temperature Operating junction temperature	over any 20 ms period	T2+ G+ T2+ G- T2- G- T2- G+	-	50	50	$\text{A}/\mu\text{s}$
			-	50	50	50	$\text{A}/\mu\text{s}$
			-	2	5	5	A
			-	5	5	0.5	V
			-40	150	150	125	W
			-	150	150	125	$^\circ\text{C}$

¹ Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 3 A/ μs .

Triacs sensitive gate

BT136X series E

ISOLATION LIMITING VALUE & CHARACTERISTIC

$T_{hs} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{isol}	R.M.S. isolation voltage from all three terminals to external heatsink	$f = 50-60 \text{ Hz}$; sinusoidal waveform; $\text{R.H.} \leq 65\%$; clean and dustfree	-		2500	V
C_{isol}	Capacitance from T2 to external heatsink	$f = 1 \text{ MHz}$	-	10	-	pF

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th j-hs}$	Thermal resistance junction to heatsink	full or half cycle with heatsink compound	-	-	5.5	K/W
$R_{th j-a}$	Thermal resistance junction to ambient	without heatsink compound in free air	-	55	7.2	K/W

STATIC CHARACTERISTICS

$T_j = 25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{GT}	Gate trigger current	$V_D = 12 \text{ V}$; $I_T = 0.1 \text{ A}$				
		T2+ G+	-	2.5	10	mA
		T2+ G-	-	4.0	10	mA
		T2- G-	-	5.0	10	mA
		T2- G+	-	11	25	mA
I_L	Latching current	$V_D = 12 \text{ V}$; $I_{GT} = 0.1 \text{ A}$				
		T2+ G+	-	3.0	15	mA
		T2+ G-	-	10	20	mA
		T2- G-	-	2.5	15	mA
		T2- G+	-	4.0	20	mA
I_H	Holding current	$V_D = 12 \text{ V}$; $I_{GT} = 0.1 \text{ A}$				
V_T	On-state voltage	$I_T = 5 \text{ A}$				
V_{GT}	Gate trigger voltage	$V_D = 12 \text{ V}$; $I_T = 0.1 \text{ A}$				
I_D	Off-state leakage current	$V_D = 400 \text{ V}$; $I_T = 0.1 \text{ A}$; $T_j = 125^\circ\text{C}$ $V_D = V_{DRM(max)}$; $T_j = 125^\circ\text{C}$	0.25	0.4	-	V
			-	0.1	0.5	mA

DYNAMIC CHARACTERISTICS

$T_j = 25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
dV_D/dt	Critical rate of rise of off-state voltage	$V_{DM} = 67\% V_{DRM(max)}$; $T_j = 125^\circ\text{C}$; exponential waveform; gate open circuit	-	50	-	V/ μ s
t_{gt}	Gate controlled turn-on time	$I_{TM} = 6 \text{ A}$; $V_D = V_{DRM(max)}$; $I_G = 0.1 \text{ A}$; $dI_G/dt = 5 \text{ A}/\mu\text{s}$	-	2	-	μ s

Triacs sensitive gate

BT136X series E




Fig.1. Maximum on-state dissipation, P_{tot} , versus rms on-state current, $IT_{(RMS)}$, where α = conduction angle.




Fig.4. Maximum permissible rms current $IT_{(RMS)}$, versus heatsink temperature Ths .




Fig.2. Maximum permissible non-repetitive peak on-state current IT_{SM} , versus pulse width t_p , for sinusoidal currents, $t_p \leq 20ms$.




Fig.5. Maximum permissible repetitive rms on-state current $IT_{(RMS)}$, versus surge duration, for sinusoidal currents, $f = 50$ Hz; $Ths \leq 92^\circ C$.




Fig.3. Maximum permissible non-repetitive peak on-state current IT_{SM} , versus number of cycles, for sinusoidal currents, $f = 50$ Hz.




Fig.6. Normalised gate trigger voltage $V_{GT}(T_j)/V_{GT}(25^\circ C)$, versus junction temperature T_j .

Triacs sensitive gate

BT136X series E




Fig.7. Normalised gate trigger current $I_{GT}(T_j)/I_{GT}(25^\circ C)$, versus junction temperature T_j .




Fig.10. Typical and maximum on-state characteristic.




Fig.8. Normalised latching current $I_L(T_j)/I_L(25^\circ C)$, versus junction temperature T_j .




Fig.11. Transient thermal impedance $Z_{th\ j-hs}$, versus pulse width t_p .




Fig.9. Normalised holding current $I_H(T_j)/I_H(25^\circ C)$, versus junction temperature T_j .




Fig.12. Typical, critical rate of rise of off-state voltage, dV_D/dt versus junction temperature T_j .

Triacs sensitive gate

BT136X series E

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g




Fig.13. SOT186A; The seating plane is electrically isolated from all terminals.

Notes

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

**Triacs
sensitive gate**

BT136X series E**DEFINITIONS**

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© Philips Electronics N.V. 1997	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.