

BU-00000-* Part # color * 0 - Black 5 - Green 2 - Red 6 - Blue 4 - Yellow 9 - White



1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 Page 1



Enlarge

BU-34 Steel Micro-Alligator 5 Amp BU-34C Solid Copper Micro-Alligator 5 Amp

- Smooth jawed clip has a microscopic tip
- Nose width is 0.0625" (1.6mm)
- Solder or crimp connection
- 7/32" (5.6mm) max. jaw opening
- Product Data Sheet
- Send us your questions about this product

BU-36 Insulator for BU-34/34C

- Skin–tight flexible vinyl
- Available in black, red, yelllow, green, blue and white
- Product Data Sheet
- Send us your questions about this product



Enlarge



Enlarge

BU-30 Steel Miniature-Alligator 5 Amp BU-30C Solid Copper Miniature-Alligator 5 Amp

- Full meshing teeth
- Jaw opens 3/16" (4.8mm) max.
- Solder or crimp connection
- 7/32" (5.6mm) jaw opening
- Federal spec.: Type TCM-1-W-C-440B(BU-30C)
- Product Data Sheet
- Send us your questions about this product

BU-32 Insulator for BU-30/30C

- Skin-tight flexible vinyl
- Available in black, red, yelllow, green, blue and white
- Product Data Sheet
- Send us your questions about this product



Enlarge

<u>Contents | Next</u> <u>Home | Insulated BNCs | Test Leads | Insulated Test Accessories | Accessories & Probes | Kits | Cross Reference | Contents | Cross Reference | Cross</u>

© 2000 Mueller Electric Company. All rights reserved. Problems with the site should be reported to the <u>webmaster</u>. This site created by <u>WebEcentric</u>.