

FEATURES

- **2.5-V, 2.7-V, and 5-V Performance**
- **-40°C to 125°C Operation**
- **No Crossover Distortion**
- **Low Supply Current at $V_{CC+} = 5$ V:**
 - LMV821...0.3 mA Typ
 - LMV822...0.5 mA Typ
 - LMV824...1 mA Typ
- **Rail-to-Rail Output Swing**
- **Gain Bandwidth of 5.5 MHz Typ at 5 V**
- **Slew Rate of 1.9 V/ μ s Typ at 5 V**


DESCRIPTION/ORDERING INFORMATION

The LMV821 single, LMV822 dual, and LMV824 quad devices are low-voltage (2.5 V to 5.5 V), low-power commodity operational amplifiers. Electrical characteristics are very similar to the LMV3xx operational amplifiers (low supply current, rail-to-rail outputs, input common-mode range that includes ground). However, the LMV8xx devices offer a higher bandwidth (5.5 MHz typical) and faster slew rate (1.9 V/ μ s typical).


The LMV8xx devices are cost-effective solutions for applications requiring low-voltage/low-power operation and space-saving considerations. The LMV821 is available in the ultra-small DCK package, which is approximately half the size of SOT-23-5. The DCK package saves space on printed circuit boards and enables the design of small portable electronic devices (cordless and cellular phones, laptops, PDAs, PCMIA). It also allows the designer to place the device closer to the signal source to reduce noise pickup and increase signal integrity.

The LMV8xx devices are characterized for operation from -40°C to 85°C. The LMV8xxI devices are characterized for operation from -40°C to 125°C.


**LMV824... D, DGV, OR PW PACKAGE
(TOP VIEW)**



**LMV822... D OR DGK PACKAGE
(TOP VIEW)**



**LMV821... DBV OR DCK PACKAGE
(TOP VIEW)**



LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005




ORDERING INFORMATION

T _A	PACKAGE ⁽¹⁾		ORDERABLE PART NUMBER	TOP-SIDE MARKING ⁽²⁾
−40°C to 85°C	Single	SC-70 – DCK	Reel of 3000	LMV821DCKR
			Reel of 250	LMV821DCKT
	Dual	SOT-23 – DBV	Reel of 3000	LMV821DBVR
			Reel of 250	LMV821DBVT
	Quad	SOIC – D	Tube of 75	LMV822D
			Reel of 2500	LMV822DR
		MSOP/VSSOP – DGK	Tube of 100	LMV822DGK
			Reel of 2500	LMV822DGKR
	−40°C to 125°C	SOIC – D	Tube of 50	LMV824D
			Reel of 2500	LMV824DR
		TSSOP – PW	Tube of 90	LMV824PW
			Reel of 2000	LMV824PWR
		TVSOP – DGV	Reel of 2000	LMV824DGVR
				MV824


(1) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.

(2) DBV/DCK/DGK: The actual top-side marking has one additional character that designates the assembly/test site.

SYMBOL (EACH AMPLIFIER)



LMV824 SIMPLIFIED SCHEMATIC



LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



Absolute Maximum Ratings⁽¹⁾

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V _{CC}	Supply voltage ⁽²⁾		5.5	V
V _{ID}	Differential input voltage ⁽³⁾		±V _{CC}	V
V _I	Input voltage range (either input)	V _{CC} –	V _{CC} +	V
	Duration of output short circuit (one amplifier) to ground ⁽⁴⁾	At or below T _A = 25°C, V _{CC} ≤ 5.5 V	Unlimited	
θ _{JA}	Package thermal impedance ⁽⁵⁾⁽⁶⁾	D package	8 pin	97
			14 pin	86
		DBV package		206
		DCK package		252
		DGK package		172
		DGV package		127
		PW package		113
T _J	Operating virtual junction temperature		150	°C
T _{stg}	Storage temperature range	−65	150	°C

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values (except differential voltages and V_{CC} specified for the measurement of I_{OS}) are with respect to the network GND.
- (3) Differential voltages are at IN+ with respect to IN−.
- (4) Short circuits from outputs to V_{CC} can cause excessive heating and eventual destruction.
- (5) Maximum power dissipation is a function of T_{J(max)}, θ_{JA}, and T_A. The maximum allowable power dissipation at any allowable ambient temperature is P_D = (T_{J(max)} − T_A)/θ_{JA}. Operating at the absolute maximum T_J of 150°C can affect reliability.
- (6) The package thermal impedance is calculated in accordance with JESD 51-7.

Recommended Operating Conditions

		MIN	MAX	UNIT
V _{CC}	Supply voltage (single-supply operation)	2.5	5	V
T _A	Operating free-air temperature	LMV8xxI	−40	125
		LMV8xx	−40	85

LMV8xx 2.5-V Electrical Characteristics
 $V_{CC+} = 2.5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 1 \text{ V}$, $V_O = 1.25 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xx			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage	$V_{CC+} = 2.5 \text{ V}$, $R_L = 600 \Omega$ to 1.25 V	25°C		1	3.5	mV
		−40°C to 85°C			4	
V_O Output swing	$V_{CC+} = 2.5 \text{ V}$, $R_L = 600 \Omega$ to 1.25 V	High level	25°C	2.3	2.37	V
			−40°C to 85°C	2.2		
		Low level	25°C	0.13	0.2	
			−40°C to 85°C	0.3		
	$V_{CC+} = 2.5 \text{ V}$, $R_L = 2 \text{ k}\Omega$ to 1.25 V	High level	25°C	2.4	2.46	
			−40°C to 85°C	2.3		
		Low level	25°C	0.08	0.12	
			−40°C to 85°C	0.2		

LMV8xxI 2.5-V Electrical Characteristics
 $V_{CC+} = 2.5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 1 \text{ V}$, $V_O = 1.25 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xxI			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage	$V_{CC+} = 2.5 \text{ V}$, $R_L = 600 \Omega$ to 1.25 V	25°C		1	3.5	mV
		−40°C to 125°C			5.5	
V_O Output swing	$V_{CC+} = 2.5 \text{ V}$, $R_L = 600 \Omega$ to 1.25 V	High level	25°C	2.28	2.37	V
			−40°C to 125°C	2.18		
		Low level	25°C	0.13	0.22	
			−40°C to 125°C	0.32		
	$V_{CC+} = 2.5 \text{ V}$, $R_L = 2 \text{ k}\Omega$ to 1.25 V	High level	25°C	2.38	2.46	
			−40°C to 125°C	2.28		
		Low level	25°C	0.08	0.14	
			−40°C to 125°C	0.22		

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



LMV8xx 2.7-V Electrical Characteristics

$V_{CC+} = 2.7\text{ V}$, $V_{CC-} = 0\text{ V}$, $V_{IC} = 1\text{ V}$, $V_O = 1.35\text{ V}$, and $R_L > 1\text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xx			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage		25°C	1	3.5	mV	
		-40°C to 85°C		4		
α_{VIO} Average temperature coefficient of input offset voltage		25°C	1		μV/°C	
I_{IB} Input bias current		25°C	30	90	nA	
		-40°C to 85°C		140		
I_{IO} Input offset current		25°C	0.5	30	nA	
		-40°C to 85°C		50		
CMRR Common-mode rejection ratio	$V_{IC} = 0\text{ to }1.7\text{ V}$	25°C	70	85	dB	
		-40°C to 85°C	68			
$+k_{SVR}$ Positive supply-voltage rejection ratio	$V_{CC+} = 1.7\text{ V to }4\text{ V}$, $V_{CC-} = -1\text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	75	85	dB	
		-40°C to 85°C	70			
$-k_{SVR}$ Negative supply-voltage rejection ratio	$V_{CC+} = 1.7\text{ V}$, $V_{CC-} = -1\text{ V to }-3.3\text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	73	85	dB	
		-40°C to 85°C	70			
V_{ICR} Common-mode input voltage range	CMRR ≥ 50 dB	25°C	-0.2 to 1.9	-0.3 to 2	V	
A_V Large-signal voltage amplification	$R_L = 600\text{ }\Omega$ to 1.35 V, $V_O = 1.35\text{ V to }2.2\text{ V}$	Sourcing	25°C	90	100	dB
			-40°C to 85°C	85		
	$R_L = 600\text{ }\Omega$ to 1.35 V, $V_O = 1.35\text{ V to }0.5\text{ V}$	Sinking	25°C	85	90	
			-40°C to 85°C	80		
	$R_L = 2\text{ k}\Omega$ to 1.35 V, $V_O = 1.35\text{ V to }2.2\text{ V}$	Sourcing	25°C	95	100	
			-40°C to 85°C	90		
	$R_L = 2\text{ k}\Omega$ to 1.35 V, $V_O = 1.35\text{ V to }0.5\text{ V}$	Sinking	25°C	90	95	
			-40°C to 85°C	85		
V_O Output swing	$V_{CC+} = 2.7\text{ V}$, $R_L = 600\text{ }\Omega$ to 1.35 V	High level	25°C	2.5	2.58	V
			-40°C to 85°C	2.4		
		Low level	25°C		0.13 0.2	
			-40°C to 85°C		0.3	
	$V_{CC+} = 2.7\text{ V}$, $R_L = 2\text{ k}\Omega$ to 1.35 V	High level	25°C	2.6	2.66	
			-40°C to 85°C	2.5		
		Low level	25°C		0.08 0.12	
			-40°C to 85°C		0.2	
I_O Output current	$V_O = 0\text{ V}$	Sourcing	25°C	12	16	mA
	$V_O = 2.7\text{ V}$	Sinking	25°C	12	26	
I_{CC} Supply current	LMV821	25°C	0.22	0.3	mA	
		-40°C to 85°C		0.5		
	LMV822 (both amplifiers)	25°C	0.45	0.6		
		-40°C to 85°C		0.8		
	LMV824 (all four amplifiers)	25°C	0.72	1		
		-40°C to 85°C		1.2		

LMV8xx 2.7-V Electrical Characteristics (continued)

$V_{CC+} = 2.7\text{ V}$, $V_{CC-} = 0\text{ V}$, $V_{IC} = 1\text{ V}$, $V_O = 1.35\text{ V}$, and $R_L > 1\text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xx			UNIT
			MIN	TYP	MAX	
SR Slew rate ⁽¹⁾		25°C		1.7		V/ μs
GBW Gain bandwidth product	(2)	25°C		5		MHz
Φ_m Phase margin	(2)	25°C		60		deg
Gain margin	(2)	25°C		8.6		dB
Amplifier-to-amplifier isolation	$V_{CC+} = 5\text{ V}$, $R_L = 100\text{ k}\Omega$ to 2.5 V ⁽³⁾	25°C		135		dB
V_n Equivalent input noise voltage	$f = 1\text{ kHz}$, $V_{IC} = 1\text{ V}$	25°C		45		nV/ $\sqrt{\text{Hz}}$
I_n Equivalent input noise current	$f = 1\text{ kHz}$	25°C		0.18		pA/ $\sqrt{\text{Hz}}$
THD Total harmonic distortion	$f = 1\text{ kHz}$, $A_V = -2$, $R_L = 10\text{ k}\Omega$, $V_O = 4.1\text{ V}_{\text{p-p}}$	25°C		0.01		%

(1) Connected as voltage follower with 1-V step input. Value specified is the slower of the positive and negative slew rates.

(2) 40-dB closed-loop dc gain, $C_L = 22\text{ pF}$

(3) Each amplifier excited in turn with 1 kHz to produce $V_O = 3\text{ V}_{\text{p-p}}$

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



LMV8xxI 2.7-V Electrical Characteristics

$V_{CC+} = 2.7\text{ V}$, $V_{CC-} = 0\text{ V}$, $V_{IC} = 1\text{ V}$, $V_O = 1.35\text{ V}$, and $R_L > 1\text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xxI			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage		25°C	1	3.5	mV	
		–40°C to 125°C	5.5			
α_{VIO} Average temperature coefficient of input offset voltage		25°C	1		μV/°C	
I_{IB} Input bias current		25°C	30	90	nA	
		–40°C to 125°C	140			
I_{IO} Input offset current		25°C	0.5	30	nA	
		–40°C to 125°C	50			
CMRR Common-mode rejection ratio	$V_{IC} = 0$ to 1.7 V	25°C	70	85	dB	
		–40°C to 125°C	68			
$+k_{SVR}$ Positive supply-voltage rejection ratio	$V_{CC+} = 1.7\text{ V}$ to 4 V, $V_{CC-} = -1\text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	75	85	dB	
		–40°C to 125°C	70			
$-k_{SVR}$ Negative supply-voltage rejection ratio	$V_{CC+} = 1.7\text{ V}$, $V_{CC-} = -1\text{ V}$ to –3.3 V, $V_O = 0$, $V_{IC} = 0$	25°C	73	85	dB	
		–40°C to 125°C	70			
V_{ICR} Common-mode input voltage range	CMRR ≥ 50 dB	25°C	–0.2 to 1.9	–0.3 to 2	V	
A_V Large-signal voltage amplification	$R_L = 600\text{ }\Omega$ to 1.35 V, $V_O = 1.35\text{ V}$ to 2.2 V	Sourcing	25°C	90	100	dB
			–40°C to 125°C	85		
	$R_L = 600\text{ }\Omega$ to 1.35 V, $V_O = 1.35\text{ V}$ to 0.5 V	Sinking	25°C	85	90	
			–40°C to 125°C	80		
	$R_L = 2\text{ k}\Omega$ to 1.35 V, $V_O = 1.35\text{ V}$ to 2.2 V	Sourcing	25°C	95	100	
			–40°C to 125°C	90		
	$R_L = 2\text{ k}\Omega$ to 1.35 V, $V_O = 1.35\text{ V}$ to 0.5 V	Sinking	25°C	90	95	
			–40°C to 125°C	85		
V_O Output swing	$V_{CC+} = 2.7\text{ V}$, $R_L = 600\text{ }\Omega$ to 1.35 V	High level	25°C	2.5	2.58	V
			–40°C to 125°C	2.4		
		Low level	25°C	0.13	0.2	
			–40°C to 125°C	0.3		
	$V_{CC+} = 2.7\text{ V}$, $R_L = 2\text{ k}\Omega$ to 1.35 V	High level	25°C	2.6	2.66	
			–40°C to 125°C	2.5		
		Low level	25°C	0.08	0.12	
			–40°C to 125°C	0.2		
I_O Output current	$V_O = 0\text{ V}$	Sourcing	25°C	12	16	mA
	$V_O = 2.7\text{ V}$	Sinking	25°C	12	26	
I_{CC} Supply current	LMV821		25°C	0.22	0.3	mA
			–40°C to 125°C	0.5		
	LMV822 (both amplifiers)		25°C	0.45	0.6	
			–40°C to 125°C	0.8		
	LMV824 (all four amplifiers)		25°C	0.72	1	
			–40°C to 125°C	1.2		

LMV8xxI 2.7-V Electrical Characteristics (continued)

$V_{CC+} = 2.7$ V, $V_{CC-} = 0$ V, $V_{IC} = 1$ V, $V_O = 1.35$ V, and $R_L > 1$ M Ω (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xxI			UNIT
			MIN	TYP	MAX	
SR Slew rate ⁽¹⁾		25°C		1.7		V/ μ s
GBW Gain bandwidth product	(2)	25°C		5		MHz
Φ_m Phase margin	(2)	25°C		60		deg
Gain margin	(2)	25°C		8.6		dB
Amplifier-to-amplifier isolation	$V_{CC+} = 5$ V, $R_L = 100$ k Ω to 2.5 V ⁽³⁾	25°C		135		dB
V_n Equivalent input noise voltage	$f = 1$ kHz, $V_{IC} = 1$ V	25°C		45		nV/ $\sqrt{\text{Hz}}$
I_n Equivalent input noise current	$f = 1$ kHz	25°C		0.18		pA/ $\sqrt{\text{Hz}}$
THD Total harmonic distortion	$f = 1$ kHz, $A_V = -2$, $R_L = 10$ k Ω , $V_O = 4.1$ V _{p-p}	25°C		0.01		%

(1) Connected as voltage follower with 1-V step input. Value specified is the slower of the positive and negative slew rates.

(2) 40-dB closed-loop dc gain, $C_L = 22$ pF

(3) Each amplifier excited in turn with 1 kHz to produce $V_O = 3$ V_{p-p}

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



LMV8xx 5-V Electrical Characteristics

$V_{CC+} = 5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 2 \text{ V}$, $V_O = 2.5 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xx			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage		25°C	1	3.5	mV	
		-40°C to 85°C		4		
α_{VIO} Average temperature coefficient of input offset voltage		25°C	1		μV/°C	
I_{IB} Input bias current		25°C	40	100	nA	
		-40°C to 85°C		150		
I_{IO} Input offset current		25°C	0.5	30	nA	
		-40°C to 85°C		50		
CMRR Common-mode rejection ratio	$V_{IC} = 0 \text{ to } 4 \text{ V}$	25°C	72	90	dB	
		-40°C to 85°C	70			
$+k_{SVR}$ Positive supply-voltage rejection ratio	$V_{CC+} = 1.7 \text{ V to } 4 \text{ V}$, $V_{CC-} = -1 \text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	75	85	dB	
		-40°C to 85°C	70			
$-k_{SVR}$ Negative supply-voltage rejection ratio	$V_{CC+} = 1.7 \text{ V}$, $V_{CC-} = -1 \text{ V to } -3.3 \text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	73	85	dB	
		-40°C to 85°C	70			
V_{ICR} Common-mode input voltage range	CMRR ≥ 50 dB	25°C	-0.2 to 4.2	-0.3 to 4.3	V	
A_V Large-signal voltage amplification	$R_L = 600 \Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 4.5 \text{ V}$	Sourcing	25°C	95	105	dB
			-40°C to 85°C	90		
	$R_L = 600 \Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 0.5 \text{ V}$	Sinking	25°C	95	105	
			-40°C to 85°C	90		
	$R_L = 2 \text{ k}\Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 4.5 \text{ V}$	Sourcing	25°C	95	105	
			-40°C to 85°C	90		
	$R_L = 2 \text{ k}\Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 0.5 \text{ V}$	Sinking	25°C	95	105	
			-40°C to 85°C	90		
V_O Output swing	$V_{CC+} = 5 \text{ V}$, $R_L = 600 \Omega$ to 2.5 V	High level	25°C	4.75	4.84	V
			-40°C to 85°C	4.7		
		Low level	25°C		0.17 0.25	
			-40°C to 85°C		0.3	
	$V_{CC+} = 5 \text{ V}$, $R_L = 2 \text{ k}\Omega$ to 2.5 V	High level	25°C	4.85	4.9	
			-40°C to 85°C	4.8		
		Low level	25°C		0.1 0.15	
			-40°C to 85°C		0.2	
I_O Output current	$V_O = 0 \text{ V}$	Sourcing	25°C	20	45	mA
			-40°C to 85°C	15		
	$V_O = 5 \text{ V}$	Sinking	25°C	20	40	
			-40°C to 85°C	15		
I_{CC} Supply current	LMV821		25°C	0.3	0.4	mA
			-40°C to 85°C		0.6	
	LMV822 (both amplifiers)		25°C	0.5	0.7	
			-40°C to 85°C		0.9	
	LMV824 (all four amplifiers)		25°C	1	0.3	
			-40°C to 85°C		1.5	

LMV8xx 5-V Electrical Characteristics (continued)
 $V_{CC+} = 5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 2 \text{ V}$, $V_O = 2.5 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xx			UNIT
			MIN	TYP	MAX	
SR Slew rate	$V_{CC+} = 5 \text{ V}$ ⁽¹⁾	25°C	1.4	1.9		V/ μs
GBW Gain bandwidth product	(2)	25°C		5.5		MHz
Φ_m Phase margin	(2)	25°C		64.2		deg
Gain margin	(2)	25°C		8.7		dB
Amplifier-to-amplifier isolation	$V_{CC+} = 5 \text{ V}$, $R_L = 100 \text{ k}\Omega$ to 2.5 V ⁽³⁾	25°C		135		dB
V_n Equivalent input noise voltage	$f = 1 \text{ kHz}$, $V_{IC} = 1 \text{ V}$	25°C		42		nV/ $\sqrt{\text{Hz}}$
I_n Equivalent input noise current	$f = 1 \text{ kHz}$	25°C		0.2		pA/ $\sqrt{\text{Hz}}$
THD Total harmonic distortion	$f = 1 \text{ kHz}$, $A_V = -2$, $R_L = 10 \text{ k}\Omega$, $V_O = 4.1 \text{ V}_{\text{p-p}}$	25°C		0.01		%

(1) Connected as voltage follower with 3-V step input. Value specified is the slower of the positive and negative slew rates.

(2) 40-dB closed-loop dc gain, $C_L = 22 \text{ pF}$

(3) Each amplifier excited in turn with 1 kHz to produce $V_O = 3 \text{ V}_{\text{p-p}}$

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



LMV8xxI 5-V Electrical Characteristics

$V_{CC+} = 5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 2 \text{ V}$, $V_O = 2.5 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xxI			UNIT
			MIN	TYP	MAX	
V_{IO} Input offset voltage		25°C	1	3.5	mV	
		–40°C to 125°C	5.5			
α_{VIO} Average temperature coefficient of input offset voltage		25°C	1		μV/°C	
I_{IB} Input bias current		25°C	40	100	nA	
		–40°C to 125°C	150			
I_{IO} Input offset current		25°C	0.5	30	nA	
		–40°C to 125°C	50			
CMRR Common-mode rejection ratio	$V_{IC} = 0 \text{ to } 4 \text{ V}$	25°C	72	90	dB	
		–40°C to 125°C	70			
$+k_{SVR}$ Positive supply-voltage rejection ratio	$V_{CC+} = 1.7 \text{ V to } 4 \text{ V}$, $V_{CC-} = –1 \text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	75	85	dB	
		–40°C to 125°C	70			
$-k_{SVR}$ Negative supply-voltage rejection ratio	$V_{CC+} = 1.7 \text{ V}$, $V_{CC-} = –1 \text{ V to } –3.3 \text{ V}$, $V_O = 0$, $V_{IC} = 0$	25°C	73	85	dB	
		–40°C to 125°C	70			
V_{ICR} Common-mode input voltage range	CMRR ≥ 50 dB	25°C	–0.2 to 4.2	–0.3 to 4.3	V	
A_V Large-signal voltage amplification	$R_L = 600 \Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 4.5 \text{ V}$	Sourcing	25°C	95	105	dB
			–40°C to 125°C	90		
	$R_L = 600 \Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 0.5 \text{ V}$	Sinking	25°C	95	105	
			–40°C to 125°C	90		
	$R_L = 2 \text{ k}\Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 4.5 \text{ V}$	Sourcing	25°C	95	105	
			–40°C to 125°C	90		
	$R_L = 2 \text{ k}\Omega$ to 2.5 V, $V_O = 2.5 \text{ V to } 0.5 \text{ V}$	Sinking	25°C	95	105	
			–40°C to 125°C	90		
V_O Output swing	$V_{CC+} = 5 \text{ V}$, $R_L = 600 \Omega$ to 2.5 V	High level	25°C	4.75	4.84	V
			–40°C to 125°C	4.6		
		Low level	25°C	0.17	0.25	
			–40°C to 125°C	0.3		
	$V_{CC+} = 5 \text{ V}$, $R_L = 2 \text{ k}\Omega$ to 2.5 V	High level	25°C	4.85	4.9	
			–40°C to 125°C	4.8		
		Low level	25°C	0.1	0.15	
			–40°C to 125°C	0.2		
I_O Output current	$V_O = 0 \text{ V}$	Sourcing	25°C	20	45	mA
			–40°C to 125°C	15		
	$V_O = 5 \text{ V}$	Sinking	25°C	20	40	
			–40°C to 125°C	15		
I_{CC} Supply current	LMV821	25°C	0.3	0.4	mA	
		–40°C to 125°C	0.6			
	LMV822 (both amplifiers)	25°C	0.5	0.7		
		–40°C to 125°C	0.9			
	LMV824 (all four amplifiers)	25°C	1	1.3		
		–40°C to 125°C	1.5			

LMV8xxI 5-V Electrical Characteristics (continued)

$V_{CC+} = 5 \text{ V}$, $V_{CC-} = 0 \text{ V}$, $V_{IC} = 2 \text{ V}$, $V_O = 2.5 \text{ V}$, and $R_L > 1 \text{ M}\Omega$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A	LMV8xxI			UNIT
			MIN	TYP	MAX	
SR Slew rate	$V_{CC+} = 5 \text{ V}$ ⁽¹⁾	25°C	1.4	1.9		$\text{V}/\mu\text{s}$
GBW Gain bandwidth product	(2)	25°C		5.5		MHz
Φ_m Phase margin	(2)	25°C		64.2		deg
Gain margin	(2)	25°C		8.7		dB
Amplifier-to-amplifier isolation	$V_{CC+} = 5 \text{ V}$, $R_L = 100 \text{ k}\Omega$ to 2.5 V ⁽³⁾	25°C		135		dB
V_n Equivalent input noise voltage	$f = 1 \text{ kHz}$, $V_{IC} = 1 \text{ V}$	25°C		42		$\text{nV}/\sqrt{\text{Hz}}$
I_n Equivalent input noise current	$f = 1 \text{ kHz}$	25°C		0.2		$\text{pA}/\sqrt{\text{Hz}}$
THD Total harmonic distortion	$f = 1 \text{ kHz}$, $A_V = -2$, $R_L = 10 \text{ k}\Omega$, $V_O = 4.1 \text{ V}_{\text{p-p}}$	25°C		0.01		%

(1) Connected as voltage follower with 3-V step input. Value specified is the slower of the positive and negative slew rates.

(2) 40-dB closed-loop dc gain, $C_L = 22 \text{ pF}$

(3) Each amplifier excited in turn with 1 kHz to produce $V_O = 3 \text{ V}_{\text{p-p}}$

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005



TYPICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 1.




Figure 2.




Figure 3.




Figure 4.

TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 5.




Figure 6.




Figure 7.




Figure 8.





LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005

 TEXAS
INSTRUMENTS
www.ti.com

TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)



TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 13.




Figure 14.

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005

 TEXAS
INSTRUMENTS
www.ti.com

TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 15.




Figure 16.

TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 17.




Figure 18.

LMV821 SINGLE, LMV822 DUAL, LMV824 QUAD LOW-VOLTAGE RAIL-TO-RAIL OUTPUT OPERATIONAL AMPLIFIERS

SLOS434G—FEBRUARY 2004—REVISED AUGUST 2005

TEXAS
INSTRUMENTS
www.ti.com

TYPICAL CHARACTERISTICS (continued)

$T_A = 25^\circ\text{C}$, $V_{CC+} = 5\text{-V Single Supply}$ (Unless Otherwise Noted)




Figure 19.

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
LMV821DBVR	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DBVRE4	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DBVT	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DBVTE4	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DCKR	ACTIVE	SC70	DCK	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DCKRE4	ACTIVE	SC70	DCK	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DCKT	ACTIVE	SC70	DCK	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821DCKTE4	ACTIVE	SC70	DCK	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDBVR	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDBVRE4	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDBVT	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDBVTE4	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDCKR	ACTIVE	SC70	DCK	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDCKRE4	ACTIVE	SC70	DCK	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDCKT	ACTIVE	SC70	DCK	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV821IDCKTE4	ACTIVE	SC70	DCK	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822D	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822DE4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822DGKR	ACTIVE	MSOP	DGK	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822DR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822DRE4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822IDE4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822IDGKR	ACTIVE	MSOP	DGK	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV822IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
LMV822IDRE4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824D	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824DE4	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824DGVR	ACTIVE	TVSOP	DGV	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824DGVRE4	ACTIVE	TVSOP	DGV	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824DR	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824DRE4	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824ID	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IDE4	ACTIVE	SOIC	D	14	50	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IDGVR	ACTIVE	TVSOP	DGV	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IDGVRE4	ACTIVE	TVSOP	DGV	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IDR	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IDRE4	ACTIVE	SOIC	D	14	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IPW	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IPWE4	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IPWR	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824IPWRE4	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824PW	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824PWE4	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824PWR	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
LMV824PWRE4	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(³) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


MECHANICAL DATA

MPDS006C – FEBRUARY 1996 – REVISED AUGUST 2000

DGV (R-PDSO-G**)

24 PINS SHOWN

PLASTIC SMALL-OUTLINE




- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15 per side.
 - D. Falls within JEDEC: 24/48 Pins – MO-153
14/16/20/56 Pins – MO-194

MECHANICAL DATA

DBV (R-PDSO-G5)

PLASTIC SMALL-OUTLINE PACKAGE




4073253-4/J 10/2005

- NOTES:
- All linear dimensions are in millimeters.
 - This drawing is subject to change without notice.
 - Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0,15 per side.
 - Falls within JEDEC MO-178 Variation AA.

MECHANICAL DATA

DCK (R-PDSO-G5)

PLASTIC SMALL-OUTLINE PACKAGE




4093553-2/E 10/2005

- NOTES:
- All linear dimensions are in millimeters.
 - This drawing is subject to change without notice.
 - Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
 - Falls within JEDEC MO-203 variation AA.

MECHANICAL DATA

DGK (S-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE




- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body dimensions do not include mold flash or protrusion.
 - D. Falls within JEDEC MO-187 variation AA.

MECHANICAL DATA

D (R-PDSO-G14)

PLASTIC SMALL-OUTLINE PACKAGE




4040047-3/F 07/2004

- NOTES:
- All linear dimensions are in inches (millimeters).
 - This drawing is subject to change without notice.
 - Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
 - Falls within JEDEC MS-012 variation AB.

MECHANICAL DATA

D (R-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE



4040047-2/F 07/2004

- NOTES:
- All linear dimensions are in inches (millimeters).
 - This drawing is subject to change without notice.
 - Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0.15).
 - Falls within JEDEC MS-012 variation AA.


MECHANICAL DATA

MTSS001C – JANUARY 1995 – REVISED FEBRUARY 1999

PW (R-PDSO-G**)

14 PINS SHOWN

PLASTIC SMALL-OUTLINE PACKAGE



4040064/F 01/97

- NOTES: A. All linear dimensions are in millimeters.
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
 D. Falls within JEDEC MO-153

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265