

Philips Semiconductors

Product specification


Damper diode
fast, high-voltage

BY459X-1500, BY459X-1500S

FEATURES

- Low forward volt drop
- Fast switching
- Soft recovery characteristic
- High thermal cycling performance
- Isolated mounting tab

SYMBOL



QUICK REFERENCE DATA

$V_R = 1500 \text{ V}$
$V_F \leq 1.2 \text{ V} / 1.25 \text{ V}$
$I_{F(\text{peak})} = 12 \text{ A} (\text{f} = 48 \text{ kHz})$
$I_{F(\text{peak})} = 10 \text{ A} (\text{f} = 82 \text{ kHz})$
$I_{FSM} \leq 100 \text{ A}$
$t_{rr} \leq 350 \text{ ns} / 220 \text{ ns}$

GENERAL DESCRIPTION


Glass-passivated double diffused rectifier diode featuring fast forward recovery and low forward recovery voltage. The device is intended for use in HDTV receivers and multi-sync monitor horizontal deflection circuits.

The BY459X series is supplied in the conventional leaded SOD113 package.

PINNING

PIN	DESCRIPTION
1	cathode
2	anode
tab	isolated

SOD113



LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{RSM}	Peak non repetitive reverse voltage		-	1500	V
V_{RRM}	Peak repetitive reverse voltage		-	1500	V
V_{RWM}	Crest working reverse voltage		-	1300	V
$I_{F(\text{peak})}$	Peak working forward current	$f = 48 \text{ kHz};$ $f = 82 \text{ kHz};$	-	-1500	A
			-	12	A
			-	-	A
			-	10	A
I_{FRM}	Peak repetitive forward current	$t = 100 \mu\text{s}$	-	100	A
$I_{F(\text{RMS})}$	RMS forward current		-	30	A
I_{FSM}	Peak non-repetitive forward current	$t = 10 \text{ ms}$ $t = 8.3 \text{ ms}$ sinusoidal; $T_j = 150^\circ\text{C}$ prior to surge; with reapplied $V_{RWM(\text{max})}$	-	100	A
			-	110	A
T_{stg}	Storage temperature		-40	150	°C
T_j	Operating junction temperature		-	150	°C

Damper diode
fast, high-voltage

BY459X-1500, BY459X-1500S

ISOLATION LIMITING VALUE & CHARACTERISTIC $T_{hs} = 25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{isol}	R.M.S. isolation voltage from both terminals to external heatsink	$f = 50\text{-}60\text{ Hz}$; sinusoidal waveform; $R.H. \leq 65\%$; clean and dustfree	-		2500	V
C_{isol}	Capacitance from both terminals to external heatsink	$f = 1\text{ MHz}$	-	10	-	pF

THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j-hs}$	Thermal resistance junction to heatsink	with heatsink compound	-	-	4.8	K/W
$R_{th\ j-a}$	Thermal resistance junction to ambient	without heatsink compound in free air.	-	55	5.9	K/W

STATIC CHARACTERISTICS $T_j = 25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP.		MAX.		UNIT
			BY459X-	1500	1500S	1500	
V_F	Forward voltage	$I_F = 6.5\text{ A}$	0.95	1.05	1.30	1.35	V
	Reverse current	$I_F = 6.5\text{ A}; T_j = 125^\circ\text{C}$ $V_R = 1300\text{ V}$ $V_R = 1300\text{ V}; T_j = 125^\circ\text{C}$	0.85	0.95	1.20	1.25	V

DYNAMIC CHARACTERISTICS $T_j = 25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	TYP.		MAX.		UNIT
			BY459X-	1500	1500S	1500	
t_{rr}	Reverse recovery time	$I_F = 1\text{ A}, V_R \geq 30\text{ V};$	0.25	0.17	0.35	0.22	μs
	Reverse recovery charge	$I_F = 2\text{ A}, -dI_F/dt = 20\text{ A}/\mu\text{s}$	2.0	0.70	3.0	0.95	μC
	Peak forward recovery voltage	$I_F = 6.5\text{ A}, dI_F/dt = 50\text{ A}/\mu\text{s}$	8.0	11.0	14.0	19.0	V
	Forward recovery time	$I_F = 6.5\text{ A}, dI_F/dt = 50\text{ A}/\mu\text{s}$	170	200	250	300	ns

Damper diode fast, high-voltage

BY459X-1500, BY459X-1500S




Fig.1. Definition of V_{fr} and t_{fr}




Fig.4. Maximum allowable pulse width t_p versus line frequency; Basic horizontal deflection circuit.




Fig.2. Definition of t_{rr} and Q_s




Fig.5. BY459X-1500 Typical and maximum forward characteristic $I_F = f(V_F)$; parameter T_j




Fig.3. Basic horizontal deflection circuit.





Fig.6. BY459X-1500S Typical and maximum forward characteristic $I_F = f(V_F)$; parameter T_j

**Damper diode
fast, high-voltage****BY459X-1500, BY459X-1500S**

Damper diode fast, high-voltage

BY459X-1500, BY459X-1500S

MECHANICAL DATA

Dimensions in mm

Net Mass: 2 g




Fig.8. SOD113; The seating plane is electrically isolated from all terminals.

Notes

1. Refer to mounting instructions for F-pack envelopes.
2. Epoxy meets UL94 V0 at 1/8".

Damper diode
fast, high-voltage

BY459X-1500, BY459X-1500S

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	
© Philips Electronics N.V. 1998	
All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.	
The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.