




BYV12...BYV16

Vishay Telefunken

Fast Silicon Mesa Rectifiers

Features

- Glass passivated junction
- Hermetically sealed package
- Soft recovery characteristic
- Low reverse current



Applications

Fast rectifier and switch for example for TV-line output circuits and switch mode power supply

94 9539

Absolute Maximum Ratings

T_j = 25°C

Parameter	Test Conditions	Type	Symbol	Value	Unit
Reverse voltage =Repetitive peak reverse voltage		BYV12	V _R =V _R RM	100	V
		BYV13	V _R =V _R RM	400	V
		BYV14	V _R =V _R RM	600	V
		BYV15	V _R =V _R RM	800	V
		BYV16	V _R =V _R RM	1000	V
Peak forward surge current	t _p =10ms, half sinewave		I _{FSM}	40	A
Repetitive peak forward current			I _{FRM}	9	A
Average forward current	φ=180°, T _{amb} =25°C		I _{FAV}	1.5	A
Junction and storage temperature range			T _j =T _{stg}	-65...+175	°C

Maximum Thermal Resistance

T_j = 25°C

Parameter	Test Conditions	Symbol	Value	Unit
Junction ambient	l=10mm, T _L =constant	R _{thJA}	45	K/W
	on PC board with spacing 25mm	R _{thJA}	100	K/W

Electrical Characteristics

T_j = 25°C

Parameter	Test Conditions	Type	Symbol	Min	Typ	Max	Unit
Forward voltage	I _F =1A		V _F			1.5	V
Reverse current	V _R =V _R RM		I _R		1	5	μA
	V _R =V _R RM, T _j =150°C		I _R		60	150	μA
Reverse recovery time	I _F =0.5A, I _R =1A, i _R =0.25A		t _{rr}			300	ns
Reverse recovery charge	I _F =1A, di/dt=5A/μs		Q _{rr}			200	nC




BYV12...BYV16

Vishay Telefunken




Characteristics ($T_j = 25^\circ\text{C}$ unless otherwise specified)




94 9101

Figure 1. Typ. Thermal Resistance vs. Lead Length




94 9517

Figure 4. Junction Temperature vs. Reverse/Repetitive Peak Reverse Voltage




94 9519

Figure 2. Max. Average Forward Current vs. Ambient Temperature




94 9521

Figure 5. Reverse Current vs. Junction Temperature




94 9518

Figure 3. Max. Average Forward Current vs. Ambient Temperature




94 9520

Figure 6. Max. Forward Current vs. Forward Voltage



94 9523


Figure 7. Typ. Diode Capacitance vs. Reverse Voltage



94 9522

Figure 8. Thermal Response

Dimensions in mm





Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems
with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Telefunken products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Telefunken against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423