


TOSHIBA CMOS DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TC4S584F

SCHMITT TRIGGER

TC4S584F is the one circuit inverter having the schmitt trigger function at the input terminal.

That is, since the circuit threshold level voltage at the leading and trailing edges of input waveform are different (V_P , V_N), the TC4S584F can be used in the broad range application, including line receiver, waveform shaping circuit, astable multivibrator, etc. In addition to ordinary inverter.




SSOP5-P-0.95

Weight : 0.016g (Typ.)


MAXIMUM RATINGS

| CHARACTERISTIC | SYMBOL | RATING | UNIT |
|-----------------------------|-----------|----------------------------------|-------------|
| DC Supply Voltage | V_{DD} | $V_{SS} - 0.5 \sim V_{SS} + 20$ | V |
| Input Voltage | V_{IN} | $V_{SS} - 0.5 \sim V_{DD} + 0.5$ | V |
| Output Voltage | V_{OUT} | $V_{SS} - 0.5 \sim V_{DD} + 0.5$ | V |
| DC Input Current | I_{IN} | ± 10 | mA |
| Power Dissipation | P_D | 200 | mW |
| Operating Temperature Range | T_{opr} | $-40 \sim 85$ | $^{\circ}C$ |
| Storage Temperature Range | T_{stg} | $-65 \sim 150$ | $^{\circ}C$ |
| Lead Temperature (10s) | T_L | 260 | $^{\circ}C$ |


LOGIC DIAGRAM



MARKING



PIN ASSIGNMENT (TOP VIEW)



961001EBA2

TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.



RECOMMENDED OPERATING CONDITIONS (V_{SS} = 0V)

| CHARACTERISTIC | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
|-------------------|-----------------|------|------|------|-----------------|---|
| DC Supply Voltage | V _{DD} | — | 3 | — | 18 | V |
| Input Voltage | V _{IN} | — | 0 | — | V _{DD} | V |

STATIC ELECTRICAL CHARACTERISTICS (V_{SS} = 0V)

| CHARACTERISTIC | SYM-BOL | TEST CONDITION | V _{DD} (V) | - 40°C | | 25°C | | | 85°C | | UNIT | |
|-------------------------------------|-----------------|--|------------------------|--------|------|-------|-------|-------------------|-------|------|------|----|
| | | | | MIN. | MAX. | MIN. | TYP. | MAX. | MIN. | MAX. | | |
| High-Level Output Voltage | V _{OH} | I _{OUT} < 1μA V _{IN} = V _{SS} , V _{DD} | 5 | 4.95 | — | 4.95 | 5.00 | — | 4.95 | — | V | |
| | | | 10 | 9.95 | — | 9.95 | 10.00 | — | 9.95 | — | | |
| | | | 15 | 14.95 | — | 14.95 | 15.00 | — | 14.95 | — | | |
| Low-Level Output Voltage | V _{OL} | I _{OUT} < 1μA V _{IN} = V _{SS} , V _{DD} | 5 | — | 0.05 | — | 0.00 | 0.05 | — | 0.05 | V | |
| | | | 10 | — | 0.05 | — | 0.00 | 0.05 | — | 0.05 | | |
| | | | 15 | — | 0.05 | — | 0.00 | 0.05 | — | 0.05 | | |
| Output High Current | I _{OH} | V _{OH} = 4.6V V _{OH} = 2.5V V _{OH} = 9.5V V _{OH} = 13.5V V _{IN} = V _{SS} , V _{DD} | 5 | -0.61 | — | -0.51 | -1.0 | — | -0.42 | — | mA | |
| | | | 5 | -2.5 | — | -2.1 | -4.0 | — | -1.7 | — | | |
| | | | 10 | -1.5 | — | -1.3 | -2.2 | — | -1.1 | — | | |
| | | | 15 | -4.0 | — | -3.4 | -9.0 | — | -2.8 | — | | |
| Output Low Current | I _{OL} | V _{OL} = 0.4V V _{OL} = 0.5V V _{OL} = 1.5V V _{IN} = V _{SS} , V _{DD} | 5 | 0.61 | — | 0.51 | 1.5 | — | 0.42 | — | mA | |
| | | | 10 | 1.5 | — | 1.3 | 3.8 | — | 1.1 | — | | |
| | | | 15 | 4.0 | — | 3.4 | 15.0 | — | 2.8 | — | | |
| | | | — | — | — | — | — | — | — | — | | |
| Positive Trigger Threshold Voltage* | V _P | V _{OUT} = 0.5V V _{OUT} = 1.0V V _{OUT} = 1.5V | 5 | 1.95 | 3.65 | 2.05 | 2.9 | 3.35 | 2.05 | 3.75 | V | |
| | | | 10 | 4.3 | 7.1 | 4.5 | 5.9 | 7.1 | 4.7 | 7.2 | | |
| | | | 15 | 6.9 | 10.7 | 7.1 | 9.0 | 10.6 | 7.1 | 10.8 | | |
| Negative Trigger Threshold Voltage* | V _N | V _{OUT} = 4.5V V _{OUT} = 9.0V V _{OUT} = 13.5V | 5 | 1.05 | 2.75 | 1.1 | 2.1 | 2.6 | 0.95 | 2.65 | V | |
| | | | 10 | 2.1 | 4.9 | 2.2 | 3.5 | 4.7 | 2.0 | 4.8 | | |
| | | | 15 | 3.2 | 7.0 | 3.3 | 5.0 | 6.8 | 3.1 | 6.9 | | |
| Hysteresis Voltage* | V _H | — | 5 | 0.1 | 1.35 | 0.4 | 0.75 | 1.3 | 0.4 | 1.50 | V | |
| | | | 10 | 1.7 | 3.2 | 1.8 | 2.4 | 3.2 | 1.7 | 3.4 | | |
| | | | 15 | 3.1 | 4.8 | 3.2 | 4.0 | 4.8 | 3.2 | 4.9 | | |
| Input Current | H Level | I _{IH} | V _{IH} = 18V | 18 | — | 0.1 | — | 10 ⁻⁵ | 0.1 | — | 1.0 | μA |
| | L Level | I _{IL} | V _{IL} = 0V | 18 | — | -0.1 | — | -10 ⁻⁵ | -0.1 | — | -1.0 | |
| Quiescent Device Current | I _{DD} | V _{IN} = V _{SS} , V _{DD} | 5 | — | 1 | — | 0.001 | 1 | — | 7.5 | μA | |
| | | | 10 | — | 2 | — | 0.002 | 2 | — | 15 | | |
| | | | 15 | — | 4 | — | 0.004 | 4 | — | 30 | | |

(Note) Values are different to TC4584BP, TC4584BF marked* (V_P, V_N, V_H).


● The products described in this document are subject to foreign exchange and foreign trade control laws.
 ● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
 ● The information contained herein is subject to change without notice.

DYNAMIC ELECTRICAL CHARACTERISTICS (Ta = 25°C, VSS = 0V, CL = 50pF)


| CHARACTERISTIC | SYMBOL | TEST CONDITION | VDD (V) | MIN. | TYP. | MAX. | UNIT |
|---|------------------|----------------|---------|------|------|------|------|
| | | | | | | | |
| Output Transition Time (Low to High) | t _{TLH} | — | 5 | — | 80 | 200 | ns |
| | | | 10 | — | 50 | 100 | |
| | | | 15 | — | 40 | 80 | |
| Output Transition Time (High to Low) | t _{THL} | — | 5 | — | 80 | 200 | ns |
| | | | 10 | — | 50 | 100 | |
| | | | 15 | — | 40 | 80 | |
| Propagation Delay Time | t _{pLH} | — | 5 | — | 170 | 340 | ns |
| | t _{pHL} | | 10 | — | 80 | 160 | |
| | | | 15 | — | 60 | 120 | |
| Input Capacitance | C _{IN} | — | | — | 5 | 7.5 | pF |

CIRCUIT AND WAVEFORM FOR MEASUREMENT OF DYNAMIC CHARACTERISTICS


CIRCUIT




WAVEFORM



INPUT-OUTPUT VOLTAGE CHARACTERISTICS




● INPUT-OUTPUT VOLTAGE WAVEFORM



● TRANSFER CHARACTERISTICS

OUTLINE DRAWING
SSOP5-P-0.95

Unit : mm



Weight : 0.016g (Typ.)