



Continental Device India Limited


An IS/ISO 9002 and IECQ Certified Manufacturer



IS/ISO 9002  
Lic# QSC/L- 000019.2

**NPN COMPLEMENTARY SILICON HIGH VOLTAGE TRANSISTOR**

**CC5551  
(9AW)  
TO-92  
BCE**



**MARKING : NCC  
5551**

**High Voltage NPN Transistor for General Purpose and Telephony Applications**

**ABSOLUTE MAXIMUM RATINGS**

DESCRIPTION	SYMBOL	VALUE	UNIT
Collector -Emitter Voltage	$V_{CEO}$	160	V
Collector -Base Voltage	$V_{CBO}$	180	V
Emitter -Base Voltage	$V_{EBO}$	6.0	V
Collector Current Continuous	$I_C$	600	mA
Power Dissipation @ $T_a=25^\circ\text{C}$	$P_D$	625	mW
Derate Above $25^\circ\text{C}$		5.0	mw/ $^\circ\text{C}$
Power Dissipation @ $T_c=25^\circ\text{C}$	$P_D$	1.5	W
Derate Above $25^\circ\text{C}$		12	mw/ $^\circ\text{C}$
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-55 to +150	$^\circ\text{C}$
<b>THERMAL RESISTANCE</b>			
Junction to Case	$R_{th(j-c)}$	125	$^\circ\text{C/W}$
Junction to Ambient	$R_{th(j-a)}$ (1)	357	$^\circ\text{C/W}$

(1)  $R_{th(j-a)}$  is measured with the device soldered into a typical printed circuit board


**ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$  unless specified otherwise)**

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector -Emitter Voltage	$V_{CEO}$	$I_C=1\text{mA}, I_B=0$	160	-	-	V
Collector -Base Voltage	$V_{CBO}$	$I_C=100\mu\text{A}, I_E=0$	180	-	-	V
Emitter -Base Voltage	$V_{EBO}$	$I_E=10\mu\text{A}, I_C=0$	6.0	-	-	V
Collector-Cut off Current	$I_{CBO}$	$V_{CB}=160\text{V}, I_E=0$	-	-	50	nA
		$T_a=100^\circ\text{C}$				
		$V_{CB}=160\text{V}, I_E=0$	-	-	50	$\mu\text{A}$
Emitter-Cut off Current	$I_{EBO}$	$V_{EB}=4\text{V}, I_C=0$	-	-	50	nA
DC Current Gain	$h_{FE}^*$	$I_C=1\text{mA}, V_{CE}=5\text{V}$	80	-	-	
		$I_C=10\text{mA}, V_{CE}=5\text{V}$	80	-	320	
		$I_C=50\text{mA}, V_{CE}=5\text{V}$	30	-	-	
Collector Emitter Saturation Voltage	$V_{CE(Sat)}^*$	$I_C=10\text{mA}, I_B=1\text{mA}$	-	-	0.15	V
		$I_C=50\text{mA}, I_B=5\text{mA}$	-	-	0.2	V
Base Emitter Saturation Voltage	$V_{BE(Sat)}^*$	$I_C=10\text{mA}, I_B=1\text{mA}$	-	-	1.0	V
		$I_C=50\text{mA}, I_B=5\text{mA}$	-	-	1.0	V



# NPN COMPLEMENTARY SILICON HIGH VOLTAGE TRANSISTOR

**CC5551  
(9AW)  
TO-92  
BCE**




## ELECTRICAL CHARACTERISTICS (Ta=25°C Unless Otherwise Specified)

**CC5551**


DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
<b>Dynamic Characteristics</b>						
Small Signal Current Gain	$h_{fe}$	$I_C=1mA, V_{CE}=10V$ $f=1KHz$	80	-	320	
Transition Frequency	$f_t$	$V_{CE}=10V, I_C=10mA,$ $f=100MHz$	100	-	300	MHz
Output Capacitance	$C_{ob}$	$V_{CB}=10V, I_E=0$ $f=1MHz$	-	-	6.0	pF
Input Capacitance	$C_{ib}$	$V_{EB}=0.5V, I_C=0$ $f=1MHz$	-	-	20	pF
Noise Figure	$N_F$	$V_{CE}=5V, I_C=250\mu A$ $R_S=1k\Omega, f=10Hz$ to 15.7kHz	-	-	8.0	dB

**\*Pulse Test: Pulse Width=300us, Duty Cycle=2%**

**TO-92 Plastic Package**



SEC AA




- PIN CONFIGURATION**
1. BASE
  2. COLLECTOR
  3. EMITTER

All dimensions in mm.

DIM	MIN.	MAX.
A	4.32	5.33
B	4.45	5.20
C	3.18	4.19
D	0.41	0.55
E	0.35	0.50
F	5 DEG	
G	1.14	1.40
H	1.14	1.53
K	12.70	—

**TO-92 Transistors on Tape and Ammo Pack**



All dimensions in mm unless specified otherwise

ITEM	SYMBOL	SPECIFICATION				REMARKS
		MIN.	NOM.	MAX.	TOL.	
BODY WIDTH	A1	4.0		4.8		
BODY HEIGHT	A	4.8		5.2		
BODY THICKNESS	T	3.9		4.2		
PITCH OF COMPONENT	P		12.7		±1	CUMULATIVE PITCH ERROR 1.0 mm/20 PITCH
FEED HOLE PITCH	Po		12.7		±0.3	
FEED HOLE CENTRE TO COMPONENT CENTRE	P2		6.35		±0.4	TO BE MEASURED AT BOTTOM OF CLINCH
DISTANCE BETWEEN OUTER LEADS	F		5.08		+0.6 -0.2	AT TOP OF BODY
COMPONENT ALIGNMENT	Δh		0	1		
TAPE WIDTH	W		18		±0.5	
HOLD-DOWN TAPE WIDTH	Wo		6		±0.2	
HOLE POSITION	W1		9		+0.7 -0.5	
HOLD-DOWN TAPE POSITION	W2		0.5		±0.2	
LEAD WIRE CLINCH HEIGHT	Ho		16		±0.5	
COMPONENT HEIGHT	H1			23.25		
LENGTH OF SNIPPED LEADS	L			11.0		
FEED HOLE DIAMETER	Do		4		±0.2	t1 0.3 - 0.6
TOTAL TAPE THICKNESS	t			1.2		
LEAD - TO - LEAD DISTANCE F1,	F1		2.54		+0.4 -0.1	
CLINCH HEIGHT	H2			3		
PULL - OUT FORCE	(P)		6N			

**NOTES**

1. MAXIMUM ALIGNMENT DEVIATION BETWEEN LEADS NOT TO BE GREATER THAN 0.2 mm.
2. MAXIMUM NON-CUMULATIVE VARIATION BETWEEN TAPE FEED HOLES SHALL NOT EXCEED 1 mm IN 20 PITCHES.
3. HOLDDOWN TAPE NOT TO EXCEED BEYOND THE EDGE(S) OF CARRIER TAPE AND THERE SHALL BE NO EXPOSURE OF ADHESIVE.
4. NO MORE THAN 3 CONSECUTIVE MISSING COMPONENTS ARE PERMITTED.
5. A TAPE TRAILER, HAVING AT LEAST THREE FEED HOLES ARE REQUIRED AFTER THE LAST COMPONENT.
6. SPLICES SHALL NOT INTERFERE WITH THE SPROCKET FEED HOLES.

**Packing Detail**

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-92 Bulk	1K/polybag	200 gm/1K pcs	3" x 7.5" x 7.5"	5.0K	17" x 15" x 13.5"	80.0K	23 kgs
TO-92 T&A	2K/ammo box	645 gm/2K pcs	12.5" x 8" x 1.8"	2.0K	17" x 15" x 13.5"	32.0K	12.5 kgs

### **Disclaimer**

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

**Continental Device India Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290

e-mail [sales@cdil.com](mailto:sales@cdil.com) [www.cdil.com](http://www.cdil.com)