




Continental Device India Limited

An ISO/TS16949 and ISO 9001 Certified Company



NPN SILICON POWER TRANSISTOR

CD13005

TO-220
Plastic Package

Applications

Suitable for Lighting, Switching Regulator and Motor Control

ABSOLUTE MAXIMUM RATINGS

DESCRIPTION	SYMBOL	VALUE	UNIT
Collector Base Voltage	V_{CBO}	600	V
Collector Emitter (sus) Voltage	V_{CEO}	400	V
Emitter Base Voltage	V_{EBO}	9.0	V
Collector Current Continuous	I_C	2.0	A
Peak (1)	I_{CM}	4.0	A
Base Current Continuous	I_B	0.75	A
Peak (1)	I_{BM}	1.5	A
Emitter Current Continuous	I_E	2.25	A
Peak (1)	I_{EM}	4.5	A
Power Dissipation @ $T_a=25^\circ C$	P_D	1.4	W
Derate Above 25°C		11.2	mW/ °C
Power Dissipation @ $T_c=25^\circ C$	P_D	60	W
Derate Above 25°C		480	mW/ °C
Operating And Storage Junction Temperature Range	T_j, T_{stg}	- 65 to +150	°C

THERMAL RESISTANCE

Junction to Case	$R_{th(j-c)}$	2.08	°C/W
Junction to Ambient	$R_{th(j-a)}$	89	°C/W
Maximum Lead Temperature for Soldering Purpose: 1/8" from Case for 5 Seconds	T_L	275	°C


(1) Pulse Test: Pulse Width=5ms, Duty Cycle=10%

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ C$ unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector Base Voltage	V_{CBO}	$I_C=1mA, I_E=0$	600	-	-	V
Collector Emitter (sus) Voltage	$*V_{CEO(sus)}$	$I_C=10mA, I_B=0$	400	-	-	V
Collector Cut Off Current	I_{CBO}	$V_{CB}=600V, I_E=0$ $V_{CB}=600V, I_E=0, T_c=100^\circ C$	-	-	1.0 5.0	mA
Emitter Cut Off Current	I_{EBO}	$V_{EB}=9V, I_C=0$	-	-	1.0	mA

NPN SILICON POWER TRANSISTOR

CD13005



TO-220
Plastic Package

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
DC Current Gain	$^*\text{h}_{\text{FE}}$	$^{**}\text{I}_C=0.5\text{A}, \text{V}_{\text{CE}}=5\text{V}$ $\text{I}_C=2\text{A}, \text{V}_{\text{CE}}=5\text{V}$	8	-	40	
Collector Emitter Saturation Voltage	$^*\text{V}_{\text{CE}(\text{sat})}$	$\text{I}_C=0.5\text{A}, \text{I}_B=0.1\text{A}$ $\text{I}_C=1\text{A}, \text{I}_B=0.25\text{A}$ $\text{I}_C=1.5\text{A}, \text{I}_B=0.5\text{A}$ $\text{I}_C=1\text{A}, \text{I}_B=0.25\text{A}, \text{T}_c=100^\circ\text{C}$	-	-	0.5	V
Base Emitter Saturation Voltage	$^*\text{V}_{\text{BE}(\text{sat})}$	$\text{I}_C=0.5\text{A}, \text{I}_B=0.1\text{A}$ $\text{I}_C=1\text{A}, \text{I}_B=0.25\text{A}$ $\text{I}_C=1\text{A}, \text{I}_B=0.25\text{A}, \text{T}_c=100^\circ\text{C}$	-	-	1.0	V
			-	-	1.2	V
			-	-	1.1	V

DYNAMIC CHARACTERISTICS

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Current Gain Bandwidth Product	f_T	$\text{I}_C=100\text{mA}, \text{V}_{\text{CE}}=10\text{V},$ $f=1\text{MHz}$	4.0	-	-	MHz
Output Capacitance	C_{ob}	$\text{V}_{\text{CB}}=10\text{V}, f=0.1\text{MHz}$	-	21	-	pF

SWITCHING TIME

Turn On Time	t_{on}	$\text{V}_{\text{CC}}=125\text{V}, \text{I}_C=1\text{A}, \text{I}_{B1}=0.2\text{A},$ $\text{I}_{B2}=0.2\text{A}$			1.1	μs
Storage Time	t_{stg}				4.0	μs
Fall Time	t_f				0.7	μs

** h_{FE} Classification:-

Note:- Product is pre selected in DC current gain (Groups A to F). CDIL reserves the right to ship any of the groups according to production availability.	A 11-16	B 15-19	C 18-22	E 21-25	F 24-30
MARKING	CD 13005A XY	CD 13005B XY	CD 13005C XY	CD 13005E XY	CD 13005F XY

X= Year of Manufacturer Code
Y= Month Code


*Pulse Test:- PW=300ms, Duty Cycle=2%

CD13005Rev_3 260404E

CD13005


**TO-220
Plastic Package**

TO-220 Plastic Package



DIM	MIN	MAX
A	14.42	16.51
B	9.63	10.67
C	3.56	4.83
D	—	0.90
E	1.15	1.40
F	3.75	3.88
G	2.29	2.79
H	2.54	3.43
J	—	0.56
K	12.70	14.73
L	2.80	4.07
M	2.03	2.92
N	—	31.24
O	7 DEG	


All dimensions in mm.



Pin Configuration


1. Base
2. Collector
3. Emitter
4. Collector

TO-220 Tube Packing



All Dimensions in mm

AMMO PACK SIZE



Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-220	200 pcs/polybag 50 pcs/tube	396 gm/200 pcs 120 gm/50 pcs	3" x 7.5" x 7.5" 3.5" x 3.7" x 21.5"	1.0K 1.0K	17" x 15" x 13.5" 19" x 19" x 19"	16.0K 10.0K	36 kgs 29 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com