查询CM200DU-34KA供应商
捷多邦，专业PCB打样工厂，24小时加急出货

POWEREX

CM200DU-34KA

Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

Dual IGBTMOD™ KA-Series Module

200 Amperes/1700 Volts



Outline Drawing and Circuit Diagram

Description:
Powerex IGBTMOD™ Modules are designed for use in switching applications. Each module consists of two IGBT Transistors in a half-bridge configuration with each transistor having a reverse-connected super-fast recovery free-wheel diode. All components and interconnects are isolated from the heat sinking baseplate, offering simplified system assembly and thermal management.

Features:
- ☐ Low Drive Power
- ☐ Low $V_{CE(sat)}$
- ☐ Discrete Super-Fast Recovery Free-Wheel Diode
- ☐ Isolated Baseplate for Easy Heat Sinking

Applications:
- ☐ AC Motor Control
- ☐ Motion/Servo Control
- ☐ UPS
- ☐ Welding Power Supplies
- ☐ Laser Power Supplies

Ordering Information:
Example: Select the complete module number you desire from the table - i.e. CM200DU-34KA is a 1700V (V_{CES}), 200 Ampere Dual IGBTMOD™ Power Module.

Type	Current Rating Amperes	V_{CES} Volts (x 50)
CM	200	34

Dimensions	Inches	Millimeters
A	4.33	110.0
B	3.15	80.0
C	1.14 +0.04/-0.02	29.0 +1.0/-0.5
D	3.66±0.01	93.0±0.25
E	2.44±0.01	62.0±0.25
F	0.83	21.0
G	0.16	4.0
H	0.24	6.0
J	0.59	15.0
K	0.55	14.0

Dimensions	Inches	Millimeters
M	0.33	8.5
N	0.10	2.5
P	0.85	21.6
Q	0.98	25.0
R	0.86	21.75
S	M6	M6
T	0.26 Dia.	6.5 Dia.
V	0.02	0.5
W	0.110	2.79
X	1.08	27.35

找PDF 维库一下 pdf.dzsc.com

Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM200DU-34KA
Dual IGBTMOD™ KA-Series Module
200 Amperes/1700 Volts

Absolute Maximum Ratings, T_j = 25 °C unless otherwise specified

Ratings	Symbol	CM200DU-34KA	Units
Junction Temperature	T_j	-40 to 150	°C
Storage Temperature	T_{stg}	-40 to 125	°C
Collector-Emitter Voltage (G-E SHORT)	V_{CES}	1700	Volts
Gate-Emitter Voltage (C-E SHORT)	V_{GES}	±20	Volts
Collector Current (T_c = 25°C)	I_C	200	Amperes
Peak Collector Current	I_{CM}	400*	Amperes
Emitter Current** (T_c = 25°C)	I_E	200	Amperes
Peak Emitter Current**	I_{EM}	400*	Amperes
Maximum Collector Dissipation (T_c = 25°C, $T_j \leq$ 150°C)	P_c	1100	Watts
Mounting Torque, M6 Main Terminal	–	40	in-lb
Mounting Torque, M6 Mounting	–	40	in-lb
Weight	–	580	Grams
Isolation Voltage (Main Terminal to Baseplate, AC 1 min.)	V_{iso}	3500	Volts

* Pulse width and repetition rate should be such that the device junction temperature (T_j) does not exceed $T_{j(max)}$ rating.
**Represents characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDi).

Static Electrical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Cutoff Current	I_{CES}	$V_{CE} = V_{CES}$, V_{GE} = 0V	–	–	1	mA
Gate Leakage Current	I_{GES}	$V_{GE} = V_{GES}$, V_{CE} = 0V	–	–	0.5	µA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	I_C = 20mA, V_{CE} = 10V	4.0	5.5	7.0	Volts
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C = 200A, V_{GE} = 15V, T_j = 25°C	–	3.2	4.0	Volts
		I_C = 200A, V_{GE} = 15V, T_j = 125°C	–	3.8	–	Volts
Total Gate Charge	Q_G	V_{CC} = 1000V, I_C = 200A, V_{GE} = 15V	–	900	–	nC
Emitter-Collector Voltage**	V_{EC}	I_E = 200A, V_{GE} = 0V, T_j = 25°C	–	–	4.6	Volts
		I_E = 200A, V_{GE} = 0V, T_j = 125°C	–	2.2	–	Volts

**Represents characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDi).

Dynamic Electrical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics		Symbol	Test Conditions	Min.	Typ.	Max.	Units
Input Capacitance		C_{ies}	V_{CE} = 10V, V_{GE} = 0V	–	–	29.0	nf
Output Capacitance		C_{oes}		–	–	4.8	nf
Reverse Transfer Capacitance		C_{res}		–	–	1.5	nf
Resistive	Turn-on Delay Time	$t_{d(on)}$	V_{CC} = 1000V, I_C = 200A,	–	–	600	ns
Load	Rise Time	t_r	$V_{GE1} = V_{GE2}$ = 15V,	–	–	200	ns
Switch	Turn-off Delay Time	$t_{d(off)}$	R_G = 1.6Ω,	–	–	700	ns
Times	Fall Time	t_f	Inductive Load	–	–	800	ns
Diode Reverse Recovery Time**		t_{rr}	Switching Operation	–	–	600	ns
Diode Reverse Recovery Charge**		Q_{rr}	I_E = 200A	–	9.6	–	µC

**Represents characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDi).

Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM200DU-34KA
Dual IGBTMOD™ KA-Series Module
200 Amperes/1700 Volts

Thermal and Mechanical Characteristics, T_j = 25 °C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case	$R_{th(j-c)}Q$	Per IGBT 1/2 Module	–	–	0.11	°C/W
Thermal Resistance, Junction to Case	$R_{th(j-c)}R$	Per FWDi 1/2 Module	–	–	0.18	°C/W
Contact Thermal Resistance	$R_{th(c-f)}$	Per Module, Thermal Grease Applied	–	0.020	–	°C/W
Thermal Resistance	$R_{th(j-c')}Q$	T_c Measured Point (Under Chips - IGBT Part)	–	–	0.05*	°C/W

* If you use this value, $R_{th(f-a)}$ should be measured just under the chips.

OUTPUT CHARACTERISTICS (TYPICAL)



TRANSFER CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)



CAPACITANCE VS. V_{CE} (TYPICAL)



Powerex, Inc., 200 E. Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM200DU-34KA
Dual IGBTMOD™ KA-Series Module
200 Amperes/1700 Volts

HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)



REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



GATE CHARGE, V_{GE}



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (IGBT)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (FWDi)