查询CM30MD1-12H供应商
捷多邦，专业PCB打样工厂，24小时加急出货

POWEREX

CM30MD1-12H

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CI Module

Three Phase Converter + Three Phase Inverter
30 Amperes/600 Volts



Outline Drawing and Circuit Diagram

Dimensions	Inches	Millimeters
A	4.53	115.0
B	2.36	60.0
C	1.18	30.0
D	0.18	4.5
E	4.13	105.0
F	0.20	5.0
G	0.31	8.0
H	0.59	15.0
J	0.68	17.2
K	0.10	2.54
L	0.40	10.16

Dimensions	Inches	Millimeters
N	0.51	13.0
P	0.59	15.0
Q	1.14	29.0
R	2.28	58.0
S	0.16	4.0
T	0.02	0.6
U	0.22	5.5
V	0.08	2.0
W	0.02	0.6
X	0.35	9.0
Y	0.25	6.3



Description:
Powerex CI Modules are designed for use in switching applications. Each module consists of a three phase diode converter section and a three phase IGBT inverter section. All components and interconnects are isolated from the heat sinking baseplate, offering simplified system assembly and thermal management.

Features:
- ☐ Low Drive Power
- ☐ Low $V_{CE(sat)}$
- ☐ Discrete Super-Fast Recovery (70ns) Free-Wheel Diodes
- ☐ High Frequency Operation (20-25 kHz)
- ☐ Isolated Baseplate for Easy Heat Sinking

Applications:
- ☐ AC Motor Control
- ☐ Motion/Servo Control
- ☐ General Purpose Inverters
- ☐ Robotics

Ordering Information:
Example: Select the complete nine digit module part number you desire from the table below - i.e. CM30MD1-12H is a 600V (V_{CES}), 30 Ampere CI Power Module.

Type	Current Rating Amperes	VCES Volts (x 50)
CM	30	12

找PDF 维库一下 pdf.dzsc.com

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM30MD1-12H
CI Module
Three Phase Converter + Three Phase Inverter
30 Amperes/600 Volts

Absolute Maximum Ratings, T_j = 25°C unless otherwise specified

Characteristics	Symbol	CM30MD1-12H	Units
Power Device Junction Temperature	T_j	-40 to 150	°C
Storage Temperature	T_{stg}	-40 to 125	°C
Mounting Torque, M4 Mounting Screws	—	13	in-lb
Module Weight (Typical)	—	100	Grams
Isolation Voltage, AC 1 minute, 60Hz	V_{RMS}	2500	Volts
Converter Part			
Repetitive Peak Reverse Voltage	V_{RRM}	800	Volts
Recommended AC Input Voltage	E_a	220	Volts
DC Output Current	I_O	30	Amperes
Surge (Non-repetitive) Forward Current	I_{FSM}	550	Amperes
I^2t for Fusing	I^2t	1.2×10^3	A^2s
IGBT Inverter Part			
Collector-Emitter Voltage (G-E Short)	V_{CES}	600	Volts
Gate-Emitter Voltage (C-E Short)	V_{GES}	±20	Volts
Collector Current	I_C	30	Amperes
Collector Current (Pulse)*	I_{CM}	60	Amperes
Emitter Current**	I_E	30	Amperes
Emitter Current** (Pulse)*	I_{EM}	60	Amperes
Maximum Collector Dissipation	P_C	66	Watts

Electrical and Mechanical Characteristics, T_j = 25°C unless otherwise specified

Characteristics		Symbol	Test Conditions	Min.	Typ.	Max.	Units
Converter Sector							
Repetitive Reverse Current		I_{RRM}	$V_R = V_{RRM}$, T_j = 150°C	—	—	8	mA
Forward Voltage Drop		V_{FM}	I_F = 30A	—	—	1.5	Volts
Thermal Resistance (Junction-to-Fin)		$R_{th(j-f)}$	Per Diode	—	—	1.7	°C/W
IGBT Inverter Sector							
Collector Cutoff Current		I_{CES}	$V_{CE} = V_{CES}$, V_{GE} = 0V	—	—	1	mA
Gate-Emitter Threshold Voltage		$V_{GE(th)}$	V_{CE} = 10V, I_C = 3.0mA	4.5	6.0	7.5	Volts
Gate-Emitter Cutoff Current		I_{GES}	$V_{GE} = V_{GES}$, V_{CE} = 0V	—	—	0.5	µA
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	V_{GE} = 15V, I_C = 30A, T_j = 25°C	—	2.1	2.8	Volts
			V_{GE} = 15V, I_C = 30A, T_j = 150°C	—	2.15	—	Volts
Input Capacitance		C_{ies}	V_{GE} = 0V, V_{CE} = 10V	—	—	3.0	nF
Output Capacitance		C_{oes}		—	—	2.4	nF
Reverse Transfer Capacitance		C_{res}		—	—	0.6	nF
Total Gate Charge		Q_G	V_{CC} = 300V, I_C = 30A, V_{GE} = 15V	—	90	—	nC
Resistive	Turn-on Delay Time	$t_{d(on)}$	$V_{GE1} = V_{GE2}$ = 15V,	—	—	120	nS
Load	Rise Time	t_r	V_{CC} = 300V, I_C = 30A,	—	—	300	nS
Switching	Turn-off Delay Time	$t_{d(off)}$	R_g = 21Ω,	—	—	200	nS
Times	Fall Time	t_f	Resistive Load	—	—	300	nS
Emitter-Collector Voltage		V_{EC}	I_E = 30A, V_{GE} = 0V	—	—	2.8	Volts
Reverse Recovery Time		t_{rr}	I_E = 30A, V_{GE} = 0V,	—	—	110	nS
Reverse Recovery Charge		Q_{rr}	di_E/dt = -60A/µs	—	0.08	—	µC
Thermal Resistance (Junction-to-Fin)		$R_{th(j-f)}$	Per IGBT	—	—	1.9	°C/W
			Per FWDi	—	—	2.4	°C/W

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM30MD1-12H
CI Module
Three Phase Converter + Three Phase Inverter
30 Amperes/600 Volts

OUTPUT CHARACTERISTICS (TYPICAL)



TRANSFER CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)



CAPACITANCE VS. V_{CE} (TYPICAL)



HALF-BRIDGE SWITCHING CHARACTERISTICS (TYPICAL)



REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



GATE CHARGE, V_{GE}



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724) 925-7272

CM30MD1-12H
CI Module
Three Phase Converter + Three Phase Inverter
30 Amperes/600 Volts

TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (IGBT)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (FWDi)