



查询CMBTA44供应商

Continental Device India Limited

An ISO/TS16949 and ISO 9001 Certified Company


捷多邦，专业PCB打样工厂，24小时加急出货



NPN SILICON PLANAR EPITAXIAL TRANSISTOR


CMBTA44

SOT-23
Formed SMD Package



PIN CONFIGURATION (NPN)

1 = BASE
2 = EMITTER
3 = COLLECTOR



Marking Code is =3Z

Designed for Extremely High Voltage Applications

ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$)

DESCRIPTION	SYMBOL	VALUE	UNITS
Collector Base Voltage	V_{CBO}	450	V
Collector Emitter Voltage	V_{CEO}	400	V
Emitter Base Voltage	V_{EBO}	6	V
Collector Current	I_C	300	mA
Collector Power Dissipation	P_D	350	mW
Operating And Storage Junction Temperature Range	T_j, T_{stg}	- 65 to +150	$^{\circ}\text{C}$

THERMAL RESISTANCE

Junction to Ambient in free air	$R_{th(j-a)}$	357	$^{\circ}\text{C/W}$
---------------------------------	---------------	-----	----------------------


Electrical Characteristics ($T_a=25^{\circ}\text{C}$ unless specified otherwise)

DESCRIPTION	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut Off Current	I_{CBO}	$V_{CB}=400\text{V}, I_E=0$			100	nA
Collector Cut Off Current	I_{CES}	$V_{CE}=400\text{V}, V_{BE}=0$			500	nA
Emitter Cut Off Current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$			100	nA
Collector Base Voltage	V_{CBO}	$I_C=100\mu\text{A}, I_E=0$	450			V
Collector Emitter Voltage	V_{CES}	$I_C=100\mu\text{A}, V_{BE}=0$	450			V
Collector Emitter Voltage	V_{CEO}	$I_C=1\text{mA}, I_B=0$	400			V
Emitter Base Voltage	V_{EBO}	$I_E=10\mu\text{A}, I_C=0$	6			V
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=1\text{mA}, I_B=0.1\text{mA}$			0.40	V
		$I_C=10\text{mA}, I_B=1\text{mA}$			0.50	V
		$I_C=50\text{mA}, I_B=5\text{mA}$			0.75	V
Base Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=10\text{mA}, I_B=1\text{mA}$			0.75	V
DC Current Gain	h_{FE}	$V_{CE}=10\text{V}, I_C=1\text{mA}$	40		200	
		$V_{CE}=10\text{V}, I_C=10\text{mA}$	50			
		$V_{CE}=10\text{V}, I_C=50\text{mA}$	45			
		$V_{CE}=10\text{V}, I_C=100\text{mA}$	20			
Transition Frequency	f_T	$V_{CE}=10\text{V}, I_C=10\text{mA}, f=10\text{MHz}$	20			MHz
Output Capacitance	C_{ob}	$V_{CB}=20\text{V}, I_E=0, f=1\text{MHz}$			7.0	pF
Input Capacitance	C_{ih}	$V_{EB}=0.5\text{V}, I_C=0, f=1\text{MHz}$			130	pF

CMBTA44


SOT-23
Formed SMD Package

SOT-23 Formed SMD Package



SOT-23 Package Reel Information


Reel Specifications for W Packing (13") and 7"



NOTES:

1. The bandolier of 330 mm reel contains at least 10,000 devices.
2. The bandolier of 180 mm reel contains at least 3,000 devices.
3. No more than 0.5% missing devices / reel. 50 empty compartments for 330 mm reel. 15 empty compartments for 180 mm reel.
4. Three consecutive empty places might be found provided this gap is followed by 6 consecutive devices.
5. The carrier tape (leader) starts with at least 75 empty positions (equivalent to 330 mm). In order to fix the carrier tape a self adhesive tape of 20 to 50 mm is applied. At the end of the bandolier at least 40 empty positions (equivalent to 160 mm) are there.

Tape Specification for SOT-23 Surface Mount Device



All dimensions in mm

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
SOT-23 T&R	3K/reel	136 gm/3K pcs	3" x 7.5" x 7.5"	12 K	17" x 15" x 13.5"	192 K	12 kgs
			9" x 9" x 9"	51 K	19" x 19" x 19"	408 K	28 kgs
	10K/reel	415 gm/10K pcs	13" x 13" x 0.5"	10 K	17" x 15" x 13.5"	300 K	16 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com