

# CT 3232M

## Low Power Driver / Receiver

### For MIL-STD-1553 & Macair

#### Features

- 1.5 Watt Total Hybrid Dissipation at 25% Transmitting Duty Cycle
- Monolithic Design
- Compatible with MIL-STD-1553A/B & Macair A3818, A5232, A5690 & A4905
- Meets MIL-STD-1553B
- TTL Compatible
- Full Military (-55°C to +125°C) Temperature Range
- Driver / Receiver in a single Package for Space & Weight Savings
- Filtering on Receiver to Improve S/N Ratio of System
- Pin for Pin interchangeable with CT3231 Series
- Packaging – Hermetic Metal Plug-In or Flat Package
  - 24 Lead, 1.27" sq. max x .2" Ht Flat package
  - 24 Pin, 1.27" sq. max x .175" Ht Plug-In package



#### DRIVER DESCRIPTION

The CT3232 Driver section accepts complementary TTL Data at the input, and produces a 30 Volt nominal peak-to-peak differential signal across a 140Ω load at the output. When coupled to the Data Bus with a 1:1 transformer, isolated on the Data Bus side with two 55.0Ω fault isolation resistors, and loaded by two 70Ω terminations plus additional receivers, the Data Bus signal produced is 7.2 Volts nominal peak-to-peak.

When both "DATA" and " $\overline{\text{DATA}}$ " inputs are held low or both are held high, the driver output becomes a high impedance and is "removed" from the line. In addition, an overriding "INHIBIT" input provides for removal of the Driver output from the line. A logic "1" applied to the "INHIBIT" takes priority over the condition of the data inputs and disables the Driver. See Driver Logic Waveforms, Figure 3.


DATA and  $\overline{\text{DATA}}$  inputs must be complementary waveforms, of 50% duty cycle average, with no gate delays between them.

#### RECEIVER DESCRIPTION

The CT3232 Receiver section accepts Bi-Phase Differential data at the input and produces two TTL signals at the output. The outputs are "DATA" and " $\overline{\text{DATA}}$ ", and represent positive and negative excursions (respectively) of the input beyond a predetermined threshold. See Receiver Logic Waveforms, Figure 2.

The positive and negative thresholds may be internally set by grounding the appropriate pins, or externally set with resistors. The pre-set internal thresholds will detect Data Bus signals exceeding 1Volt p-p and ignore signals less than 0.5Volt p-p when used with 1:1 transformer (See Figure 4 for a suitable transformer and typical connection).

A low level at the STROBE input inhibits the DATA and  $\overline{\text{DATA}}$  outputs. If unused, a 2KΩ pull-up to +5V is recommended.



**Figure 1 – CT3232 Functional Block Diagram and Pinouts**

## Absolute Maximum Ratings

Parameter	Range	Units
Supply Voltage, Pin 4 or 13	-0.3 to +18.0	Volts
Supply Voltage, Pin 24 or 19	0.3 to -18.0	Volts
Supply Voltage, Pin 20	-0.3 to + 7.0	Volts
Logic Input Voltage, Pin 8, 21, 22, or 23	-0.3 to +5.5V	Volts
Receiver Differential Input, Pin 15 to Pin 16	±20 (40 Vp-p)	Volts
Receiver Input Voltage, Pin 15 or Pin 16	±15	Volts
Driver Peak Output Current, Pin 1 or Pin 2	±300	mA
Total Package Power Dissipation at (Ambient) TA = + 25°C (Derate above TA = + 25°C at 40 mW/°C)	4.0 (Note 1)	Watts
Power Dissipation at Specified Case Temperatures	See Figure 5	
Operating Case Temperature Range (Tc) (See Figure 5 for limitations)	-55 to +125	°C

## Electrical Characteristics

Parameter / Condition	Sym	Min	Typ	Max	Unit
-----------------------	-----	-----	-----	-----	------

### Receiver

Power Supply Voltage Ranges		VCCR <sub>X</sub> VEER <sub>X</sub> VCCL	+11.75 -11.75 +4.75	- - -	+15.75 -15.75 +5.25	V V V
Supply Current		ICCR <sub>X</sub> IEER <sub>X</sub> ICCL	- - -	25 30 35	- - -	mA mA mA
Differential Input Impedance	f = 1MHz	Z <sub>IN</sub>	9K	-	-	Ω
Differential Voltage Range		V <sub>IDR</sub>	±20	-	-	V <sub>peak</sub>
Input Common Mode Voltage Range		V <sub>ICR</sub>	±10	-	-	V <sub>peak</sub>
Common Mode Rejection Ratio (From Point A, Fig. 4)		CMRR	40	-	-	dB
Strobe Characteristics (Logic "0" inhibits Output)						
"0" Input Current (V strobe = 0.5 V)		I <sub>IL</sub>	-	-	-4	mA
"1" Input Current (V strobe = 2.7 V)		I <sub>IH</sub>	-	-	400	μA
"0" Input Voltage		V <sub>IL</sub>	-	-	0.7	V
"1" Input Voltage		V <sub>IH</sub>	2.0	-	-	V
Strobe Delay (turn-on or turn-off)		t <sub>SD</sub>	-	20	-	ns
Threshold Characteristics (Sinewave input, 100KHz to 1MHz)						
Note: Threshold voltages are referred to the Input						
Internal (Pin 6 & 11 grounded)		V <sub>TH1</sub>	0.6	-	1.0	Vp-p
External (Pin 6 & 11 open; threshold setting resistors from Pin 5 to ground & from Pin 12 to ground; R <sub>TH</sub> Max = 10KΩ)		R <sub>TH</sub> /V <sub>TH1</sub>	-	4000	-	Ω/Vp-p
Filter Characteristics (Pin 6 & 11 Grounded)						
(Sinewave input)		f = 2MHz f = 3MHz	V <sub>TH2</sub> V <sub>TH3</sub>	1.0 3.0	- -	Vp-p Vp-p

## Electrical Characteristics con't

Parameter / Condition	Sym	Min	Typ	Max	Unit
-----------------------	-----	-----	-----	-----	------

### Receiver con't

Output Characteristics, RX Data & $\overline{\text{Data}}$ “1” State (ISOURCE = -0.4 mA) Note 2 “0” State (ISINK = 4 mA) Note 2 <i>Note: With Receiver input below threshold, both RX Data &amp; RX <math>\overline{\text{Data}}</math> outputs remain in “1” state.</i> Delay (average) from differential input zero crossings to RX Data & RX $\overline{\text{Data}}$ output 50% points.	VOH	2.5	3.3	-	V
	VOL	-	-	0.5	V
	tDRX	-	290	450	ns

Note 1: Assumes unit in free air (natural convection cooling).

### Driver

Power Supply Voltage Ranges (See Receiver Section for VCCL)		VCCTX VEETXL	+11.75 -11.75	- -	+15.75 -15.75	V V
Supply Current, “Standby” mode (See Receiver Section for ICCL) (TX Inhibit high; or TX Data & TX $\overline{\text{Data}}$ both high or both low)		ICCTXS IEETXS	- -	12 0	Note 2 1.0	mA mA
Supply Current transmitting at 1MHz into a 35Ω load at point A in Figure 4  (Iccl limits do not change with mode of operation or duty cycle)	Duty Cycle	ICC25	Note 4	45	Note 2	mA
	25%	IEEX25	Note 3	35	Note 2	mA
	100%	VCCTX IEETX	Note 4 Note 3	150 135	Note 2 Note 2	mA mA
Input Characteristics, TX Data In or TX $\overline{\text{Data}}$ In		IILD	-	-	-1.2	mA
“0” Input Current (VIN = 0.4 V)		IiHD	-	-	100	μA
“1” Input Current (VIN = 2.7 V)		VILD	-	-	0.7	V
“0” Input Voltage		ViHD	2.0	-	-	V
“1” Input Voltage						
Inhibit Characteristic		IILI	-	-	-0.8	mA
“0” Input Current (VIN = 0.4 V)		IiHi	-	-	50	μA
“1” Input Current (VIN = 2.7 V)		VILI	-	-	0.7	V
“0” Input Voltage		ViHi	2.0	-	-	V
“1” Input Voltage						
Delay from TX Inhibit (0 $\overline{\text{O}}$ 1) to inhibited output impedance		tDXOFF	-	300	450	ns
Delay from TX $\overline{\text{Inhibit}}$ (1 $\overline{\text{O}}$ 0) to active output impedance		tDXON	-	100	350	ns
Differential output noise, inhibit mode		VNOI	-	-	10	mVPEAK
Differential output impedance (inhibited) at 1MHz		ZOI	10K	-	-	Ω
Output Characteristics (Figure 3)		VO	28	32	35	Vp-p
Differential output level (140 ohm load)		ZOA	-	-	10	Ω
Differential Active output impedance at 1MHz		tr / tF	200	-	300	ns
Rise and Fall times (10% to 90% of p-p output)		VOS	-	±20	±75	mVpeak
Output offset at point A in Fig. 4 (35Ω load) 2.5μS after mid-bit crossing of the parity bit of the last word of a 660μS message						
Delay from 50% point of TX Data or TX $\overline{\text{Data}}$ input to zero crossing of differential output		tDTX	-	220	350	ns

Note 2: Maximum supply currents for driver and receiver combined are included in power and thermal data table.

## Electrical Characteristics con't

Parameter / Condition	Sym	Min	Typ	Max	Unit
-----------------------	-----	-----	-----	-----	------


### Power and Thermal Data, Total Hybrid (Driver and Receiver)

Total Supply Current, "Standby" mode or transmitting at less than 1% duty cycle (e.g. 20μS of transmission every 2mS or longer interval)		ICCS	-	40	50	mA
		IEES	-	30	40	mA
		ICCL	-	35	45	mA
Total Supply Current transmitting at 1MHz into a 35Ω load at point A in Figure 4  (ICCL limits do not change with mode of operation or duty cycle)	Duty Cycle	ICC25	Note 4	70	80	mA
	25%	IEE25	Note 4	65	75	mA
	100%	ICC100	Note 4	175	190	mA
		IEE100	Note 3	165	180	mA
Power Dissipation of most critical (hottest) device in hybrid during continuous transmission (100% duty cycle)	<u>Supply Voltage</u> ±12V ±15V	PC12	Note 3	300	400	mA
		PC15	Note 3	450	600	mA
Thermal Resistance, junction-to-case, of most critical device		ØJC	-	80	100	°C / W
Allowable transmitting duty cycle when case is held to +100°C maximum		Note 5	-	-	100	%
Allowable transmitting duty cycle when case is held to +125°C maximum	<u>Supply Voltage</u> ±12V ±15V	Note 5	-	-	80	%
		Note 5	-	-	55	%


Note 3: Decreases linearly to zero at zero duty cycle.

Note 4: Decreases linearly to applicable "Standby" value at zero duty cycle.


Note 5: Based upon operating junction temperature of 160°C for hottest device. For lower operating junction temperatures, reduce maximum duty cycle accordingly.



**Figure 2 – Receiver Logic Waveforms**



### Figure 5 – Typical Power Dissipation (Total Hybrid)



Notes:1. Dimensions shown are in inches.  
2. Pins are equally spaced at .100 ±.002 tolerance non-cumulative each row.

**Figure 6 – Package Outline Drawings**

Pin #	Function	Pin #	Function
1	Tx Data Out	13	+VCCR <sub>X</sub>
2	Tx $\overline{\text{Data}}$ Out	14	NC
3	Ground C	15	Rx Data In
4	+VCC <sub>TX</sub>	16	Rx $\overline{\text{Data}}$ In
5	Ext. Data Threshold	17	Ground A
6	Int. Data Threshold	18	Case
7	Rx Data Out	19	-VEER <sub>X</sub>
8	Strobe	20	+VCCL (+5V)
9	Ground B	21	Tx Inhibit
10	Rx $\overline{\text{Data}}$ Out	22	Tx Data In
11	Int. $\overline{\text{Data}}$ Threshold	23	Tx $\overline{\text{Data}}$ In
12	Ext. $\overline{\text{Data}}$ Threshold	24	-VEET <sub>X</sub>

**Table I – CT3232 Pin Out Description (Plug-In & Flat Package)**



### Ordering Information

Model Number	Screening	Package
CT3232M	Military Temperature, -55°C to +125°C, Screened to the Individual Test Methods of MIL-STD-883	Plug-In
CT3232MFP		Flat Package

**Specifications subject to change without notice**

The information contained in this data sheet is believed to be accurate; however, Aeroflex Laboratories Incorporated assumes no responsibility for its use, and no license or rights are granted by implication or otherwise in connection therewith.

**Aeroflex Circuit Technology**  
**35 South Service Road**  
**Plainview New York 11803**  
**www.aeroflex.com**

**Telephone: (516) 694-6700**  
**FAX: (516) 694-6715**  
**Toll Free Inquiries: (800) THE-1553**  
**E-Mail: sales-act@aeroflex.com**