


SMD Ultra Fast Recovery Rectifier

COMCHIP
www.comchip.com.tw

CURA101 Thru CURA107

Reverse Voltage: 50 - 1000 Volts
Forward Current: 1.0 Amp




Features

- Ideal for surface mount applications
- Easy pick and place
- Plastic package has Underwriters Lab. flammability classification 94V-0
- Ultra fast recovery time: 50 - 75 nS
- Low leakage current

Mechanical data

- Case: Mini SMA/SOD-123 molded plastic
- Terminals: solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Mounting position: Any
- Approx. Weight: 0.063 gram



Maximum Ratings and Electrical Characteristics

Parameter	Symbol	CURA 101	CURA 102	CURA 103	CURA 104	CURA 105	CURA 106	CURA 107	Unit
Max. Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Max. DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Max. RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Peak Surge Forward Current 8.3ms single half sine-wave superimposed on rateload (JEDEC method)	I _{FSM}	30							A
Max. Average Forward Current	I _O	1.0							A
Max. Instantaneous Forward Current at 1.0 A	V _F	1.0			1.3	1.7			V
Reverse recovery time	T _{rr}	50				75			nS
Max. DC Reverse Current at Rated DC Blocking Voltage Ta=25℃ Ta=100℃	I _R	5.0 50							uA
Max. Thermal Resistance (Note 1)	R _{θJA}	42							℃/W
Operating Junction Temperature	T _j	-55 to +150							℃
Storage Temperature	T _{STG}	-55 to +150							℃

Note 1: Thermal resistance from junction to ambient.

Rating and Characteristic Curves (CURA101 Thru CURA107)

Fig. 1 - Reverse Characteristics




Fig.2 - Forward Characteristics




Fig. 3 - Junction Capacitance




Fig. 4 - Non Repetitive Forward Surge Current




Fig. 5 - Test Circuit Diagram and Reverse Recovery Time Characteristics





Fig. 6 - Current Derating Curve

