


## 225107-000 Product Details



**225107-000**

TE Internal Number: 225107-000

 [Active](#)

### SolderSleeve Wire Splices

 [Always ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Wire Splice
- Splice Type = SolderSleeve
- CMA (Min.-Max) = 4,800 - 9,000 CMA
- Fluid Resistance = Immersion
- Wire Temperature Rating Range (Max.) = 125° C to 150° C

[View all Features](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">SolderSleeve Wire Splice</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul> <p style="text-align: right;"><a href="#">List all Documents</a></p>

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Product Type = Wire Splice</li> <li>• Splice Type = SolderSleeve</li> <li>• Connection Type = Solder</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• Fluid Resistance = Immersion</li> </ul> <p><b>Housing Related Features:</b></p> <ul style="list-style-type: none"> <li>• CMA (Min.-Max) (CMA [mm<sup>2</sup>]) = 4,800 - 9,000 [2.40 - 4.50]</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li> <li>• RoHS/ELV Compliance History = Always was ELV compliant</li> </ul>	<p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• Wire Temperature Rating Range (Max.) = 125° C to 150° C</li> <li>• Operating Temperature (Max.) (°C) = 150</li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• Application = Wire to Wire Splicing</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Raychem</li> </ul>