





**SEME
LAB**
D1022UK**METAL GATE RF SILICON FET****MECHANICAL DATA**

PIN 1	SOURCE (COMMON)	PIN 2	DRAIN 1
PIN 3	DRAIN 2	PIN 4	GATE 2
PIN 5	GATE 1		

DIM	mm	Tol.	Inches	Tol.
A	6.45	0.13	0.254	0.005
B	1.65R	0.13	0.65R	0.005
C	45°	5°	45°	5°
D	16.51	0.76	0.650	0.03
E	6.47	0.13	0.255	0.005
F	18.41	0.13	0.725	0.005
G	1.52	0.13	0.060	0.005
H	4.82		0.190	
I	24.76	0.13	0.975	0.005
J	1.52	0.13	0.060	0.005
K	0.81R	0.13	0.032R	0.005
M	0.13	0.02	0.005	0.001
N	2.16	0.13	0.085	0.005

**GOLD METALLISED
MULTI-PURPOSE SILICON
DMOS RF FET
100W – 28V – 500MHz
PUSH–PULL**

FEATURES

- SIMPLIFIED AMPLIFIER DESIGN
- SUITABLE FOR BROAD BAND APPLICATIONS
- LOW C_{rss}
- SIMPLE BIAS CIRCUITS
- LOW NOISE
- HIGH GAIN – 10 dB MINIMUM

APPLICATIONS

- HF/VHF/UHF COMMUNICATIONS
from 1 MHz to 500 MHz

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^\circ\text{C}$ unless otherwise stated)

P_D	Power Dissipation	292W
BV_{DSS}	Drain – Source Breakdown Voltage	70V
BV_{GSS}	Gate – Source Breakdown Voltage	$\pm 20\text{V}$
$I_{D(sat)}$	Drain Current	15A
T_{stg}	Storage Temperature	-65 to 150°C
	Maximum Operating Junction Temperature	200°C



**SEME
LAB**

D1022UK

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^\circ\text{C}$ unless otherwise stated)

Parameter	Test Conditions		Min.	Typ.	Max.	Unit
PER SIDE						
BV_{DSS}	Drain–Source Breakdown Voltage	$V_{GS} = 0$	$I_D = 100\text{mA}$	70		V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 28\text{V}$	$V_{GS} = 0$		3	mA
I_{GSS}	Gate Leakage Current	$V_{GS} = 20\text{V}$	$V_{DS} = 0$		1	μA
$V_{GS(\text{th})}$	Gate Threshold Voltage*	$I_D = 10\text{mA}$	$V_{DS} = V_{GS}$	1	7	V
g_{fs}	Forward Transconductance*	$V_{DS} = 10\text{V}$	$I_D = 3\text{A}$	2.4		mhos
$V_{GS(\text{th})\text{match}}$	Gate Threshold Voltage Matching Between Sides	$I_D = 10\text{mA}$	$V_{DS} = V_{GS}$		0.1	V
TOTAL DEVICE						
G_{PS}	Common Source Power Gain	$P_O = 100\text{W}$ $V_{DS} = 28\text{V}$ $f = 500\text{MHz}$	$I_{DQ} = 1.2\text{A}$	10		dB
η	Drain Efficiency			50		%
VSWR	Load Mismatch Tolerance			20:1		—
PER SIDE						
C_{iss}	Input Capacitance	$V_{DS} = 28\text{V}$	$V_{GS} = -5\text{V}$	$f = 1\text{MHz}$	180	pF
C_{oss}	Output Capacitance	$V_{DS} = 28\text{V}$	$V_{GS} = 0$	$f = 1\text{MHz}$	90	pF
C_{rss}	Reverse Transfer Capacitance	$V_{DS} = 28\text{V}$	$V_{GS} = 0$	$f = 1\text{MHz}$	7.5	pF

* Pulse Test: Pulse Duration = 300 μs , Duty Cycle $\leq 2\%$


HAZARDOUS MATERIAL WARNING

The ceramic portion of the device between leads and metal flange is beryllium oxide. Beryllium oxide dust is highly toxic and care must be taken during handling and mounting to avoid damage to this area.

THESE DEVICES MUST NEVER BE THROWN AWAY WITH GENERAL INDUSTRIAL OR DOMESTIC WASTE.

THERMAL DATA

$R_{THj-\text{case}}$	Thermal Resistance Junction – Case	Max. 0.6°C / W
-----------------------	------------------------------------	----------------



**SEME
LAB**

D1022UK




Figure 1
Power Output and Efficiency vs. Input





Figure 2
Power Output and Gain vs. Input Power

OPTIMUM SOURCE AND LOAD IMPEDANCE


Frequency MHz	Z_S Ω	Z_L Ω
500	$2.0 - j2.2$	$2.6 - j0.6$

N.B. Impedances measured terminal to terminal



**SEME
LAB**

D1022UK



D1022UK 500MHz TEST FIXTURE

- | | |
|------------|---|
| T1, 6 | 7cm UT85 50 Ohm semi-rigid coax on Siemens B62152A1x1 2 hole ferrite core |
| T2, 3,4, 5 | 7.7 cm UT85-15 15 ohm semi-rigid coax |
| L1 | 6 turns 19swg enamelled copper wire, 3.5mm internal diameter |
| L2 | 8.5 turns 19swg enamelled copper wire on Fair-rite FT82 ferrite core |