

Network Surge Suppressor

Essential protection for data and communication lines



Model #: DB25-ALL

- ▶ Complete serial port (DB25) surge protection
- ▶ Protects against the effects of electrostatic discharge, faulty wiring and lightning
- ▶ Lifetime product warranty
- ▶ Heavy duty grounding lead

DESCRIPTION

Tripp Lite's DB25-ALL offers dataline surge suppression for any DB25 serial port, regardless of cable configurations. Connects and protects all 25 pins plus D shell chassis for universal protection of any DB25 application. User configurable for use with male or female captive DB25 port. Convenient DB25 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface connections, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Lifetime warranty.

SUPPRESSION: Reversible DB9 m/f jacks, protects pins 1-25 and chassis, 18V clamping

KEY BUYING POINTS

- DB25 protects 25 pin serial connections for dataline surge suppression of data terminal, data communications equipment and PCs, printers, modems and more
- Reversible for use with male or female captive DB25 ports
- Offers protection on all 25 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- Lifetime product warranty

TYPICAL APPLICATIONS

- Ideal for the protection of data terminals, data communications equipment, PCs, printers, modems and more.

PACKAGE INCLUDES

- DB25-ALL dataline protector
- Instruction manual and warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	Protects any RS-232 DB25 serial port, regardless of cable configuration. Self-programming to your application. User configurable for male or female captive ports.
DATALINE SURGE SUPPRESSION	
Additional Dataline protection:	Protects pins 1 through 25 and chassis of a DB25 port. Peak pulse clamping voltage - 18V. Max current 340 amps. Shunt capacity <30pF.

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.