

Surface Mount

Directional Couplers

NEW!

DBTC-75-OHMS SERIES

6 to 20 dB Coupling 75Ω 5 to 1500 MHz


Features

- very flat coupling
- very broadband, multi octave
- temperature stable, BLUE CELL™ base
- all welded construction
- leads attached for better solderability
- micro-miniature coupler
- protected by U.S. Patent 6,140,887 & 6,784,521



No Leads

CASE STYLE: AT790-1
PRICE: \$1.99 ea. QTY (25)
\$1.69 ea. QTY (1000)



Leads

CASE STYLE: AT1030
PRICE: \$2.14 ea. QTY (25)
\$1.84 ea. QTY (1000)

Applications

- cable TV

Directional Coupler Electrical Specifications

MODEL NO.	FREQ. RANGE (MHz) f_1 - f_2	COUPLING (dB)		MAINLINE LOSS* (dB)				THEORETICAL LOSS (dB)	DIRECTIVITY (dB)				VSWR** (:1)	POWER INPUT, W									
		Nom.	Max. Flatness	L Typ.	L Max.	M Typ. Max.	U Typ. Max.		U Typ. Max.	L Typ. Min.	M Typ. Min.	U Typ. Min.		U Typ. Min.	L Max.	MU Max.							
DBTC-6-4-75	5-1250	6.8±0.3	±0.8	2.2	3.1	2.2	2.6	2.3	2.8	2.3	2.9	1.02	15	13	17	13	16	10	12	7	1.40	0.5	1.0
DBTC-10-4-75	5-1000	10.5±0.5	±0.7	1.5	2.2	1.4	2.0	1.5	2.0	—	—	0.40	21	16	20	13	16	—	—	—	1.30	0.5	1.0
DBTC-13-5-75	5-1000 1000-1500	13.2±0.5 13.6±0.5	±0.6 ±0.8	0.9	1.4	1.0	1.5	1.1	1.6	—	—	0.21	21	17	19	14	18	—	—	—	1.30	0.5	1.0
DBTC-16-5-75	5-1000 1000-1500	16.3±0.5 16.5±0.5	±0.7 ±0.7	1.2	2.0	1.0	1.5	1.1	1.6	—	—	0.10	22	16	21	13	20	—	—	—	1.30	1.0	1.0
DBTC-18-4-75	5-1000	18.2±0.5	±0.7	0.8	1.5	0.8	1.4	1.0	1.6	—	—	0.07	25	16	21	14	15	—	—	—	1.30	1.0	1.0
DBTC-20-4-75	5-1250	20.5±0.5	±0.9	0.4	0.7	0.6	0.9	0.8	1.2	1.1	1.5	0.04	20	16	19	13	11	7	9	6	1.40	0.5	1.0

* Includes theoretical loss at coupled port

** For coupled port VSWR above 500 MHz, 1.6:1 typ.

L = low range [f_1 to 10 f_1]

M = mid range [10 f_1 to $f_2/2$]

U = upper range [$f_2/2$ to f_2]

MU = 1000-1250 MHz

To order models with leads, add "L" suffix to model No.

Pin Connections


INPUT	3
OUTPUT	4
COUPLED	1
GROUND	2
NOT USED*	5,6

*pins 5&6 must be isolated


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

Outline Drawing



Demo Board MCL P/N: TB-279 Suggested PCB Layout (PL-151)



NOTE: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350 WITH DIELECTRIC THICKNESS 0.030" ± 0.002", COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT
- ▨ DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Reflow Solder Assembly

Silver-bearing solder (Sn/Pb/Ag 62/36/2%) is recommended; however, tin-lead eutectic (Sn/Pb 63/37%) may be used. For temperature profiles, see Application Note AN-40-004

Outline Dimensions (inch/mm)

Case Style	A	B	C	D	E	F	G	H	J	K	L	wt. grams
AT790-1	.150	.150	.150	.050	.030	.025	.028	.050	.160	.030	—	.10
AT1030	.166	.150	.155	.050	.037	.025	.012	.060	.184	.030	.004	.10

REV. G	M89618	ED-104888/1
DBTC-6-4-75L	ED-104888C/1	ED-8953/1
DBTC-10-4-75L	ED-8953A/1	ED-8957/1
DBTC-13-5-75L	ED-8967/1	ED-8967A/1
DBTC-16-5-75L	ED-8978A/1	ED-8978B/1
DBTC-18-4-75L	ED-8956A/1	ED-10793/1
DBTC-20-4-75L	ED-10793A/1	

DBTC-75L-OHMS SERIES

